



Magnum-X

Extremely slim and easy to handle heavy duty lifting sling ideal for small crane hooks

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
Magnum-X 5t 2m	5000	5	2	1.0	36	6	0.94
Magnum-X 5t 3m	5000	5	3	1.0	36	6	1.41
Magnum-X 5t 4m	5000	5	4	1.0	36	6	1.88
Magnum-X 5t 5m	5000	5	5	1.0	36	6	2.35
Magnum-X 5t 6m	5000	5	6	1.0	36	6	2.82
Magnum-X 5t 7m	5000	5	7	1.0	36	6	3.29
Magnum-X 5t 8m	5000	5	8	1.0	36	6	3.76
Magnum-X 5t 10m	5000	5	10	1.0	36	6	4.7
Magnum-X 5t 12m	5000	5	12	1.0	36	6	5.64
Magnum-X 10t 2m	10000	10	2	2	67	11	1.8
Magnum-X 10t 2.5m	10000	10	2.5	2	67	11	2.25
Magnum-X 10t 3m	10000	10	3	2	67	11	2.7
Magnum-X 10t 4m	10000	10	4	2	67	11	4.1
Magnum-X 10t 5m	10000	10	5	2	67	11	5
Magnum-X 10t 6m	10000	10	6	2	67	11	5.9
Magnum-X 10t 7m	10000	10	7	2	67	11	6.8
Magnum-X 10t 8m	10000	10	8	2	67	11	7.7
Magnum-X 10t 10m	10000	10	10	2	67	11	9.5
Magnum-X 10t 12m	10000	10	12	2	67	11	10.8



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
Magnum-X 20t 2.5m	20000	20	2.5	2	88	13	4.5
Magnum-X 20t 3m	20000	20	3	2	88	13	5.4
Magnum-X 20t 4m	20000	20	4	2	88	13	7.7
Magnum-X 20t 5m	20000	20	5	2	88	13	9.5
Magnum-X 20t 6m	20000	20	6	2	88	13	11.3
Magnum-X 20t 7m	20000	20	7	2	88	13	13.1
Magnum-X 20t 8m	20000	20	8	2	88	13	14.9
Magnum-X 20t 12m	20000	20	12	2	88	13	21.6
Magnum-X 25t 4m	25000	25	4	2	85	17	10.1
Magnum-X 25t 5m	25000	25	5	2	85	17	12.5
Magnum-X 25t 6m	25000	25	6	2	85	17	14.9
Magnum-X 25t 7m	25000	25	7	2	85	17	17.3
Magnum-X 25t 8m	25000	25	8	2	85	17	19.7
Magnum-X 30t 2m	30000	30	2	2	91	23	6.54
Magnum-X 30t 2.5m	30000	30	2.5	2	91	23	5.75
Magnum-X 30t 3m	30000	30	3	2	91	23	6.9
Magnum-X 30t 4m	30000	30	4	2	91	23	12.1
Magnum-X 30t 5m	30000	30	5	2	91	23	15
Magnum-X 30t 6m	30000	30	6	2	91	23	17.9
Magnum-X 30t 7m	30000	30	7	2	91	23	20.8



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
Magnum-X 30t 8m	30000	30	8	2	91	23	23.7
Magnum-X 30t 9m	30000	30	9	2	91	23	20.7
Magnum-X 30t 10m	30000	30	10	2	91	23	29.5
Magnum-X 30t 12m	30000	30	12	2	91	23	27.6
Magnum-X 40t 2.5m	40000	40	2.5	2	101	25	8.75
Magnum-X 40t 3m	40000	40	3	2	101	25	10.5
Magnum-X 40t 4m	40000	40	4	2	101	25	16.1
Magnum-X 40t 5m	40000	40	5	2	101	25	20
Magnum-X 40t 6m	40000	40	6	2	101	25	23.9
Magnum-X 40t 7m	40000	40	7	2	101	25	27.8
Magnum-X 40t 8m	40000	40	8	2	101	25	31.7
Magnum-X 40t 10m	40000	40	10	2	101	25	39.5
Magnum-X 40t 12m	40000	40	12	2	101	25	42
Magnum-X 50t 3m	50000	50	3	2	143	24	15.6
Magnum-X 50t 4m	50000	50	4	2	143	24	21.3
Magnum-X 50t 5m	50000	50	5	2	143	24	26.5
Magnum-X 50t 6m	50000	50	6	2	143	24	31.7
Magnum-X 50t 7m	50000	50	7	2	143	24	36.9
Magnum-X 50t 8m	50000	50	8	2	143	24	42.1
Magnum-X 50t 10m	50000	50	10	2	143	24	52.5



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
Magnum-X 50t 12m	50000	50	12	2	143	24	62.4
Magnum-X 50t 13m	50000	50	13	2	143	24	-
Magnum-X 60t 4m	60000	60	4	3	142	26	28.9
Magnum-X 60t 5m	60000	60	5	3	142	26	36
Magnum-X 60t 6m	60000	60	6	3	142	26	43.1
Magnum-X 60t 7m	60000	60	7	3	142	26	50.2
Magnum-X 60t 8m	60000	60	8	3	142	26	57.3
Magnum-X 60t 10m	60000	60	10	3	142	26	71.5
Magnum-X 60t 12m	60000	60	12	3	142	26	69.6
Magnum-X 80t 4m	80000	80	4	3	207	21	38.1
Magnum-X 80t 5m	80000	80	5	3	207	21	47.5
Magnum-X 80t 6m	80000	80	6	3	207	21	56.9
Magnum-X 80t 7m	80000	80	7	3	207	21	66.3
Magnum-X 80t 8m	80000	80	8	3	207	21	75.7
Magnum-X 80t 10m	80000	80	10	3	207	21	94.5
Magnum-X 80t 12m	80000	80	12	3	207	21	98.4
Magnum-X 100t 4m	100000	100	4	3	291	20	54.9
Magnum-X 100t 5m	100000	100	5	3	291	20	68.5
Magnum-X 100t 6m	100000	100	6	3	291	20	82.1
Magnum-X 100t 7m	100000	100	7	3	291	20	95.7



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
Magnum-X 100t 8m	100000	100	8	3	291	20	109.3
Magnum-X 100t 10m	100000	100	10	3	291	20	136.5
Magnum-X 100t 12m	100000	100	12	3	291	20	141.6
Magnum-X 125t 4m	125000	125	4	3	280	31	75.3
Magnum-X 125t 5m	125000	125	5	3	280	31	94
Magnum-X 125t 6m	125000	125	6	3	280	31	112.7
Magnum-X 125t 7m	125000	125	7	3	280	31	131.4
Magnum-X 125t 8m	125000	125	8	3	280	31	150.1
Magnum-X 125t 10m	125000	125	10	3	280	31	187.5
Magnum-X 125t 12m	125000	125	12	3	280	31	224.4
Magnum-X 150t 4m	150000	150	4	5	314	33	80.5
Magnum-X 150t 5m	150000	150	5	5	314	33	100.5
Magnum-X 150t 6m	150000	150	6	5	314	33	120.5
Magnum-X 150t 7m	150000	150	7	5	314	33	140.5
Magnum-X 150t 8m	150000	150	8	5	314	33	160.5
Magnum-X 150t 10m	150000	150	10	5	314	33	200.5
Magnum-X 150t 12m	150000	150	12	5	314	33	240

Item Name short	Weight per Meter [kg/m]	Colour
Magnum-X 5t 2m	0.47	Red
Magnum-X 5t 3m	0.47	Red



Item Name short	Weight per Meter [kg/m]	Colour
Magnum-X 5t 4m	0.47	Red
Magnum-X 5t 5m	0.47	Red
Magnum-X 5t 6m	0.47	Red
Magnum-X 5t 7m	0.47	Red
Magnum-X 5t 8m	0.47	Red
Magnum-X 5t 10m	0.47	Red
Magnum-X 5t 12m	0.47	Red
Magnum-X 10t 2m	0.93	Orange
Magnum-X 10t 2.5m	0.93	Orange
Magnum-X 10t 3m	0.93	Orange
Magnum-X 10t 4m	0.93	Orange
Magnum-X 10t 5m	0.93	Orange
Magnum-X 10t 6m	0.93	Orange
Magnum-X 10t 7m	0.93	Orange
Magnum-X 10t 8m	0.93	Orange
Magnum-X 10t 10m	0.93	Orange
Magnum-X 10t 12m	0.93	Orange
Magnum-X 20t 2.5m	2.05	Orange
Magnum-X 20t 3m	2.05	Orange
Magnum-X 20t 4m	2.05	Orange
Magnum-X 20t 5m	2.05	Orange
Magnum-X 20t 6m	2.05	Orange
Magnum-X 20t 7m	2.05	Orange
Magnum-X 20t 8m	2.05	Orange
Magnum-X 20t 12m	2.05	Orange
Magnum-X 25t 4m	2.72	Orange



Item Name short	Weight per Meter [kg/m]	Colour
Magnum-X 25t 5m	2.72	Orange
Magnum-X 25t 6m	2.72	Orange
Magnum-X 25t 7m	2.72	Orange
Magnum-X 25t 8m	2.72	Orange
Magnum-X 30t 2m	3.27	Orange
Magnum-X 30t 2.5m	3.27	Orange
Magnum-X 30t 3m	3.27	Orange
Magnum-X 30t 4m	3.27	Orange
Magnum-X 30t 5m	3.27	Orange
Magnum-X 30t 6m	3.27	Orange
Magnum-X 30t 7m	3.27	Orange
Magnum-X 30t 8m	3.27	Orange
Magnum-X 30t 9m	3.27	Orange
Magnum-X 30t 10m	3.27	Orange
Magnum-X 30t 12m	3.27	Orange
Magnum-X 40t 2.5m	3.5	Orange
Magnum-X 40t 3m	3.5	Orange
Magnum-X 40t 4m	3.5	Orange
Magnum-X 40t 5m	3.5	Orange
Magnum-X 40t 6m	3.5	Orange
Magnum-X 40t 7m	3.5	Orange
Magnum-X 40t 8m	3.5	Orange
Magnum-X 40t 10m	3.5	Orange
Magnum-X 40t 12m	3.5	Orange
Magnum-X 50t 3m	4.83	Orange
Magnum-X 50t 4m	4.83	Orange



Item Name short	Weight per Meter [kg/m]	Colour
Magnum-X 50t 5m	4.83	Orange
Magnum-X 50t 6m	4.83	Orange
Magnum-X 50t 7m	4.83	Orange
Magnum-X 50t 8m	4.83	Orange
Magnum-X 50t 10m	4.83	Orange
Magnum-X 50t 12m	4.83	Orange
Magnum-X 50t 13m	4.83	Orange
Magnum-X 60t 4m	5.83	Orange
Magnum-X 60t 5m	5.83	Orange
Magnum-X 60t 6m	5.83	Orange
Magnum-X 60t 7m	5.83	Orange
Magnum-X 60t 8m	5.83	Orange
Magnum-X 60t 10m	5.83	Orange
Magnum-X 60t 12m	5.83	Orange
Magnum-X 80t 4m	8.17	Orange
Magnum-X 80t 5m	8.17	Orange
Magnum-X 80t 6m	8.17	Orange
Magnum-X 80t 7m	8.17	Orange
Magnum-X 80t 8m	8.17	Orange
Magnum-X 80t 10m	8.17	Orange
Magnum-X 80t 12m	8.17	Orange
Magnum-X 100t 4m	11.8	Orange
Magnum-X 100t 5m	11.8	Orange
Magnum-X 100t 6m	11.8	Orange
Magnum-X 100t 7m	11.8	Orange
Magnum-X 100t 8m	11.8	Orange



Item Name short	Weight per Meter [kg/m]	Colour
Magnum-X 100t 10m	11.8	Orange
Magnum-X 100t 12m	11.8	Orange
Magnum-X 125t 4m	16.25	Orange
Magnum-X 125t 5m	16.25	Orange
Magnum-X 125t 6m	16.25	Orange
Magnum-X 125t 7m	16.25	Orange
Magnum-X 125t 8m	16.25	Orange
Magnum-X 125t 10m	16.25	Orange
Magnum-X 125t 12m	16.25	Orange
Magnum-X 150t 4m	19.75	Orange
Magnum-X 150t 5m	19.75	Orange
Magnum-X 150t 6m	19.75	Orange
Magnum-X 150t 7m	19.75	Orange
Magnum-X 150t 8m	19.75	Orange
Magnum-X 150t 10m	19.75	Orange
Magnum-X 150t 12m	19.75	Orange



ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Dimension L1	5000 kg	10000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg	125000 kg
2 m	2025045	2026603	-	-	2017500 2017500	-	-	-	-	-	-
2.5 m	-	2020987 MGX10/2.5	2020991 MGX20/2.5	-	2020993 MGX30/2.5	2020995 MGX40/2.5	-	-	-	-	-
3 m	2026602	2020989 MGX10/3	2020992	-	2020994 MGX30/3	2020996 MGX40/3	2024598	-	-	-	-
4 m	2010959 2010959	2002763	2002765	2002767	2002769	2002771 MGX40/4	2002773	2002775	2002777	2002779	2002781
5 m	2010960 2010960	2002764	2002766	2002768	2002770	2002772 MGX40/5	2002774	2002776	2002778	2002780	2002782
6 m	2010961 MGX05-6	2003251	2003253	2003255	2003257	2003259 MGX40/6	2003261 MGX50/6	2003263	2003265	2003267	2003269
7 m	2010962	2003252 MGX10/7	2003254 MGX20/7	2003256	2003258 MGX30/7	2003260 MGX40/7	2003262	2003264	2003266	2003268	2003270
8 m	2010963	2003738 MGX10/8	2003739 MGX20/8	2003740	2003741 MGX30/8	2003742 MGX40/8	2003743	2003744	2003745	2003746	2003747
9 m	-	-	-	-	2014794 2014794	-	-	-	-	-	-
10 m	2014758	2014760	-	-	2014765	2014767	2014769	2014771	2014773	2014775	2014777
12 m	2014759	2014761	2014763	-	2014766	2014768	2014770	2014772	2014774	2014776	2014778
13 m	-	-	-	-	-	-	2021245 2021245	-	-	-	-

Dimension L1	150000 kg
2 m	-
2.5 m	-
3 m	-
4 m	2002783
5 m	2002784
6 m	2003271
7 m	2003272
8 m	2003748
9 m	-
10 m	2014779
12 m	2014780
13 m	-

■ Norms EN 1492-2: 2000

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United
Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet
Certified
Safety**

■ Main Material	High-performance polyester
■ Temperature Range	- 40 tot + 100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

