

Magnum-X

Eslinga de elevación extremadamente fina y fácil de manejar para cargas pesadas, ideal para ganchos de grúa pequeños



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
Magnum-X 5t 2m	5000	5	2	1.0	36	6	0.94
Magnum-X 5t 3m	5000	5	3	1.0	36	6	1.41
Magnum-X 5t 4m	5000	5	4	1.0	36	6	1.88
Magnum-X 5t 5m	5000	5	5	1.0	36	6	2.35
Magnum-X 5t 6m	5000	5	6	1.0	36	6	2.82
Magnum-X 5t 7m	5000	5	7	1.0	36	6	3.29
Magnum-X 5t 8m	5000	5	8	1.0	36	6	3.76
Magnum-X 10t 2m	10000	10	2	2	67	11	1.8
Magnum-X 10t 3m	10000	10	3	2	67	11	2.7
Magnum-X 10t 4m	10000	10	4	2	67	11	4.1
Magnum-X 10t 5m	10000	10	5	2	67	11	5
Magnum-X 10t 6m	10000	10	6	2	67	11	5.9
Magnum-X 10t 7m	10000	10	7	2	67	11	6.8
Magnum-X 10t 8m	10000	10	8	2	67	11	7.7
Magnum-X 20t 2m	20000	20	2	2	88	13	3.6
Magnum-X 20t 3m	20000	20	3	2	88	13	5.4
Magnum-X 20t 4m	20000	20	4	2	88	13	7.7
Magnum-X 20t 5m	20000	20	5	2	88	13	9.5
Magnum-X 20t 6m	20000	20	6	2	88	13	11.3
Magnum-X 20t 7m	20000	20	7	2	88	13	13.1
Magnum-X 20t 8m	20000	20	8	2	88	13	14.9



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
Magnum-X 20t 10m	20000	20	10	2	88	13	18.5
Magnum-X 20t 12m	20000	20	12	2	88	13	21.6
Magnum-X 25t 4m	25000	25	4	2	85	17	10.1
Magnum-X 25t 5m	25000	25	5	2	85	17	12.5
Magnum-X 25t 6m	25000	25	6	2	85	17	14.9
Magnum-X 25t 7m	25000	25	7	2	85	17	17.3
Magnum-X 25t 8m	25000	25	8	2	85	17	19.7
Magnum-X 30t 2m	30000	30	2	2	91	23	-
Magnum-X 30t 4m	30000	30	4	2	91	23	12.1
Magnum-X 30t 5m	30000	30	5	2	91	23	15
Magnum-X 30t 6m	30000	30	6	2	91	23	17.9
Magnum-X 30t 7m	30000	30	7	2	91	23	20.8
Magnum-X 30t 8m	30000	30	8	2	91	23	23.7
Magnum-X 30t 9m	30000	30	9	2	91	23	20.7
Magnum-X 30t 10m	30000	30	10	2	91	23	29.5
Magnum-X 30t 12m	30000	30	12	2	91	23	27.6
Magnum-X 40t 4m	40000	40	4	2	101	25	16.1
Magnum-X 40t 5m	40000	40	5	2	101	25	20
Magnum-X 40t 6m	40000	40	6	2	101	25	23.9
Magnum-X 40t 7m	40000	40	7	2	101	25	27.8



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
Magnum-X 40t 8m	40000	40	8	2	101	25	31.7
Magnum-X 50t 4m	50000	50	4	2	143	24	21.3
Magnum-X 50t 5m	50000	50	5	2	143	24	26.5
Magnum-X 50t 6m	50000	50	6	2	143	24	31.7
Magnum-X 50t 7m	50000	50	7	2	143	24	36.9
Magnum-X 50t 8m	50000	50	8	2	143	24	42.1
Magnum-X 50t 10m	50000	50	10	2	143	24	52.5
Magnum-X 50t 12m	50000	50	12	2	143	24	62.4
Magnum-X 60t 4m	60000	60	4	3	142	26	28.9
Magnum-X 60t 5m	60000	60	5	3	142	26	36
Magnum-X 60t 6m	60000	60	6	3	142	26	43.1
Magnum-X 60t 7m	60000	60	7	3	142	26	50.2
Magnum-X 60t 8m	60000	60	8	3	142	26	57.3
Magnum-X 80t 4m	80000	80	4	3	207	21	38.1
Magnum-X 80t 5m	80000	80	5	3	207	21	47.5
Magnum-X 80t 6m	80000	80	6	3	207	21	56.9
Magnum-X 80t 7m	80000	80	7	3	207	21	66.3
Magnum-X 80t 8m	80000	80	8	3	207	21	75.7
Magnum-X 100t 4m	100000	100	4	3	291	20	54.9
Magnum-X 100t 5m	100000	100	5	3	291	20	68.5



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
Magnum-X 100t 6m	100000	100	6	3	291	20	82.1
Magnum-X 100t 7m	100000	100	7	3	291	20	95.7
Magnum-X 100t 8m	100000	100	8	3	291	20	109.3
Magnum-X 125t 4m	125000	125	4	3	280	31	75.3
Magnum-X 125t 5m	125000	125	5	3	280	31	94
Magnum-X 125t 6m	125000	125	6	3	280	31	112.7
Magnum-X 125t 7m	125000	125	7	3	280	31	131.4
Magnum-X 125t 8m	125000	125	8	3	280	31	150.1
Magnum-X 150t 4m	150000	150	4	5	314	33	80.5
Magnum-X 150t 5m	150000	150	5	5	314	33	100.5
Magnum-X 150t 6m	150000	150	6	5	314	33	120.5
Magnum-X 150t 7m	150000	150	7	5	314	33	140.5
Magnum-X 150t 8m	150000	150	8	5	314	33	160.5

Nombre corto del ítem	Peso por metro [kg/m]	Color
Magnum-X 5t 2m	0.47	Rojo
Magnum-X 5t 3m	0.47	Rojo
Magnum-X 5t 4m	0.47	Rojo
Magnum-X 5t 5m	0.47	Rojo
Magnum-X 5t 6m	0.47	Rojo
Magnum-X 5t 7m	0.47	Rojo
Magnum-X 5t 8m	0.47	Rojo



Nombre corto del Item	Peso por metro [kg/m]	Color
Magnum-X 10t 2m	0.93	Naranja
Magnum-X 10t 3m	0.93	Naranja
Magnum-X 10t 4m	0.93	Naranja
Magnum-X 10t 5m	0.93	Naranja
Magnum-X 10t 6m	0.93	Naranja
Magnum-X 10t 7m	0.93	Naranja
Magnum-X 10t 8m	0.93	Naranja
Magnum-X 20t 2m	2.05	Naranja
Magnum-X 20t 3m	2.05	Naranja
Magnum-X 20t 4m	2.05	Naranja
Magnum-X 20t 5m	2.05	Naranja
Magnum-X 20t 6m	2.05	Naranja
Magnum-X 20t 7m	2.05	Naranja
Magnum-X 20t 8m	2.05	Naranja
Magnum-X 20t 10m	2.05	Naranja
Magnum-X 20t 12m	2.05	Naranja
Magnum-X 25t 4m	2.72	Naranja
Magnum-X 25t 5m	2.72	Naranja
Magnum-X 25t 6m	2.72	Naranja
Magnum-X 25t 7m	2.72	Naranja
Magnum-X 25t 8m	2.72	Naranja
Magnum-X 30t 2m	3.27	Naranja
Magnum-X 30t 4m	3.27	Naranja
Magnum-X 30t 5m	3.27	Naranja
Magnum-X 30t 6m	3.27	Naranja
Magnum-X 30t 7m	3.27	Naranja



Nombre corto del Item	Peso por metro [kg/m]	Color
Magnum-X 30t 8m	3.27	Naranja
Magnum-X 30t 9m	3.27	Naranja
Magnum-X 30t 10m	3.27	Naranja
Magnum-X 30t 12m	3.27	Naranja
Magnum-X 40t 4m	3.5	Naranja
Magnum-X 40t 5m	3.5	Naranja
Magnum-X 40t 6m	3.5	Naranja
Magnum-X 40t 7m	3.5	Naranja
Magnum-X 40t 8m	3.5	Naranja
Magnum-X 50t 4m	4.83	Naranja
Magnum-X 50t 5m	4.83	Naranja
Magnum-X 50t 6m	4.83	Naranja
Magnum-X 50t 7m	4.83	Naranja
Magnum-X 50t 8m	4.83	Naranja
Magnum-X 50t 10m	4.83	Naranja
Magnum-X 50t 12m	4.83	Naranja
Magnum-X 60t 4m	5.83	Naranja
Magnum-X 60t 5m	5.83	Naranja
Magnum-X 60t 6m	5.83	Naranja
Magnum-X 60t 7m	5.83	Naranja
Magnum-X 60t 8m	5.83	Naranja
Magnum-X 80t 4m	8.17	Naranja
Magnum-X 80t 5m	8.17	Naranja
Magnum-X 80t 6m	8.17	Naranja
Magnum-X 80t 7m	8.17	Naranja
Magnum-X 80t 8m	8.17	Naranja



Nombre corto del ítem	Peso por metro [kg/m]	Color
Magnum-X 100t 4m	11.8	Naranja
Magnum-X 100t 5m	11.8	Naranja
Magnum-X 100t 6m	11.8	Naranja
Magnum-X 100t 7m	11.8	Naranja
Magnum-X 100t 8m	11.8	Naranja
Magnum-X 125t 4m	16.25	Naranja
Magnum-X 125t 5m	16.25	Naranja
Magnum-X 125t 6m	16.25	Naranja
Magnum-X 125t 7m	16.25	Naranja
Magnum-X 125t 8m	16.25	Naranja
Magnum-X 150t 4m	19.75	Naranja
Magnum-X 150t 5m	19.75	Naranja
Magnum-X 150t 6m	19.75	Naranja
Magnum-X 150t 7m	19.75	Naranja
Magnum-X 150t 8m	19.75	Naranja



REFERENCIAS DE PEDIDO [Global Item Number/Local ERP Number SSES]

Dimensión L1	5000 kg	10000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg
2 m	2025045 RHX000005002001	2026603 RHX000010002001	2026604 RHX000020002001	-	2017500 RHX000030002001	-	-	-	-
3 m	2026602	2020989 RHX000010003001	2020992 RHX000020003001	-	-	-	-	-	-
4 m	2010959 RHX000005004001	2002763 RHX000010004001	2002765 RHX000020004001	2002767 RHX000025004001	2002769 RHX000030004001	2002771 RHX000040004001	2002773 RHX000050004001	2002775 RHX000060004001	2002777 RHX000070004001
5 m	2010960 RHX000005005001	2002764 RHX000010005001	2002766 RHX000020005001	2002768 RHX000025005001	2002770 RHX000030005001	2002772 RHX000040005001	2002774 RHX000050005001	2002776 RHX000060005001	2002778 RHX000070005001
6 m	2010961 RHX000005006001	2003251 RHX000010006001	2003253 RHX000020006001	2003255 RHX000025006001	2003257 RHX000030006001	2003259 RHX000040006001	2003261 RHX000050006001	2003263 RHX000060006001	2003265 RHX000070006001
7 m	2010962 RHX000005007001	2003252 RHX000010007001	2003254 RHX000020007001	2003256 RHX000025007001	2003258 RHX000030007001	2003260 RHX000040007001	2003262 RHX000050007001	2003264 RHX000060007001	2003266 RHX000070007001
8 m	2010963 RHX000005008001	2003738 RHX000010008001	2003739 RHX000020008001	2003740 RHX000025008001	2003741 RHX000030008001	2003742 RHX000040008001	2003743 RHX000050008001	2003744 RHX000060008001	2003746 RHX000070008001
9 m	-	-	-	-	2014794 RHX000030009001	-	-	-	-
10 m	-	-	2014762 RHX000020010001	-	2014765 RHX000030010001	-	2014769 RHX000050010001	-	-
12 m	-	-	2014763 RHX000020012001	-	2014766 RHX000030012001	-	2014770 RHX000050012001	-	-

Dimensión L1	150000 kg
2 m	-
3 m	-
4 m	2002783 RHX000150004001
5 m	2002784 RHX000150005001
6 m	2003271 RHX000150006001
7 m	2003272 RHX000150007001
8 m	2003748 RHX000150008001
9 m	-
10 m	-
12 m	-

- Normas EN 1492-2: 2000
- Material principal Poliéster de alto rendimiento

SpanSet S.A
Pol.Ind. Nº 7 Alm. 6
Barrio de Agaraitz,
Villabona 20150
Gipuzkoa
+34 943 692 600
sse@spanset.es
www.spanset.es



Sujeto a cambios técnicos. Reservados todos los derechos. Queda prohibida la reproducción total o parcial de esta Ficha Técnica por cualquier medio (impresión, fotocopia o cualquier otro procedimiento), así como su tratamiento informático, duplicación o distribución mediante sistemas electrónicos, sin la autorización por escrito de SpanSet. Esta Ficha técnica ha sido preparada con el debido cuidado; SpanSet no acepta ninguna responsabilidad por errores u omisiones. © SpanSet S.A

SpanSet
Certified
Safety

■ Rango de temperatura	- 40 tot + 100°C
■ Protección de la etiqueta	Si
■ Unidad de embalaje (PU) Contiene	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

