



Magnum-X

Élingue de levage extrêmement fine et facile à manipuler pour les charges lourdes, idéale pour les petits crochets de grue.

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
Magnum-X 5t 2m	5000	5	2	1.0	36	6	0.94
Magnum-X 5t 3m	5000	5	3	1.0	36	6	1.41
Magnum-X 5t 4m	5000	5	4	1.0	36	6	1.88
Magnum-X 5t 5m	5000	5	5	1.0	36	6	2.35
Magnum-X 5t 6m	5000	5	6	1.0	36	6	2.82
Magnum-X 5t 7m	5000	5	7	1.0	36	6	3.29
Magnum-X 5t 8m	5000	5	8	1.0	36	6	3.76
Magnum-X 10t 2m	10000	10	2	2	67	11	1.8
Magnum-X 10t 3m	10000	10	3	2	67	11	2.7
Magnum-X 10t 4m	10000	10	4	2	67	11	4.1
Magnum-X 10t 5m	10000	10	5	2	67	11	5
Magnum-X 10t 6m	10000	10	6	2	67	11	5.9
Magnum-X 10t 7m	10000	10	7	2	67	11	6.8
Magnum-X 10t 8m	10000	10	8	2	67	11	7.7
Magnum-X 20t 2m	20000	20	2	2	88	13	3.6
Magnum-X 20t 3m	20000	20	3	2	88	13	5.4
Magnum-X 20t 4m	20000	20	4	2	88	13	7.7
Magnum-X 20t 5m	20000	20	5	2	88	13	9.5
Magnum-X 20t 6m	20000	20	6	2	88	13	11.3



Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
Magnum-X 20t 7m	20000	20	7	2	88	13	13.1
Magnum-X 20t 8m	20000	20	8	2	88	13	14.9
Magnum-X 20t 10m	20000	20	10	2	88	13	18.5
Magnum-X 20t 12m	20000	20	12	2	88	13	21.6
Magnum-X 25t 4m	25000	25	4	2	85	17	10.1
Magnum-X 25t 5m	25000	25	5	2	85	17	12.5
Magnum-X 25t 6m	25000	25	6	2	85	17	14.9
Magnum-X 25t 7m	25000	25	7	2	85	17	17.3
Magnum-X 25t 8m	25000	25	8	2	85	17	19.7
Magnum-X 30t 2m	30000	30	2	2	91	23	6.54
Magnum-X 30t 4m	30000	30	4	2	91	23	12.1
Magnum-X 30t 5m	30000	30	5	2	91	23	15
Magnum-X 30t 6m	30000	30	6	2	91	23	17.9
Magnum-X 30t 7m	30000	30	7	2	91	23	20.8
Magnum-X 30t 8m	30000	30	8	2	91	23	23.7
Magnum-X 30t 9m	30000	30	9	2	91	23	20.7
Magnum-X 30t 10m	30000	30	10	2	91	23	29.5
Magnum-X 30t 12m	30000	30	12	2	91	23	27.6
Magnum-X 40t 4m	40000	40	4	2	101	25	16.1
Magnum-X 40t 5m	40000	40	5	2	101	25	20



Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
Magnum-X 40t 6m	40000	40	6	2	101	25	23.9
Magnum-X 40t 7m	40000	40	7	2	101	25	27.8
Magnum-X 40t 8m	40000	40	8	2	101	25	31.7
Magnum-X 50t 4m	50000	50	4	2	143	24	21.3
Magnum-X 50t 5m	50000	50	5	2	143	24	26.5
Magnum-X 50t 6m	50000	50	6	2	143	24	31.7
Magnum-X 50t 7m	50000	50	7	2	143	24	36.9
Magnum-X 50t 8m	50000	50	8	2	143	24	42.1
Magnum-X 50t 10m	50000	50	10	2	143	24	52.5
Magnum-X 50t 12m	50000	50	12	2	143	24	62.4
Magnum-X 60t 4m	60000	60	4	3	142	26	28.9
Magnum-X 60t 5m	60000	60	5	3	142	26	36
Magnum-X 60t 6m	60000	60	6	3	142	26	43.1
Magnum-X 60t 7m	60000	60	7	3	142	26	50.2
Magnum-X 60t 8m	60000	60	8	3	142	26	57.3
Magnum-X 80t 4m	80000	80	4	3	207	21	38.1
Magnum-X 80t 5m	80000	80	5	3	207	21	47.5
Magnum-X 80t 6m	80000	80	6	3	207	21	56.9
Magnum-X 80t 7m	80000	80	7	3	207	21	66.3
Magnum-X 80t 8m	80000	80	8	3	207	21	75.7



Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
Magnum-X 100t 4m	100000	100	4	3	291	20	54.9
Magnum-X 100t 5m	100000	100	5	3	291	20	68.5
Magnum-X 100t 6m	100000	100	6	3	291	20	82.1
Magnum-X 100t 7m	100000	100	7	3	291	20	95.7
Magnum-X 100t 8m	100000	100	8	3	291	20	109.3
Magnum-X 125t 4m	125000	125	4	3	280	31	75.3
Magnum-X 125t 5m	125000	125	5	3	280	31	94
Magnum-X 125t 6m	125000	125	6	3	280	31	112.7
Magnum-X 125t 7m	125000	125	7	3	280	31	131.4
Magnum-X 125t 8m	125000	125	8	3	280	31	150.1
Magnum-X 150t 4m	150000	150	4	5	314	33	80.5
Magnum-X 150t 5m	150000	150	5	5	314	33	100.5
Magnum-X 150t 6m	150000	150	6	5	314	33	120.5
Magnum-X 150t 7m	150000	150	7	5	314	33	140.5
Magnum-X 150t 8m	150000	150	8	5	314	33	160.5

Nom court de l'article	Poids par mètre [kg/m]	Couleur
Magnum-X 5t 2m	0.47	Rouge
Magnum-X 5t 3m	0.47	Rouge
Magnum-X 5t 4m	0.47	Rouge
Magnum-X 5t 5m	0.47	Rouge



Nom court de l'article	Poids par mètre [kg/m]	Couleur
Magnum-X 5t 6m	0.47	Rouge
Magnum-X 5t 7m	0.47	Rouge
Magnum-X 5t 8m	0.47	Rouge
Magnum-X 10t 2m	0.93	Orange
Magnum-X 10t 3m	0.93	Orange
Magnum-X 10t 4m	0.93	Orange
Magnum-X 10t 5m	0.93	Orange
Magnum-X 10t 6m	0.93	Orange
Magnum-X 10t 7m	0.93	Orange
Magnum-X 10t 8m	0.93	Orange
Magnum-X 20t 2m	2.05	Orange
Magnum-X 20t 3m	2.05	Orange
Magnum-X 20t 4m	2.05	Orange
Magnum-X 20t 5m	2.05	Orange
Magnum-X 20t 6m	2.05	Orange
Magnum-X 20t 7m	2.05	Orange
Magnum-X 20t 8m	2.05	Orange
Magnum-X 20t 10m	2.05	Orange
Magnum-X 20t 12m	2.05	Orange
Magnum-X 25t 4m	2.72	Orange
Magnum-X 25t 5m	2.72	Orange
Magnum-X 25t 6m	2.72	Orange
Magnum-X 25t 7m	2.72	Orange
Magnum-X 25t 8m	2.72	Orange
Magnum-X 30t 2m	3.27	Orange
Magnum-X 30t 4m	3.27	Orange



Nom court de l'article	Poids par mètre [kg/m]	Couleur
Magnum-X 30t 5m	3.27	Orange
Magnum-X 30t 6m	3.27	Orange
Magnum-X 30t 7m	3.27	Orange
Magnum-X 30t 8m	3.27	Orange
Magnum-X 30t 9m	3.27	Orange
Magnum-X 30t 10m	3.27	Orange
Magnum-X 30t 12m	3.27	Orange
Magnum-X 40t 4m	3.5	Orange
Magnum-X 40t 5m	3.5	Orange
Magnum-X 40t 6m	3.5	Orange
Magnum-X 40t 7m	3.5	Orange
Magnum-X 40t 8m	3.5	Orange
Magnum-X 50t 4m	4.83	Orange
Magnum-X 50t 5m	4.83	Orange
Magnum-X 50t 6m	4.83	Orange
Magnum-X 50t 7m	4.83	Orange
Magnum-X 50t 8m	4.83	Orange
Magnum-X 50t 10m	4.83	Orange
Magnum-X 50t 12m	4.83	Orange
Magnum-X 60t 4m	5.83	Orange
Magnum-X 60t 5m	5.83	Orange
Magnum-X 60t 6m	5.83	Orange
Magnum-X 60t 7m	5.83	Orange
Magnum-X 60t 8m	5.83	Orange
Magnum-X 80t 4m	8.17	Orange
Magnum-X 80t 5m	8.17	Orange



Nom court de l'article	Poids par mètre [kg/m]	Couleur
Magnum-X 80t 6m	8.17	Orange
Magnum-X 80t 7m	8.17	Orange
Magnum-X 80t 8m	8.17	Orange
Magnum-X 100t 4m	11.8	Orange
Magnum-X 100t 5m	11.8	Orange
Magnum-X 100t 6m	11.8	Orange
Magnum-X 100t 7m	11.8	Orange
Magnum-X 100t 8m	11.8	Orange
Magnum-X 125t 4m	16.25	Orange
Magnum-X 125t 5m	16.25	Orange
Magnum-X 125t 6m	16.25	Orange
Magnum-X 125t 7m	16.25	Orange
Magnum-X 125t 8m	16.25	Orange
Magnum-X 150t 4m	19.75	Orange
Magnum-X 150t 5m	19.75	Orange
Magnum-X 150t 6m	19.75	Orange
Magnum-X 150t 7m	19.75	Orange
Magnum-X 150t 8m	19.75	Orange



NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSFR]

Dimension L1	5000 kg	10000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg	125000 kg
2 m	2025045	2026603	2026604	-	2017500	-	-	-	-	-	-
3 m	2026602	2020989	2020992	-	-	-	-	-	-	-	-
4 m	2010959	2002763	2002765	2002767	2002769	2002771	2002773	2002775	2002777	2002779	2002781
5 m	2010960	2002764	2002766	2002768	2002770	2002772	2002774	2002776	2002778	2002780	2002782
6 m	2010961	2003251	2003253	2003255	2003257	2003259	2003261	2003263	2003265	2003267	2003269
7 m	2010962	2003252	2003254	2003256	2003258	2003260	2003262	2003264	2003266	2003268	2003270
8 m	2010963	2003738	2003739	2003740	2003741	2003742	2003743	2003744	2003745	2003746	2003747
9 m	-	-	-	-	2014794	-	-	-	-	-	-
10 m	-	-	2014762	-	2014765	-	2014769	-	-	-	-
12 m	-	-	2014763	-	2014766	-	2014770	-	-	-	-

Dimension L1	150000 kg
2 m	-
3 m	-
4 m	2002783
5 m	2002784
6 m	2003271
7 m	2003272
8 m	2003748
9 m	-
10 m	-
12 m	-

- Normes EN 1492-2: 2000
- Matériel principal Polyester haute performance
- Plage de température - 40 tot + 100°C
- Protection d'étiquette Oui
- Contenu des unités d'emballage (UE) 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

