

Magnum-X Short

Extremely slim and easy to handle heavy duty lifting sling version from 0.375 m to 2 m



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight per Meter [kg/m]
Magnum-X short 10t 1m	10000	10	1	55	10	-
Magnum-X short 10t 1.5m	10000	10	1.5	55	10	-
Magnum-X short 10t 2m	10000	10	2	55	10	0.93
Magnum-X short 20t 1m	20000	20	1	70	13	2.05
Magnum-X short 20t 1.5m	20000	20	1.5	70	13	2.05
Magnum-X short 20t 2m	20000	20	2	70	13	2.05
Magnum-X short 30t 1m	30000	30	1	100	21	3.27
Magnum-X short 30t 1.5m	30000	30	1.5	100	21	3.27
Magnum-X short 30t 2m	30000	30	2	100	21	3.27

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Dimension L1	10000 kg	20000 kg	30000 kg
1 m	2002791 D048679	2002793 D048826	2002795 D048829
1.5 m	2002792 D048824	2002794 D048827	2002796 D048830
2 m	2003279 D048825	2003280 D048828	2003281 D048831

■ Main Material	High-performance polyester
■ Colour	Orange
■ Temperature Range	- 40 tot + 100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

**SpanSet GmbH & Co.
KG**
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**