

Magnum-X Short

Extremely slim and easy to handle heavy duty lifting sling version from 0.375 m to 2 m



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight per Meter [kg/m]
Magnum-X short 10t 1m	10000	10	1	55	10	-
Magnum-X short 10t 1.5m	10000	10	1.5	55	10	-
Magnum-X short 10t 2m	10000	10	2	55	10	0.93
Magnum-X short 20t 1m	20000	20	1	70	13	2.05
Magnum-X short 20t 1.5m	20000	20	1.5	70	13	2.05
Magnum-X short 20t 2m	20000	20	2	70	13	2.05
Magnum-X short 30t 1m	30000	30	1	100	21	3.27
Magnum-X short 30t 1.5m	30000	30	1.5	100	21	3.27
Magnum-X short 30t 2m	30000	30	2	100	21	3.27

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Dimension L1	10000 kg	20000 kg	30000 kg
1 m	2002791	2002793	2002795
1.5 m	2002792	2002794	2002796
2 m	2003279	2003280	2003281

■ Main Material	High-performance polyester
■ Colour	Orange
■ Temperature Range	- 40 tot + 100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

