

Magnum-X Smart 2

Slim heavy duty round sling with replaceable protective hose, made of durable high-performance fibre



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
Magnum-X SMART 20t 4m	20000	20	4	2	76	15	9.6
Magnum-X SMART 20t 5m	20000	20	5	2	76	15	12
Magnum-X SMART 20t 6m	20000	20	6	2	76	15	14.4
Magnum-X SMART 20t 7m	20000	20	7	2	76	15	16.8
Magnum-X SMART 20t 8m	20000	20	8	2	76	15	19.2
Magnum-X SMART 30t 4m	30000	30	4	2	88	20	14.8
Magnum-X SMART 30t 5m	30000	30	5	2	88	20	18.5
Magnum-X SMART 30t 6m	30000	30	6	2	88	20	22.2
Magnum-X SMART 30t 7m	30000	30	7	2	88	20	25.9
Magnum-X SMART 30t 8m	30000	30	8	2	88	20	29.6
Magnum-X SMART 40t 4m	40000	40	4	3	110	24	19.2
Magnum-X SMART 40t 5m	40000	40	5	3	110	24	24
Magnum-X SMART 40t 6m	40000	40	6	3	110	24	28.8
Magnum-X SMART 40t 7m	40000	40	7	3	110	24	33.6
Magnum-X SMART 40t 8m	40000	40	8	3	110	24	38.4

Item Name short	Weight per Meter [kg/m]
Magnum-X SMART 20t 4m	2.4
Magnum-X SMART 20t 5m	2.4
Magnum-X SMART 20t 6m	2.4
Magnum-X SMART 20t 7m	2.4



Item Name short	Weight per Meter [kg/m]
Magnum-X SMART 20t 8m	2.4
Magnum-X SMART 30t 4m	3.27
Magnum-X SMART 30t 5m	3.27
Magnum-X SMART 30t 6m	3.27
Magnum-X SMART 30t 7m	3.27
Magnum-X SMART 30t 8m	3.27
Magnum-X SMART 40t 4m	3.50
Magnum-X SMART 40t 5m	3.50
Magnum-X SMART 40t 6m	3.50
Magnum-X SMART 40t 7m	3.50
Magnum-X SMART 40t 8m	3.50

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

WLL kg	4 m	5 m	6 m	7 m	8 m
20000 kg	2002785	2002786	2003273	2003274	2003749
30000 kg	2002787	2002788	2003275	2003276	2003750
40000 kg	2002789	2002790	2003277	2003278	2003751

- **Main Material** High-performance polyester
- **Colour** Orange
- **Temperature Range** - 40 tot + 100°C
- **Packaging Unit (PU) Content** 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

