

MagnumForce

Eslinga reforzada con fibras HMPE de alto rendimiento reduce el desgaste y mayor resistencia a los cortes



Nombre corto del Item	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
MagnumForce 10t 2m	10000	10	2	2	70	7	1.6
MagnumForce 10t 3m	10000	10	3	2	70	7	2.4
MagnumForce 10t 4m	10000	10	4	2	70	7	3.2
MagnumForce 10t 5m	10000	10	5	2	70	7	4
MagnumForce 20t 2m	20000	20	2	2	91	18	3.2
MagnumForce 20t 3m	20000	20	3	2	91	18	4.8
MagnumForce 20t 4m	20000	20	4	2	91	18	6.4
MagnumForce 20t 5m	20000	20	5	2	91	18	8
MagnumForce 30t 2m	30000	30	2	3	115	20	5.2
MagnumForce 30t 3m	30000	30	3	3	115	20	7.8
MagnumForce 30t 4m	30000	30	4	3	115	20	10.4
MagnumForce 30t 5m	30000	30	5	3	115	20	13
MagnumForce 40t 2m	40000	40	2	3	135	22	6.8
MagnumForce 40t 3m	40000	40	3	3	135	22	10.2
MagnumForce 40t 4m	40000	40	4	3	135	22	13.6
MagnumForce 40t 5m	40000	40	5	3	135	22	17
MagnumForce 50t 2m	50000	50	2	3	152	23	8.4
MagnumForce 50t 3m	50000	50	3	3	152	23	12.6
MagnumForce 50t 4m	50000	50	4	3	152	23	16.8



Nombre corto del Item	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
MagnumForce 50t 5m	50000	50	5	3	152	23	21
MagnumForce 60t 2m	60000	60	2	3	165	23	10
MagnumForce 60t 3m	60000	60	3	3	165	23	15
MagnumForce 60t 4m	60000	60	4	3	165	23	20
MagnumForce 60t 5m	60000	60	5	3	165	23	25
MagnumForce 80t 2m	80000	80	2	3	200	27	12.2
MagnumForce 80t 3m	80000	80	3	3	200	27	18.3
MagnumForce 80t 4m	80000	80	4	3	200	27	24.4
MagnumForce 80t 5m	80000	80	5	3	200	27	30.5
MagnumForce 100t 2m	100000	100	2	3	190	35	14.2
MagnumForce 100t 3m	100000	100	3	3	190	35	21.3
MagnumForce 100t 4m	100000	100	4	3	190	35	28.4
MagnumForce 100t 5m	100000	100	5	3	190	35	35.5

Nombre corto del Item	Peso por metro [kg/m]
MagnumForce 10t 2m	0.8
MagnumForce 10t 3m	0.8
MagnumForce 10t 4m	0.8
MagnumForce 10t 5m	0.8
MagnumForce 20t 2m	1.6
MagnumForce 20t 3m	1.6
MagnumForce 20t 4m	1.6
MagnumForce 20t 5m	1.6
MagnumForce 30t 2m	2.6



Nombre corto del ítem	Peso por metro [kg/m]
MagnumForce 30t 3m	2.6
MagnumForce 30t 4m	2.6
MagnumForce 30t 5m	2.6
MagnumForce 40t 2m	3.4
MagnumForce 40t 3m	3.4
MagnumForce 40t 4m	3.4
MagnumForce 40t 5m	3.4
MagnumForce 50t 2m	4.2
MagnumForce 50t 3m	4.2
MagnumForce 50t 4m	4.2
MagnumForce 50t 5m	4.2
MagnumForce 60t 2m	5.0
MagnumForce 60t 3m	5.0
MagnumForce 60t 4m	5.0
MagnumForce 60t 5m	5.0
MagnumForce 80t 2m	6.1
MagnumForce 80t 3m	6.1
MagnumForce 80t 4m	6.1
MagnumForce 80t 5m	6.1
MagnumForce 100t 2m	7.1
MagnumForce 100t 3m	7.1
MagnumForce 100t 4m	7.1
MagnumForce 100t 5m	7.1

REFERENCIAS DE PEDIDO[Global Item Number/Local ERP Number SSES]

Dimensión L1	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg
2 m	2026519 RHF000010002001	2026520 RHF000020002001	2026526 RHF000030002001	2032556 RHF000040002001	2033146 RHF000050002001	2033173 RHF000060002001	2033147 RHF000080002001	2033148 RHF000100002001
3 m	2026518 RHF000010003001	2026521 RHF000020003001	2026527 RHF000030003001	2026532 RHF000040003001	2026539 RHF000050003001	2026544 RHF000060003001	2026549 RHF000080003001	2026554 RHF000100003001
4 m	2002539 RHF000010004001	2002544 RHF000020004001	2002549 RHF000030004001	2002554 RHF000040004001	2002559 RHF000050004001	2008377 RHF000060004001	2008382 RHF000080004001	2008387 RHF000100004001
5 m	2002540 RHF000010005001	2002545 RHF000020005001	2002550 RHF000030005001	2002555 RHF000040005001	2002560 RHF000050005001	2008378 RHF000060005001	2008383 RHF000080005001	2008388 RHF000100005001



■ Material principal	Polietileno de alto peso molecular (HMPE)
■ Color	Naranja
■ Rango de temperatura	- 40 tot + 70°C
■ Unidad de embalaje (PU) Contiene	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

