

MagnumForce

Funi in HMPE rinforzata con fibre altamente performanti che riducono l'usura e aumentano la resistenza al taglio



Nome articolo breve	WLL kg [kg]	WLL ton [t]	L1 [m]	L1 min. [m]	Larghezza parte a contatto sotto carico [mm]	Spessore sotto carico [mm]	Peso netto [kg]
MagnumForce 10t 4m	10000	10	4	2	70	7	3.2
MagnumForce 10t 5m	10000	10	5	2	70	7	4
MagnumForce 10t 6m	10000	10	6	2	70	7	4.8
MagnumForce 10t 7m	10000	10	7	2	70	7	5.6
MagnumForce 10t 8m	10000	10	8	2	70	7	6.4
MagnumForce 20t 4m	20000	20	4	2	91	18	6.4
MagnumForce 20t 5m	20000	20	5	2	91	18	8
MagnumForce 20t 6m	20000	20	6	2	91	18	9.6
MagnumForce 20t 7m	20000	20	7	2	91	18	11.2
MagnumForce 20t 8m	20000	20	8	2	91	18	12.8
MagnumForce 30t 4m	30000	30	4	3	115	20	10.4
MagnumForce 30t 5m	30000	30	5	3	115	20	13
MagnumForce 30t 6m	30000	30	6	3	115	20	15.6
MagnumForce 30t 7m	30000	30	7	3	115	20	18.2
MagnumForce 30t 8m	30000	30	8	3	115	20	20.8
MagnumForce 40t 4m	40000	40	4	3	135	22	13.6
MagnumForce 40t 5m	40000	40	5	3	135	22	17
MagnumForce 40t 6m	40000	40	6	3	135	22	20.4
MagnumForce 40t 7m	40000	40	7	3	135	22	23.8



Nome articolo breve	WLL kg [kg]	WLL ton [t]	L1 [m]	L1 min. [m]	Larghezza parte a contatto sotto carico [mm]	Spessore sotto carico [mm]	Peso netto [kg]
MagnumForce 40t 8m	40000	40	8	3	135	22	27.2
MagnumForce 50t 4m	50000	50	4	3	152	23	16.8
MagnumForce 50t 5m	50000	50	5	3	152	23	21
MagnumForce 50t 6m	50000	50	6	3	152	23	25.2
MagnumForce 50t 7m	50000	50	7	3	152	23	29.4
MagnumForce 50t 8m	50000	50	8	3	152	23	33.6
MagnumForce 60t 4m	60000	60	4	3	165	23	20
MagnumForce 60t 5m	60000	60	5	3	165	23	25
MagnumForce 60t 6m	60000	60	6	3	165	23	30
MagnumForce 60t 7m	60000	60	7	3	165	23	35
MagnumForce 60t 8m	60000	60	8	3	165	23	40
MagnumForce 80t 4m	80000	80	4	3	200	27	24.4
MagnumForce 80t 5m	80000	80	5	3	200	27	30.5
MagnumForce 80t 6m	80000	80	6	3	200	27	36.6
MagnumForce 80t 7m	80000	80	7	3	200	27	42.7
MagnumForce 80t 8m	80000	80	8	3	200	27	48.8
MagnumForce 100t 4m	100000	100	4	3	190	35	28.4
MagnumForce 100t 5m	100000	100	5	3	190	35	35.5
MagnumForce 100t 6m	100000	100	6	3	190	35	42.6
MagnumForce 100t 7m	100000	100	7	3	190	35	49.7



Nome articolo breve	WLL kg [kg]	WLL ton [t]	L1 [m]	L1 min. [m]	Larghezza parte a contatto sotto carico [mm]	Spessore sotto carico [mm]	Peso netto [kg]
MagnumForce 100t 8m	100000	100	8	3	190	35	56.8

Nome articolo breve	Peso al metro [kg/m]
MagnumForce 10t 4m	0.8
MagnumForce 10t 5m	0.8
MagnumForce 10t 6m	0.8
MagnumForce 10t 7m	0.8
MagnumForce 10t 8m	0.8
MagnumForce 20t 4m	1.6
MagnumForce 20t 5m	1.6
MagnumForce 20t 6m	1.6
MagnumForce 20t 7m	1.6
MagnumForce 20t 8m	1.6
MagnumForce 30t 4m	2.6
MagnumForce 30t 5m	2.6
MagnumForce 30t 6m	2.6
MagnumForce 30t 7m	2.6
MagnumForce 30t 8m	2.6
MagnumForce 40t 4m	3.4
MagnumForce 40t 5m	3.4
MagnumForce 40t 6m	3.4
MagnumForce 40t 7m	3.4
MagnumForce 40t 8m	3.4
MagnumForce 50t 4m	4.2
MagnumForce 50t 5m	4.2
MagnumForce 50t 6m	4.2
MagnumForce 50t 7m	4.2
MagnumForce 50t 8m	4.2
MagnumForce 60t 4m	5.0
MagnumForce 60t 5m	5.0
MagnumForce 60t 6m	5.0



Nome articolo breve	Peso al metro [kg/m]
MagnumForce 60t 7m	5.0
MagnumForce 60t 8m	5.0
MagnumForce 80t 4m	6.1
MagnumForce 80t 5m	6.1
MagnumForce 80t 6m	6.1
MagnumForce 80t 7m	6.1
MagnumForce 80t 8m	6.1
MagnumForce 100t 4m	7.1
MagnumForce 100t 5m	7.1
MagnumForce 100t 6m	7.1
MagnumForce 100t 7m	7.1
MagnumForce 100t 8m	7.1

ARTICOLO[Global Item Number/Local ERP Number SSIT]

Dimensione L1	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg
4 m	2002539 MAGNUMF-010-080	2002544 MAGNUMF-020-080	2002549 MAGNUMF-030-080	2002554 MAGNUMF-040-080	2002559 MAGNUMF-050-080	2008377 MAGNUMF-060-080	2008382 MAGNUMF-080-080	2008387 MAGNUMF-100-080
5 m	2002540 MAGNUMF-010-100	2002545 MAGNUMF-020-100	2002550 MAGNUMF-030-100	2002555 MAGNUMF-040-100	2002560 MAGNUMF-050-100	2008378 MAGNUMF-060-100	2008383 MAGNUMF-080-100	2008388 MAGNUMF-100-100
6 m	2002541 MAGNUMF-010-120	2002546 MAGNUMF-020-120	2002551 MAGNUMF-030-120	2002556 MAGNUMF-040-120	2002561 MAGNUMF-050-120	2008379 MAGNUMF-060-120	2008384 MAGNUMF-080-120	2008389 MAGNUMF-100-120
7 m	2002542 MAGNUMF-010-140	2002547 MAGNUMF-020-140	2002552 MAGNUMF-030-140	2002557 MAGNUMF-040-140	2002562 MAGNUMF-050-140	2008380 MAGNUMF-060-140	2008385 MAGNUMF-080-140	2008390 MAGNUMF-100-140
8 m	2002543 MAGNUMF-010-160	2002548 MAGNUMF-020-160	2002553 MAGNUMF-030-160	2002558 MAGNUMF-040-160	2002563 MAGNUMF-050-160	2008381 MAGNUMF-060-160	2008386 MAGNUMF-080-160	2008391 MAGNUMF-100-160

- **Materiale principale** Polietilene ad alto peso molecolare (HMPE)
- **Colore** Arancio
- **Intervallo di temperatura** - 40 tot + 70°C
- **Packaging Unit (PU) Contenuto** 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

