

MagnumForce

A linga reforçada com fibras HMPE de alto desempenho reduz o desgaste e aumenta a resistência a cortes.



Nome curto do item	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Largura do tecido sob carga [mm]	Espessura sob carga [mm]	Peso líquido [kg]
MagnumForce 10t 2m	10000	10	2	2	70	7	1.6
MagnumForce 10t 3m	10000	10	3	2	70	7	2.4
MagnumForce 10t 4m	10000	10	4	2	70	7	3.2
MagnumForce 10t 5m	10000	10	5	2	70	7	4
MagnumForce 20t 2m	20000	20	2	2	91	18	3.2
MagnumForce 20t 3m	20000	20	3	2	91	18	4.8
MagnumForce 20t 4m	20000	20	4	2	91	18	6.4
MagnumForce 20t 5m	20000	20	5	2	91	18	8
MagnumForce 30t 2m	30000	30	2	3	115	20	5.2
MagnumForce 30t 3m	30000	30	3	3	115	20	7.8
MagnumForce 30t 4m	30000	30	4	3	115	20	10.4
MagnumForce 30t 5m	30000	30	5	3	115	20	13
MagnumForce 40t 2m	40000	40	2	3	135	22	6.8
MagnumForce 40t 3m	40000	40	3	3	135	22	10.2
MagnumForce 40t 4m	40000	40	4	3	135	22	13.6
MagnumForce 40t 5m	40000	40	5	3	135	22	17
MagnumForce 50t 2m	50000	50	2	3	152	23	8.4
MagnumForce 50t 3m	50000	50	3	3	152	23	12.6
MagnumForce 50t 4m	50000	50	4	3	152	23	16.8



Nome curto do item	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Largura do tecido sob carga [mm]	Espessura sob carga [mm]	Peso líquido [kg]
MagnumForce 50t 5m	50000	50	5	3	152	23	21
MagnumForce 60t 2m	60000	60	2	3	165	23	10
MagnumForce 60t 3m	60000	60	3	3	165	23	15
MagnumForce 60t 4m	60000	60	4	3	165	23	20
MagnumForce 60t 5m	60000	60	5	3	165	23	25
MagnumForce 80t 2m	80000	80	2	3	200	27	12.2
MagnumForce 80t 3m	80000	80	3	3	200	27	18.3
MagnumForce 80t 4m	80000	80	4	3	200	27	24.4
MagnumForce 80t 5m	80000	80	5	3	200	27	30.5
MagnumForce 100t 2m	100000	100	2	3	190	35	14.2
MagnumForce 100t 3m	100000	100	3	3	190	35	21.3
MagnumForce 100t 4m	100000	100	4	3	190	35	28.4
MagnumForce 100t 5m	100000	100	5	3	190	35	35.5

Nome curto do item	Peso por metro [kg/m]
MagnumForce 10t 2m	0.8
MagnumForce 10t 3m	0.8
MagnumForce 10t 4m	0.8
MagnumForce 10t 5m	0.8
MagnumForce 20t 2m	1.6
MagnumForce 20t 3m	1.6
MagnumForce 20t 4m	1.6
MagnumForce 20t 5m	1.6
MagnumForce 30t 2m	2.6



Nome curto do item	Peso por metro [kg/m]
MagnumForce 30t 3m	2.6
MagnumForce 30t 4m	2.6
MagnumForce 30t 5m	2.6
MagnumForce 40t 2m	3.4
MagnumForce 40t 3m	3.4
MagnumForce 40t 4m	3.4
MagnumForce 40t 5m	3.4
MagnumForce 50t 2m	4.2
MagnumForce 50t 3m	4.2
MagnumForce 50t 4m	4.2
MagnumForce 50t 5m	4.2
MagnumForce 60t 2m	5.0
MagnumForce 60t 3m	5.0
MagnumForce 60t 4m	5.0
MagnumForce 60t 5m	5.0
MagnumForce 80t 2m	6.1
MagnumForce 80t 3m	6.1
MagnumForce 80t 4m	6.1
MagnumForce 80t 5m	6.1
MagnumForce 100t 2m	7.1
MagnumForce 100t 3m	7.1
MagnumForce 100t 4m	7.1
MagnumForce 100t 5m	7.1

NÚMEROS DE ORDEM[Global Item Number/Local ERP Number SSSES]

Dimensão L1	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg	100000 kg
2 m	2026519 RHF000010002001RHF000020002001RHF000030002001RHF000040002001RHF000050002001RHF000060002001RHF000080002001RHF000100002001	2026520	2026526	2032556	2033146	2033173	2033147	2033148
3 m	2026518 RHF000010003001RHF000020003001RHF000030003001RHF000040003001RHF000050003001RHF000060003001RHF000080003001RHF000100003001	2026521	2026527	2026532	2026539	2026544	2026549	2026554
4 m	2002539 RHF000010004001RHF000020004001RHF000030004001RHF000040004001RHF000050004001RHF000060004001RHF000080004001RHF000100004001	2002544	2002549	2002554	2002559	2008377	2008382	2008387
5 m	2002540 RHF000010005001RHF000020005001RHF000030005001RHF000040005001RHF000050005001RHF000060005001RHF000080005001RHF000100005001	2002545	2002550	2002555	2002560	2008378	2008383	2008388



■ Material principal	Polietileno de alto peso molecular (HMPE)
■ Cor	Laranja
■ Gama de temperaturas	- 40 tot + 70°C
■ Unidade de embalagem (PU) Contém	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

