

MagnumPlus

Eslinga redonda extra resistente para elevación de cargas pesadas de manera segura, fácil de manejar y alta resistencia al desgaste

Nombre corto del ítem	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
MagnumPlus 10t 4m	10000	10	4	1	93	12	9.3
MagnumPlus 10t 5m	10000	10	5	1	93	12	11.5
MagnumPlus 10t 6m	10000	10	6	1	93	12	13.7
MagnumPlus 10t 7m	10000	10	7	1	93	12	15.9
MagnumPlus 10t 8m	10000	10	8	1	93	12	18.1
MagnumPlus 15t 4m	15000	15	4	1	110	15	13.3
MagnumPlus 15t 5m	15000	15	5	1	110	15	16.5
MagnumPlus 15t 6m	15000	15	6	1	110	15	19.7
MagnumPlus 15t 7.0m	15000	15	7	1	110	15	22.9
MagnumPlus 15t 8m	15000	15	8	1	110	15	26.1
MagnumPlus 20t 4m	20000	20	4	1.3	140	18	18.1
MagnumPlus 20t 5m	20000	20	5	1.3	140	18	22.5
MagnumPlus 20t 6m	20000	20	6	1.3	140	18	26.9
MagnumPlus 20t 7m	20000	20	7	1.3	140	18	31.3
MagnumPlus 20t 8.0m	20000	20	8	1.3	140	18	35.7
MagnumPlus 25t 4m	25000	25	4	1.3	153	25	22.9
MagnumPlus 25t 5m	25000	25	5	1.3	153	25	28.5
MagnumPlus 25t 6m	25000	25	6	1.3	153	25	34.1
MagnumPlus 25t 7m	25000	25	7	1.3	153	25	39.7



Nombre corto del ítem	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
MagnumPlus 25t 8m	25000	25	8	1.3	153	25	45.3
MagnumPlus 30t 4m	30000	30	4	1.3	165	19	30.1
MagnumPlus 30t 5m	30000	30	5	1.3	165	19	37.5
MagnumPlus 30t 6m	30000	30	6	1.3	165	19	44.9
MagnumPlus 30t 7m	30000	30	7	1.3	165	19	52.3
MagnumPlus 30t 8m	30000	30	8	1.3	165	19	59.7
MagnumPlus 40t 4m	40000	40	4	3	180	22	40.5
MagnumPlus 40t 5m	40000	40	5	3	180	22	50.5
MagnumPlus 40t 6m	40000	40	6	3	180	22	60.5
MagnumPlus 40t 7m	40000	40	7	3	180	22	70.5
MagnumPlus 40t 8m	40000	40	8	3	180	22	80.5
MagnumPlus 50t 4m	50000	50	4	3	208	24	52.5
MagnumPlus 50t 5m	50000	50	5	3	208	24	65.5
MagnumPlus 50t 6m	50000	50	6	3	208	24	78.5
MagnumPlus 50t 7m	50000	50	7	3	208	24	91.5
MagnumPlus 50t 8m	50000	50	8	3	208	24	104.5
MagnumPlus 60t 4m	60000	60	4	3	244	27	59.7
MagnumPlus 60t 5m	60000	60	5	3	244	27	74.5
MagnumPlus 60t 6m	60000	60	6	3	244	27	89.3
MagnumPlus 60t 7m	60000	60	7	3	244	27	104.1



Nombre corto del ítem	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
MagnumPlus 60t 8m	60000	60	8	3	244	27	118.9
MagnumPlus 80t 4,0m	80000	80	4	3	279	47	80.5
MagnumPlus 80t 5,0m	80000	80	5	3	279	47	100.5
MagnumPlus 80t 6,0m	80000	80	6	3	279	47	120.5
MagnumPlus 80t 7,0m	80000	80	7	3	279	47	140.5
MagnumPlus 80t 8,0m	80000	80	8	3	279	47	160.5
MagnumPlus 100t 4,0m	100000	100	4	3	294	49	104.5
MagnumPlus 100t 5,0m	100000	100	5	3	294	49	130.5
MagnumPlus 100t 6,0m	100000	100	6	3	294	49	156.5
MagnumPlus 100t 7,0m	100000	100	7	3	294	49	182.5
MagnumPlus 100t 8,0m	100000	100	8	3	294	49	208.5

Nombre corto del ítem	Peso por metro [kg/m]
MagnumPlus 10t 4m	2.2
MagnumPlus 10t 5m	2.2
MagnumPlus 10t 6m	2.2
MagnumPlus 10t 7m	2.2
MagnumPlus 10t 8m	2.2
MagnumPlus 15t 4m	2.7
MagnumPlus 15t 5m	2.7
MagnumPlus 15t 6m	2.7
MagnumPlus 15t 7,0m	2.7
MagnumPlus 15t 8m	2.7
MagnumPlus 20t 4m	4
MagnumPlus 20t 5m	4



Nombre corto del ítem	Peso por metro [kg/m]
MagnumPlus 20t 6m	4
MagnumPlus 20t 7m	4
MagnumPlus 20t 8,0m	4
MagnumPlus 25t 4m	5
MagnumPlus 25t 5m	5
MagnumPlus 25t 6m	5
MagnumPlus 25t 7m	5
MagnumPlus 25t 8m	5
MagnumPlus 30t 4m	6.5
MagnumPlus 30t 5m	6.5
MagnumPlus 30t 6m	6.5
MagnumPlus 30t 7m	6.5
MagnumPlus 30t 8m	6.5
MagnumPlus 40t 4m	9.7
MagnumPlus 40t 5m	9.7
MagnumPlus 40t 6m	9.7
MagnumPlus 40t 7m	9.7
MagnumPlus 40t 8m	9.7
MagnumPlus 50t 4m	12.5
MagnumPlus 50t 5m	12.5
MagnumPlus 50t 6m	12.5
MagnumPlus 50t 7m	12.5
MagnumPlus 50t 8m	12.5
MagnumPlus 60t 4m	16.6
MagnumPlus 60t 5m	16.6
MagnumPlus 60t 6m	16.6
MagnumPlus 60t 7m	16.6
MagnumPlus 60t 8m	16.6
MagnumPlus 80t 4,0m	20.8
MagnumPlus 80t 5,0m	20.8
MagnumPlus 80t 6,0m	20.8
MagnumPlus 80t 7,0m	20.8
MagnumPlus 80t 8,0m	20.8



Nombre corto del ítem	Peso por metro [kg/m]
MagnumPlus 100t 4,0m	24.3
MagnumPlus 100t 5,0m	24.3
MagnumPlus 100t 6,0m	24.3
MagnumPlus 100t 7.0m	24.3
MagnumPlus 100t 8.0m	24.3

REFERENCIAS DE PEDIDO[Global Item Number/Local ERP Number SSES]

Dimensión L1	10000 kg	15000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg	80000 kg
4 m	2002743	2002745	2002747	2002749	2002751	2002753	2002755	2002757	2002759
	RHG000010004001	RHG000015004001	RHG000020004001	RHG000025004001	RHG000030004001	RHG000040004001	RHG000050004001	RHG000060004001	RHG000070004001
5 m	2002744	2002746	2002748	2002750	2002752	2002754	2002756	2002758	2002760
	RHG000010005001	RHG000015005001	RHG000020005001	RHG000025005001	RHG000030005001	RHG000040005001	RHG000050005001	RHG000060005001	RHG000070005001
6 m	2003231	2003233	2003235	2003237	2003239	2003241	2003243	2003245	2003247
	RHG000010006001	RHG000015006001	RHG000020006001	RHG000025006001	RHG000030006001	RHG000040006001	RHG000050006001	RHG000060006001	RHG000070006001
7 m	2003232	2003234	2003236	2003238	2003240	2003242	2003244	2003246	2003248
	RHG000010007001	RHG000015007001	RHG000020007001	RHG000025007001	RHG000030007001	RHG000040007001	RHG000050007001	RHG000060007001	RHG000070007001
8 m	2003728	2003729	2003730	2003731	2003732	2003733	2003734	2003735	2003736
	RHG000010008001	RHG000015008001	RHG000020008001	RHG000025008001	RHG000030008001	RHG000040008001	RHG000050008001	RHG000060008001	RHG000070008001

- Normas EN 1492-2: 2000
- Material principal Poliéster
- Color Naranja
- Rango de temperatura - 40 tot + 100°C
- Protección de la etiqueta Si
- Unidad de embalaje (PU) Contiene 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - Nutzlänge.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

