

MagnumPlus

Serrage puissant pour les charges lourdes

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
MagnumPlus 10t 2m	10000	10	2	1	93	12	4.4
MagnumPlus 10t 2.5m	10000	10	2.5	1	93	12	5.5
MagnumPlus 10t 3m	10000	10	3	1	93	12	6.6
MagnumPlus 10t 4m	10000	10	4	1	93	12	9.3
MagnumPlus 10t 5m	10000	10	5	1	93	12	11.5
MagnumPlus 10t 6m	10000	10	6	1	93	12	13.7
MagnumPlus 10t 7m	10000	10	7	1	93	12	15.9
MagnumPlus 10t 8m	10000	10	8	1	93	12	18.1
MagnumPlus 15t 2m	15000	15	2	1	110	15	5.4
MagnumPlus 15t 2.5m	15000	15	2.5	1	110	15	6.75
MagnumPlus 15t 3m	15000	15	3	1	110	15	8.1
MagnumPlus 15t 4m	15000	15	4	1	110	15	13.3
MagnumPlus 15t 5m	15000	15	5	1	110	15	16.5
MagnumPlus 15t 6m	15000	15	6	1	110	15	19.7
MagnumPlus 15t 7.0m	15000	15	7	1	110	15	22.9
MagnumPlus 15t 8m	15000	15	8	1	110	15	26.1
MagnumPlus 20t 2m	20000	20	2	1.3	140	18	8
MagnumPlus 20t 2.5m	20000	20	2.5	1.3	140	18	10
MagnumPlus 20t 3m	20000	20	3	1.3	140	18	12



Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
MagnumPlus 20t 4m	20000	20	4	1.3	140	18	18.1
MagnumPlus 20t 5m	20000	20	5	1.3	140	18	22.5
MagnumPlus 20t 6m	20000	20	6	1.3	140	18	26.9
MagnumPlus 20t 7m	20000	20	7	1.3	140	18	31.3
MagnumPlus 25t 2.5m	25000	25	2.5	1.3	153	25	12.5
MagnumPlus 25t 3m	25000	25	3	1.3	153	25	15
MagnumPlus 25t 4m	25000	25	4	1.3	153	25	22.9
MagnumPlus 25t 5m	25000	25	5	1.3	153	25	28.5
MagnumPlus 25t 6m	25000	25	6	1.3	153	25	34.1
MagnumPlus 25t 7m	25000	25	7	1.3	153	25	39.7
MagnumPlus 25t 8m	25000	25	8	1.3	153	25	45.3
MagnumPlus 30t 3m	30000	30	3	1.3	165	19	19.5
MagnumPlus 30t 4m	30000	30	4	1.3	165	19	30.1
MagnumPlus 30t 5m	30000	30	5	1.3	165	19	37.5
MagnumPlus 30t 6m	30000	30	6	1.3	165	19	44.9
MagnumPlus 30t 7m	30000	30	7	1.3	165	19	52.3
MagnumPlus 30t 8m	30000	30	8	1.3	165	19	59.7
MagnumPlus 40t 3m	40000	40	3	3	180	22	29.1
MagnumPlus 40t 4m	40000	40	4	3	180	22	40.5
MagnumPlus 40t 5m	40000	40	5	3	180	22	50.5



Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Surface de contact sous charge [mm]	Épaisseur de contact sous charge [mm]	Poids net [kg]
MagnumPlus 40t 6m	40000	40	6	3	180	22	60.5
MagnumPlus 40t 7m	40000	40	7	3	180	22	70.5
MagnumPlus 40t 8m	40000	40	8	3	180	22	80.5
MagnumPlus 50t 3m	50000	50	3	3	208	24	37.5
MagnumPlus 50t 4m	50000	50	4	3	208	24	52.5
MagnumPlus 50t 5m	50000	50	5	3	208	24	65.5
MagnumPlus 50t 6m	50000	50	6	3	208	24	78.5
MagnumPlus 50t 7m	50000	50	7	3	208	24	91.5
MagnumPlus 50t 8m	50000	50	8	3	208	24	104.5
MagnumPlus 60t 3m	60000	60	3	3	244	27	49.8
MagnumPlus 60t 4m	60000	60	4	3	244	27	59.7
MagnumPlus 60t 5m	60000	60	5	3	244	27	74.5
MagnumPlus 60t 6m	60000	60	6	3	244	27	89.3
MagnumPlus 60t 7m	60000	60	7	3	244	27	104.1
MagnumPlus 60t 8m	60000	60	8	3	244	27	118.9

Nom court de l'article	Poids par mètre [kg/m]
MagnumPlus 10t 2m	2.2
MagnumPlus 10t 2.5m	2.2
MagnumPlus 10t 3m	2.2
MagnumPlus 10t 4m	2.2
MagnumPlus 10t 5m	2.2
MagnumPlus 10t 6m	2.2



Nom court de l'article	Poids par mètre [kg/m]
MagnumPlus 10t 7m	2.2
MagnumPlus 10t 8m	2.2
MagnumPlus 15t 2m	2.7
MagnumPlus 15t 2.5m	2.7
MagnumPlus 15t 3m	2.7
MagnumPlus 15t 4m	2.7
MagnumPlus 15t 5m	2.7
MagnumPlus 15t 6m	2.7
MagnumPlus 15t 7.0m	2.7
MagnumPlus 15t 8m	2.7
MagnumPlus 20t 2m	4
MagnumPlus 20t 2.5m	4
MagnumPlus 20t 3m	4
MagnumPlus 20t 4m	4
MagnumPlus 20t 5m	4
MagnumPlus 20t 6m	4
MagnumPlus 20t 7m	4
MagnumPlus 25t 2.5m	5
MagnumPlus 25t 3m	5
MagnumPlus 25t 4m	5
MagnumPlus 25t 5m	5
MagnumPlus 25t 6m	5
MagnumPlus 25t 7m	5
MagnumPlus 25t 8m	5
MagnumPlus 30t 3m	6.5
MagnumPlus 30t 4m	6.5
MagnumPlus 30t 5m	6.5
MagnumPlus 30t 6m	6.5
MagnumPlus 30t 7m	6.5
MagnumPlus 30t 8m	6.5
MagnumPlus 40t 3m	9.7
MagnumPlus 40t 4m	9.7
MagnumPlus 40t 5m	9.7



Nom court de l'article	Poids par mètre [kg/m]
MagnumPlus 40t 6m	9.7
MagnumPlus 40t 7m	9.7
MagnumPlus 40t 8m	9.7
MagnumPlus 50t 3m	12.5
MagnumPlus 50t 4m	12.5
MagnumPlus 50t 5m	12.5
MagnumPlus 50t 6m	12.5
MagnumPlus 50t 7m	12.5
MagnumPlus 50t 8m	12.5
MagnumPlus 60t 3m	16.6
MagnumPlus 60t 4m	16.6
MagnumPlus 60t 5m	16.6
MagnumPlus 60t 6m	16.6
MagnumPlus 60t 7m	16.6
MagnumPlus 60t 8m	16.6

NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSCH]

Dimension L1	10000 kg	15000 kg	20000 kg	25000 kg	30000 kg	40000 kg	50000 kg	60000 kg
2 m	2020851 ES100/0200	2027560 ES150/0200	2023220 ES200/0200	-	-	-	-	-
2.5 m	2020997 ES100/0250	2020999 ES150/0250	2021001 ES200/0250	2021003 ES250/0250	-	-	-	-
3 m	2020998 ES100/0300	2021000 ES150/0300	2021002 ES200/0300	2021004 ES250/0300	2021006 ES300/0300	2021008 ES400/0300	2026463 ES500/0300	2026497 ES600/0300
4 m	2002743 ES100/0400	2002745 ES150/0400	2002747 ES200/0400	2002749 ES250/0400	2002751 ES300/0400	2002753 ES400/0400	2002755 ES500/0400	2002757 ES600/0400
5 m	2002744 ES100/0500	2002746 ES150/0500	2002748 ES200/0500	2002750 ES250/0500	2002752 ES300/0500	2002754 ES400/0500	2002756 ES500/0500	2002758 ES600/0500
6 m	2003231 ES100/0600	2003233 ES150/0600	2003235 ES200/0600	2003237 ES250/0600	2003239 ES300/0600	2003241 ES400/0600	2003243 ES500/0600	2003245 ES600/0600
7 m	2003232 ES100/0700	2003234 ES150/0700	2003236 ES200/0700	2003238 ES250/0700	2003240 ES300/0700	2003242 ES400/0700	2003244 ES500/0700	2003246 ES600/0700
8 m	2003728 ES100/0800	2003729 ES150/0800	-	2003731 ES250/0800	2003732 ES300/0800	2003733 ES400/0800	2003734 ES500/0800	2003735 ES600/0800

- Normes
- Matériel principal

EN 1492-2: 2000
Polyester

SpanSet AG
Eichbühlstrasse 31
8618 Oetwil am See
Suisse
Tel.: +41 44 929 70
70
info@spanset.ch
www.spanset.ch



Sous réserve de modifications techniques. Tous droits réservés. Aucune partie de cette fiche technique ne peut être reproduite sous quelque forme que ce soit (impression, photocopie, microfilm ou tout autre procédé) ou traitée, dupliquée ou distribuée à l'aide de systèmes électroniques sans l'autorisation écrite de SpanSet. Cette fiche technique a été préparée avec le plus grand soin ; SpanSet décline toute responsabilité en cas d'erreur ou d'omission. © SpanSet AG - Suisse

**SpanSet
Certified
Safety**

■ Couleur	Orange
■ Plage de température	- 40 tot + 100°C
■ Protection d'étiquette	Oui
■ Contenu des unités d'emballage (UE)	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - Nutzlänge.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

