

Magnum®Plus Flex

Optimal adaptation under load with an elastic sleeve that provides protection and prevents creasing



Item Name short	WLL kg [kg]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight per Meter [kg/m]
MagnumPlus Flex 10t 2m	10000	2	2	88	18	2.1
MagnumPlus Flex 10t 3m	10000	3	2	88	18	2.1
MagnumPlus Flex 10t 4m	10000	4	2	88	18	2.1
MagnumPlus Flex 10t 5m	10000	5	2	88	18	2.1
MagnumPlus Flex 10t 6m	10000	6	2	88	18	2.1
MagnumPlus Flex 10t 7m	10000	7	2	88	18	2.1
MagnumPlus Flex 10t 8m	10000	8	2	88	18	2.1
MagnumPlus Flex 20t 2m	20000	2	2	143	22	4.3
MagnumPlus Flex 20t 3m	20000	3	2	143	22	4.3
MagnumPlus Flex 20t 4m	20000	4	2	143	22	4.3
MagnumPlus Flex 20t 5m	20000	5	2	143	22	4.3
MagnumPlus Flex 20t 6m	20000	6	2	143	22	4.3
MagnumPlus Flex 20t 7m	20000	7	2	143	22	4.3
MagnumPlus Flex 20t 8m	20000	8	2	143	22	4.3
MagnumPlus Flex 30t 3m	30000	3	-	180	25	6.5
MagnumPlus Flex 30t 4m	30000	4	-	180	25	6.5
MagnumPlus Flex 30t 5m	30000	5	-	180	25	6.5
MagnumPlus Flex 30t 6m	30000	6	-	180	25	6.5
MagnumPlus Flex 30t 7m	30000	7	-	180	25	6.5
MagnumPlus Flex 30t 8m	30000	8	-	180	25	6.5



Item Name short	WLL kg [kg]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight per Meter [kg/m]
MagnumPlus Flex 40t 3m	40000	3	3	181	29	7.5
MagnumPlus Flex 40t 4m	40000	4	3	181	29	7.5
MagnumPlus Flex 40t 5m	40000	5	3	181	29	7.5
MagnumPlus Flex 40t 6m	40000	6	3	181	29	7.5
MagnumPlus Flex 40t 7m	40000	7	3	181	29	7.5
MagnumPlus Flex 40t 8m	40000	8	3	181	29	7.5
MagnumPlus Flex 50t 3m	50000	3	3	213	35	10.2
MagnumPlus Flex 50t 4m	50000	4	3	213	35	10.2
MagnumPlus Flex 50t 5m	50000	5	3	213	35	10.2
MagnumPlus Flex 50t 6m	50000	6	3	213	35	10.2
MagnumPlus Flex 50t 7m	50000	7	3	213	35	10.2
MagnumPlus Flex 50t 8m	50000	8	3	213	35	10.2



ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Dimension L1	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg
2 m	2028143 D094296	2028144 D094298	-	-	-
3 m	2027060 D093918	2027072 D093924	2027677 D093930	2027078 D093938	2027084 D093944
4 m	2027061 D093920	2027073 D093925	2027678 D093931	2027079 D093939	2027085 D093945
5 m	2027062 D093921	2027074 D093926	2027679 D093934	2027080 D093940	2027086 D093946
6 m	2027063 D093864	2027075 D093927	2027680 D093935	2027081 D093941	2027087 D093947
7 m	2027064 D093922	2027076 D093928	2027681 D093936	2027082 D093942	2027088 D093948
8 m	2027065 D093923	2027077 D093929	2027682 D093937	2027083 D093943	2027089 D093949

- Colour Orange
- Temperature Range - 40 tot + 100°C
- Packaging Unit (PU) Content 1

1. WLL - working load limit, Nennt Tragfähigkeit. Gilt für Anschlagart direkt.
2. L1 - Nutzlänge.
3. Abweichend von der DIN EN 1492-2 ist der Werkstoff in dieser Rundschlinge bis zu einer Einsatztemperatur von +70°C geeignet.
4. In der DIN EN 1492-2 ist HMPE als Werkstoff nicht aufgeführt und Materialmischungen sind nicht vorgesehen.

