

Magnum®Plus Flex

Optimal adaptation under load with an elastic sleeve that provides protection and prevents creasing



Item Name short	WLL kg [kg]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight per Meter [kg/m]
MagnumPlus Flex 10t 2m	10000	2	2	88	18	2.1
MagnumPlus Flex 10t 3m	10000	3	2	88	18	2.1
MagnumPlus Flex 10t 4m	10000	4	2	88	18	2.1
MagnumPlus Flex 10t 5m	10000	5	2	88	18	2.1
MagnumPlus Flex 10t 6m	10000	6	2	88	18	2.1
MagnumPlus Flex 10t 7m	10000	7	2	88	18	2.1
MagnumPlus Flex 10t 8m	10000	8	2	88	18	2.1
MagnumPlus Flex 20t 2m	20000	2	2	143	22	4.3
MagnumPlus Flex 20t 3m	20000	3	2	143	22	4.3
MagnumPlus Flex 20t 4m	20000	4	2	143	22	4.3
MagnumPlus Flex 20t 5m	20000	5	2	143	22	4.3
MagnumPlus Flex 20t 6m	20000	6	2	143	22	4.3
MagnumPlus Flex 20t 7m	20000	7	2	143	22	4.3
MagnumPlus Flex 20t 8m	20000	8	2	143	22	4.3
MagnumPlus Flex 30t 3m	30000	3	-	180	25	6.5
MagnumPlus Flex 30t 4m	30000	4	-	180	25	6.5
MagnumPlus Flex 30t 5m	30000	5	-	180	25	6.5
MagnumPlus Flex 30t 6m	30000	6	-	180	25	6.5
MagnumPlus Flex 30t 7m	30000	7	-	180	25	6.5
MagnumPlus Flex 30t 8m	30000	8	-	180	25	6.5



Item Name short	WLL kg [kg]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight per Meter [kg/m]
MagnumPlus Flex 40t 3m	40000	3	3	181	29	7.5
MagnumPlus Flex 40t 4m	40000	4	3	181	29	7.5
MagnumPlus Flex 40t 5m	40000	5	3	181	29	7.5
MagnumPlus Flex 40t 6m	40000	6	3	181	29	7.5
MagnumPlus Flex 40t 7m	40000	7	3	181	29	7.5
MagnumPlus Flex 40t 8m	40000	8	3	181	29	7.5
MagnumPlus Flex 50t 3m	50000	3	3	213	35	10.2
MagnumPlus Flex 50t 4m	50000	4	3	213	35	10.2
MagnumPlus Flex 50t 5m	50000	5	3	213	35	10.2
MagnumPlus Flex 50t 6m	50000	6	3	213	35	10.2
MagnumPlus Flex 50t 7m	50000	7	3	213	35	10.2
MagnumPlus Flex 50t 8m	50000	8	3	213	35	10.2

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Dimension L1	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg
2 m	2028143	2028144	-	-	-
3 m	2027060	2027072	2027677	2027078	2027084
4 m	2027061	2027073	2027678	2027079	2027085
5 m	2027062	2027074	2027679	2027080	2027086
6 m	2027063	2027075	2027680	2027081	2027087
7 m	2027064	2027076	2027681	2027082	2027088
8 m	2027065	2027077	2027682	2027083	2027089

- Colour Orange
- Temperature Range - 40 tot + 100°C

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
 Certified
 Safety**

■ Packaging Unit (PU) Content 1

1. WLL - working load limit, Nenntragfähigkeit. Gilt für Anschlagart direkt.
2. LT - Nutzlänge.
3. Abweichend von der DIN EN 1492-2 ist der Werkstoff in dieser Rundschlinge bis zu einer Einsatztemperatur von +70°C geeignet.
4. In der DIN EN 1492-2 ist HMPE als Werkstoff nicht aufgeführt und Materialmischungen sind nicht vorgesehen.

