




Manilha em forma de lira com pino

Pino roscado para (des)montagem rápida.

Nome curto do item	CMU [kg]	CMU [t]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]
G4-1-005	500	0.5	28.5	8	6	10	13
G4-1-007	750	0.75	31	10	8	10.5	14
G4-1-010	1000	1	37	11	10	13	17
G4-1-015	1500	1.5	43	13	11	14.5	18
G4-1-020	2000	2	48	16	13	16.5	21
G4-1-032	3250	3.25	60	19	16	21.5	27
G4-1-047	4750	4.75	71	22	19	25.5	32
G4-1-065	6500	6.5	84	25	22	29	37
G4-1-085	8500	8.5	95	28	25	34	43
G4-1-095	9500	9.5	108	32	30	37	46
G4-1-120	12000	12	119	35	32	41	51
G4-1-135	13500	13.5	132	38	35	45	57
G4-1-170	17000	17	146	40	40	49	60
G4-1-250	25000	25	178	45	45	63.5	73
G4-1-350	35000	35	197	50	50	73	83
G4-1-550	55000	55	230	65	65	90	105



NÚMEROS DE ORDEM[Global Item Number/Local ERP Number SSES]

CMU	G4-1-005	G4-1-007	G4-1-010	G4-1-015	G4-1-020	G4-1-032	G4-1-047	G4-1-065	G4-1-080
0.5 t	2025777 C83G4100080050X	-	-	-	-	-	-	-	-
0.75 t	-	2025778 C83G4100100070X	-	-	-	-	-	-	-
1 t	-	-	2025785 C83G4100110100X	-	-	-	-	-	-
1.5 t	-	-	-	2025786 C83G4100130150X	-	-	-	-	-
2 t	-	-	-	-	2025787 C83G4100160200X	-	-	-	-
3.25 t	-	-	-	-	-	2025788 C83G4100190320X	-	-	-
4.75 t	-	-	-	-	-	-	2025789 C83G4100220470X	-	-
6.5 t	-	-	-	-	-	-	-	2025790 C83G4100250650X	-
8.5 t	-	-	-	-	-	-	-	-	2025791 C83G4100280000X
9.5 t	-	-	-	-	-	-	-	-	-
12 t	-	-	-	-	-	-	-	-	-
13.5 t	-	-	-	-	-	-	-	-	-
17 t	-	-	-	-	-	-	-	-	-
25 t	-	-	-	-	-	-	-	-	-
35 t	-	-	-	-	-	-	-	-	-
55 t	-	-	-	-	-	-	-	-	-

CMU	G4-1-135	G4-1-170	G4-1-250	G4-1-350	G4-1-550
0.5 t	-	-	-	-	-
0.75 t	-	-	-	-	-
1 t	-	-	-	-	-
1.5 t	-	-	-	-	-
2 t	-	-	-	-	-
3.25 t	-	-	-	-	-
4.75 t	-	-	-	-	-
6.5 t	-	-	-	-	-



CMU	G4-1-135	G4-1-170	G4-1-250	G4-1-350	G4-1-550
8.5 t	-	-	-	-	-
9.5 t	-	-	-	-	-
12 t	-	-	-	-	-
13.5 t	2025794 C83G4100381350X	-	-	-	-
17 t	-	2025795 C83G4100400170X	-	-	-
25 t	-	-	2025796 C83G4100502500X	-	-
35 t	-	-	-	2025797 C83G4100573500X	-
55 t	-	-	-	-	2025798 G4-1-550

- Normas EN 13889
- Material principal Aço
- Cor Cinza
- Gama de temperaturas -20 °C to + 200 °C
- Unidade de embalagem (PU) Contém 1

