




MaXafe 55mm

5000daN to 10000daN Lashing capacity webbing lashing strap, ideal for transverse and diagonal lashing of heavy vehicles and machines

Item Name short	L1 [m]	Lashing End Fitting Component	Weight Net [kg]
MaXafe LC5000/55 2pc 3m DJHS	3	DJHS-50	4.50
MaXafe LC5000/55 2pc 3m DH	3	DH-50	6.50
MaXafe LC5000/55 2pc 4m DJHS	4	DJHS-50	4.70
MaXafe LC5000/55 2pc 4m DH	4	DH-50	6.70



ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Lashing Capacity	Lashing End Fitting Component	3 m	4 m
5000 daN	 DJHS-50	2005985 01825-2-SPH-3M	2005986 01825-2-SPH-4M
5000 daN	 DH-50	2005988 01825-2-LS-3M	2005989 01825-2-LS-4M

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Webbing Material	High-performance webbing low expansion <2 %
■ Colour	Green
■ Webbing Width B	55 mm
■ Lashing Capacity	5'000 daN
■ Anti Belt Slip (ABS)	No
■ Tension Force Indicator (TFI)	No
■ Label Protection	Yes
■ Handle Type	Long Wide
■ Packaging Unit (PU) Content	1

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet
Certified
Safety**

