

Morse di sollevamento Exoset

La pinza perfetta per l'uso professionale

Nome articolo breve	WLL ton [t]	Larghezza apertura ganascia [mm]	For Material	A [mm]	B [mm]	C [mm]	D [mm]
0.5t EVU	0.5	0 - 16	Normal max.37HRC	39	209	134	40
0.5t EVU/H	0.5	0 - 16	Hard max.47HRC	39	209	134	40
0.5t EVU/S	0.5	0 - 16	Acciaio inox max.37HRC	39	209	134	40
0.5t EVU/J	0.5	15 - 30	Normal max.37HRC	39	226	134	40
0.5t EVU/HJ	0.5	15 - 30	Hard max.47HRC	39	226	134	40
0.5t EVU/SJ	0.5	15 - 30	Acciaio inox max.37HRC	39	226	134	40
1t EVU/H	1	0 - 20	Hard max.47HRC	39	22	145	52
1t EVU	1	0 - 20	Normal max.37HRC	39	237	145	52
1t EVU/S	1	0 - 20	Acciaio inox max.37HRC	39	237	145	52
1t EVU/J	1	20 - 40	Normal max.37HRC	39	237	145	52
1t EVU/ HJ	1	20 - 40	Hard max.47HRC	39	237	145	52
1t EVU/ SJ	1	20 - 40	Acciaio inox max.37HRC	39	237	145	52
2t EVU	2	0 - 35	Normal max.37HRC	68	375	209	76
2t EVU/H	2	0 - 35	Hard max.47HRC	68	375	209	76
2t EVU/S	2	0 - 35	Acciaio inox max.37HRC	68	375	209	76
2t EVU/J	2	35 - 70	Normal max.37HRC	68	375	209	76
2t EVU/HJ	2	35 - 70	Hard max.47HRC	68	375	209	76
2t EVU/SJ	2	35 - 70	Acciaio inox max.37HRC	68	375	209	76
3t EVU/H	3	0 - 40	Hard max.47HRC	73	446	262	101
3t EVU/S	3	0 - 40	Acciaio inox max.37HRC	73	446	262	101
3t EVU	3	0 - 40	Normal max.37HRC	73	446	262	101
3t EVU/J	3	40 - 80	Normal max.37HRC	73	446	262	101



Nome articolo breve	WLL ton [t]	Larghezza apertura ganascia [mm]	For Material	A [mm]	B [mm]	C [mm]	D [mm]
3t EVU/HJ	3	40 - 80	Hard max.47HRC	73	446	262	101
3t EVU/SJ	3	40 - 80	Acciaio inox max.37HRC	73	446	262	101
5t EVU	5	0 - 40	Normal max.37HRC	73	446	262	101
5t EVU/H	5	0 - 40	Hard max.47HRC	73	446	262	101
5t EVU/S	5	0 - 40	Acciaio inox max.37HRC	73	446	262	101
5t EVU/J	5	40 - 80	Normal max.37HRC	73	446	262	101
5t EVU/HJ	5	40 - 80	Hard max.47HRC	73	446	262	101
5t EVU/SJ	5	40 - 80	Acciaio inox max.37HRC	73	446	262	101
6t EVU	6	0 - 50	Normal max.37HRC	80	549	327	131
6t EVU/H	6	0 - 50	Hard max.47HRC	80	549	327	131
6t EVU/S	6	0 - 50	Acciaio inox max.37HRC	80	549	327	131
6t EVU/J	6	50 - 100	Normal max.37HRC	80	549	327	131
6t EVU/HJ	6	50 - 100	Hard max.47HRC	80	549	327	131
6t EVU/SJ	6	50 - 100	Acciaio inox max.37HRC	80	549	327	131

Nome articolo breve	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Peso netto [kg]
0.5t EVU	44	22	123	13	20	28	1.9
0.5t EVU/H	44	22	123	13	20	28	1.9
0.5t EVU/S	44	22	123	13	20	28	1.9
0.5t EVU/J	41	41	125	13	20	28	2.0
0.5t EVU/HJ	41	41	125	13	20	28	2.0
0.5t EVU/SJ	41	41	125	13	20	28	2.0
1t EVU/H	46	28	123	13	20	28	2.1
1t EVU	44	28	127	13	20	28	2.1
1t EVU/S	44	28	127	13	20	28	2.1
1t EVU/J	44	51	145	13	20	28	2.6



Nome articolo breve	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Peso netto [kg]
1t EVU/ HJ	44	51	145	13	20	28	2.6
1t EVU/ SJ	44	51	145	13	20	28	2.6
2t EVU	61	48	192	18	32	44	7.6
2t EVU/H	61	48	192	18	32	44	7.6
2t EVU/S	61	48	192	18	32	44	7.6
2t EVU/J	61	87	225	18	32	44	8.9
2t EVU/HJ	61	87	225	18	32	44	8.9
2t EVU/SJ	61	87	225	18	32	44	8.9
3t EVU/H	71	55	225	22	42	58	14.8
3t EVU/S	71	55	225	22	42	58	14.8
3t EVU	71	55	225	22	42	62	14.8
3t EVU/J	71	100	265	22	42	58	13.7
3t EVU/HJ	71	100	265	22	42	58	13.7
3t EVU/SJ	71	100	265	22	42	58	13.7
5t EVU	71	55	225	22	42	62	16
5t EVU/H	71	55	225	22	42	62	16
5t EVU/S	71	55	225	22	42	62	16
5t EVU/J	71	100	265	22	42	62	16.4
5t EVU/ HJ	71	100	265	22	42	62	16.4
5t EVU/SJ	71	100	265	22	42	62	16.4
6t EVU	97	59	280	37	42	62	24
6t EVU/H	97	59	280	37	42	62	24
6t EVU/S	97	59	280	37	42	62	24
6t EVU/J	97	114	330	37	42	62	24.9
6t EVU/HJ	97	114	330	37	42	62	24.9
6t EVU/SJ	97	114	330	37	42	62	24.9



ARTICOLO[Global Item Number/Local ERP Number SSIT]

WLL verticale	For Material	Larghezza apertura ganascia	Larghezza apertura ganascia	0.5 t	1 t	2 t	3 t	5 t	6 t
1100 lbs	Normal max.37HRC	0 - 16 mm	0 - 0.63 in	2002421	-	-	-	-	-
1100 lbs	Normal max.37HRC	15 - 30 mm	0.59 - 1.18 in	2030330 T-2030330	-	-	-	-	-
1100 lbs	Acciaio inox max.37HRC	0 - 16 mm	0 - 0.63 in	2012567	-	-	-	-	-
1100 lbs	Acciaio inox max.37HRC	15 - 30 mm	0.59 - 1.18 in	2030342	-	-	-	-	-
1100 lbs	Hard max.47HRC	0 - 16 mm	0 - 0.63 in	2012561	-	-	-	-	-
1100 lbs	Hard max.47HRC	15 - 30 mm	0.59 - 1.18 in	2030336	-	-	-	-	-
2204 lbs	Normal max.37HRC	0 - 20 mm	0 - 0.79 in	-	2002422	-	-	-	-
2204 lbs	Normal max.37HRC	20 - 40 mm	0.79 - 2.75 in	-	2030331	-	-	-	-
2204 lbs	Acciaio inox max.37HRC	0 - 20 mm	0 - 0.79 in	-	2012568	-	-	-	-
2204 lbs	Acciaio inox max.37HRC	20 - 40 mm	0.79 - 2.75 in	-	2030343	-	-	-	-
2204 lbs	Hard max.47HRC	0 - 20 mm	0 - 0.79 in	-	2012562	-	-	-	-
2204 lbs	Hard max.47HRC	20 - 40 mm	0.79 - 2.75 in	-	2030337	-	-	-	-
4409 lbs	Normal max.37HRC	0 - 35 mm	0 - 1.38 in	-	-	2002423	-	-	-
4409 lbs	Normal max.37HRC	35 - 70 mm	1.38 - 2.75 in	-	-	2030332	-	-	-
4409 lbs	Acciaio inox max.37HRC	0 - 35 mm	0 - 1.38 in	-	-	2012569	-	-	-
4409 lbs	Acciaio inox max.37HRC	35 - 70 mm	1.38 - 2.75 in	-	-	2030344	-	-	-
4409 lbs	Hard max.47HRC	0 - 35 mm	0 - 1.38 in	-	-	2012563	-	-	-
4409 lbs	Hard max.47HRC	35 - 70 mm	1.38 - 2.75 in	-	-	2030338	-	-	-
6613 lbs	Normal max.37HRC	0 - 40 mm	0 - 0.79 in	-	-	-	2002424	-	-
6613 lbs	Normal max.37HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	2030333	-	-
6613 lbs	Acciaio inox max.37HRC	0 - 40 mm	0 - 1.57 in	-	-	-	2012570	-	-
6613 lbs	Acciaio inox max.37HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	2030345	-	-
6613 lbs	Hard max.47HRC	0 - 40 mm	0 - 1.57 in	-	-	-	2012564	-	-
6613 lbs	Hard max.47HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	2030339	-	-
11023 lbs	Normal max.37HRC	0 - 40 mm	0 - 1.57 in	-	-	-	-	2002425	-
11023 lbs	Normal max.37HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	-	2030334	-
11023 lbs	Acciaio inox max.37HRC	0 - 40 mm	0 - 1.57 in	-	-	-	-	2012571	-
11023 lbs	Acciaio inox max.37HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	-	2030346	-
11023 lbs	Hard max.47HRC	0 - 40 mm	0 - 1.57 in	-	-	-	-	2012565	-
11023 lbs	Hard max.47HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	-	2030340	-
13227 lbs	Normal max.37HRC	0 - 50 mm	0 - 1.97 in	-	-	-	-	-	2002426
13227 lbs	Normal max.37HRC	50 - 100 mm	1.97 - 3.94 in	-	-	-	-	-	2030335
13227 lbs	Acciaio inox max.37HRC	0 - 50 mm	0 - 1.97 in	-	-	-	-	-	2012572 T-2012572



WLL verticale	For Material	Larghezza apertura ganascia	Larghezza apertura ganascia	0.5 t	1 t	2 t	3 t	5 t	6 t
13227 lbs	Acciaio inox max.37HRC	50 - 100 mm	1.97 - 3.94 in	-	-	-	-	-	2030347
13227 lbs	Hard max.47HRC	0 - 50 mm	0 - 1.97 in	-	-	-	-	-	2012566 T-2012566
13227 lbs	Hard max.47HRC	50 - 100 mm	1.97 - 3.94 in	-	-	-	-	-	2030341

- **Norme** EN 13155 ASME B30.20 DNV GL
- **Packaging Unit (PU) Contenuto** 1

