


Multi-Leg Sling 1

One leg modular system sling with replaceable components and textile protective sleeve for longer service life

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	L1 max. [m]	Weight for 1m [kg]	Weight per Meter [kg/m]
MLS1 1000 EH/C 1m	1000	1	1	0.38	10	1.4	0.3
MLS1 1000 EH/C 2m	1000	1	2	0.38	10	1.4	0.3
MLS1 1000 EH/C 3m	1000	1	3	0.38	10	1.4	0.3
MLS1 1000 EH/C 4m	1000	1	4	0.38	10	1.4	0.3
MLS1 2000 EH/C 1m	2000	2	1	0.38	10	2.5	0.5
MLS1 2000 EH/C 2m	2000	2	2	0.38	10	2.5	0.5
MLS1 2000 EH/C 3m	2000	2	3	0.38	10	2.5	0.5
MLS1 2000 EH/C 4m	2000	2	4	0.38	10	2.5	0.5
MLS1 3000 EH/C 1m	3000	3	1	0.38	20	3.7	0.8
MLS1 3000 EH/C 2m	3000	3	2	0.38	20	3.7	0.8
MLS1 3000 EH/C 3m	3000	3	3	0.38	20	3.7	0.8
MLS1 3000 EH/C 4m	3000	3	4	0.38	20	3.7	0.8
MLS1 4000 EH/C 1m	4000	4	1	0.38	20	5.7	1
MLS1 4000 EH/C 2m	4000	4	2	0.38	20	5.7	1
MLS1 4000 EH/C 3m	4000	4	3	0.38	20	5.7	1
MLS1 4000 EH/C 4m	4000	4	4	0.38	20	5.7	1
MLS1 5000 EH/C 1m	5000	5	1	0.38	20	6.6	1.1
MLS1 5000 EH/C 2m	5000	5	2	0.38	20	6.6	1.1
MLS1 5000 EH/C 3m	5000	5	3	0.38	20	6.6	1.1
MLS1 5000 EH/C 4m	5000	5	4	0.38	20	6.6	1.1



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	L1 max. [m]	Weight for 1m [kg]	Weight per Meter [kg/m]
MLS1 6000 EH/C 1m	6000	6	1	1	20	9.1	1.4
MLS1 6000 EH/C 2m	6000	6	2	1	20	9.1	1.4
MLS1 6000 EH/C 3m	6000	6	3	1	20	9.1	1.4
MLS1 6000 EH/C 4m	6000	6	4	1	20	9.1	1.4
MLS1 8000 EH/C 1m	8000	8	1	1	20	9.4	1.8
MLS1 8000 EH/C 2m	8000	8	2	1	20	9.4	1.8
MLS1 8000 EH/C 3m	8000	8	3	1	20	9.4	1.8
MLS1 8000 EH/C 4m	8000	8	4	1	20	9.4	1.8
MLS1 10000 EH/C 1m	10000	10	1	2	30	23	2.5
MLS1 10000 EH/C 2m	10000	10	2	2	30	23	2.5
MLS1 10000 EH/C 3m	10000	10	3	2	30	23	2.5
MLS1 10000 EH/C 4m	10000	10	4	2	30	23	2.5
MLS1 15000 EH/C 1m	15000	15	1	2	30	36	3.5
MLS1 15000 EH/C 2m	15000	15	2	2	30	36	3.5
MLS1 15000 EH/C 3m	15000	15	3	2	30	36	3.5
MLS1 15000 EH/C 4m	15000	15	4	2	30	36	3.5
MLS1 20000 EH/C 1m	20000	20	1	2	30	56	5
MLS1 20000 EH/C 2m	20000	20	2	2	30	56	5
MLS1 20000 EH/C 3m	20000	20	3	2	30	56	5
MLS1 20000 EH/C 4m	20000	20	4	2	30	56	5
MLS1 25000 EH/C 1m	25000	25	1	2	30	89	6



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	L1 max. [m]	Weight for 1m [kg]	Weight per Meter [kg/m]
MLS1 25000 EH/C 2m	25000	25	2	2	30	89	6
MLS1 25000 EH/C 3m	25000	25	3	2	30	89	6
MLS1 25000 EH/C 4m	25000	25	4	2	30	89	6
MLS1 30000 EH/C 1m	30000	30	1	2	30	94	8
MLS1 30000 EH/C 2m	30000	30	2	2	30	94	8
MLS1 30000 EH/C 3m	30000	30	3	2	30	94	8
MLS1 30000 EH/C 4m	30000	30	4	2	30	94	8

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

WLL kg	1 m	2 m	3 m	4 m
1000 kg	2024691	2002836	2003306	2003307
2000 kg	2024694	2002838	2003308	2003309
3000 kg	2024697	2002840	2003310	2003311
4000 kg	2024699	2002842	2003312	2003313
5000 kg	2024700	2002844	2003314	2003315
6000 kg	2024701	2002846	2003316	2003317
8000 kg	2024702	2002848	2003318	2003319
10000 kg	2024692	2002850	2003320	2003321
15000 kg	2024693	2002852	2003322	2003323
20000 kg	2024695	2002854	2003324	2003325
25000 kg	2024696	2002856	2003326	2003327
30000 kg	2024698	2002858	2003328	2003329

- Norms EN 1492-2
- Main Material Polyester
- Temperature Range -40°C / +100°C
- Packaging Unit (PU) Content 1

SpanSet Nederland B.V.
Plaza 10A 4782 SK
Moerdijk Nederland
Tel.: +31 (0) 168 38 68 00
info@spanset.nl
www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
Certified
Safety**