

Multi-Leg Sling 4

Four leg modular system sling with replaceable components and textile protective sleeve for longer service life



Item Name short	WLL kg [kg]	WLL t [t]	WLL Single Folded Application [kg]	WLL Single Direct Application [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS4 2100 EH/C 1m	2100	2.1	2100	1500	1	0.38	10
MLS4 2100 EH/C 2m	2100	2.1	2100	1500	2	0.38	10
MLS4 2100 EH/C 3m	2100	2.1	2100	1500	3	0.38	10
MLS4 2100 EH/C 4m	2100	2.1	2100	1500	4	0.38	10
MLS4 4200 EH/C 1m	4200	4.2	4200	3000	1	0.38	10
MLS4 4200 EH/C 2m	4200	4.2	4200	3000	2	0.38	10
MLS4 4200 EH/C 3m	4200	4.2	4200	3000	3	0.38	10
MLS4 4200 EH/C 4m	4200	4.2	4200	3000	4	0.38	10
MLS4 6300 EH/C 1m	6300	6.3	6300	4500	1	0.38	20
MLS4 6300 EH/C 2m	6300	6.3	6300	4500	2	0.38	20
MLS4 6300 EH/C 3m	6300	6.3	6300	4500	3	0.38	20
MLS4 6300 EH/C 4m	6300	6.3	6300	4500	4	0.38	20
MLS4 8400 EH/C 1m	8400	8.4	8400	6000	1	0.38	20
MLS4 8400 EH/C 2m	8400	8.4	8400	6000	2	0.38	20
MLS4 8400 EH/C 3m	8400	8.4	8400	6000	3	0.38	20
MLS4 8400 EH/C 4m	8400	8.4	8400	6000	4	0.38	20
MLS4 10500 EH/C 1m	10500	10.5	10500	7500	1	0.38	20
MLS4 10500 EH/C 2m	10500	10.5	10500	7500	2	0.38	20
MLS4 10500 EH/C 3m	10500	10.5	10500	7500	3	0.38	20



Item Name short	WLL kg [kg]	WLL t [t]	WLL Single Folded Application [kg]	WLL Single Direct Application [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS4 10500 EH/C 4m	10500	10.5	10500	7500	4	0.38	20
MLS4 12600 EH/C 1m	12600	12.6	12600	9000	1	1	20
MLS4 12600 EH/C 2m	12600	12.6	12600	9000	2	1	20
MLS4 12600 EH/C 3m	12600	12.6	12600	9000	3	1	20
MLS4 12600 EH/C 4m	12600	12.6	12600	9000	4	1	20
MLS4 16800 EH/C 1m	16800	16.8	16800	12000	1	1	20
MLS4 16800 EH/C 2m	16800	16.8	16800	12000	2	1	20
MLS4 16800 EH/C 3m	16800	16.8	16800	12000	3	1	20
MLS4 16800 EH/C 4m	16800	16.8	16800	12000	4	1	20
MLS4 21000 EH/C 1m	21000	21	21000	15000	1	1	30
MLS4 21000 EH/C 2m	21000	21	21000	15000	2	1	30
MLS4 21000 EH/C 3m	21000	21	21000	15000	3	1	30
MLS4 21000 EH/C 4m	21000	21	21000	15000	4	1	30
MLS4 31500 EH/C 1m	31500	31.5	31500	22500	1	1	30
MLS4 31500 EH/C 2m	31500	31.5	31500	22500	2	1	30
MLS4 31500 EH/C 3m	31500	31.5	31500	22500	3	1	30
MLS4 31500 EH/C 4m	31500	31.5	31500	22500	4	1	30
MLS4 42000 EH/C 1m	42000	42	42000	30000	1	1	30
MLS4 42000 EH/C 2m	42000	42	42000	30000	2	1	30
MLS4 42000 EH/C 3m	42000	42	42000	30000	3	1	30



Item Name short	WLL kg [kg]	WLL t [t]	WLL Single Folded Application [kg]	WLL Single Direct Application [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS4 42000 EH/C 4m	42000	42	42000	30000	4	1	30
MLS4 52500 EH/C 1m	52500	52.5	52500	37000	1	1	30
MLS4 52500 EH/C 2m	52500	52.5	52500	37500	2	1	30
MLS4 52500 EH/C 3m	52500	52.5	52500	37500	3	1	30
MLS4 52500 EH/C 4m	52500	52.5	52500	37500	4	1	30
MLS4 63000 EH/C 1m	63000	63	63000	45000	1	1	30
MLS4 63000 EH/C 2m	63000	63	63000	45000	2	1	30
MLS4 63000 EH/C 3m	63000	63	63000	45000	3	1	30
MLS4 63000 EH/C 4m	63000	63	63000	45000	4	1	30

Item Name short	Weight for 1m [kg]	Weight per Meter [kg/m]
MLS4 2100 EH/C 1m	9.1	1.2
MLS4 2100 EH/C 2m	9.1	1.2
MLS4 2100 EH/C 3m	9.1	1.2
MLS4 2100 EH/C 4m	9.1	1.2
MLS4 4200 EH/C 1m	11.8	2
MLS4 4200 EH/C 2m	11.8	2
MLS4 4200 EH/C 3m	11.8	2
MLS4 4200 EH/C 4m	11.8	2
MLS4 6300 EH/C 1m	18.4	3.2
MLS4 6300 EH/C 2m	18.4	3.2
MLS4 6300 EH/C 3m	18.4	3.2
MLS4 6300 EH/C 4m	18.4	3.2
MLS4 8400 EH/C 1m	27.1	4
MLS4 8400 EH/C 2m	27.1	4
MLS4 8400 EH/C 3m	27.1	4



Item Name short	Weight for 1m [kg]	Weight per Meter [kg/m]
MLS4 8400 EH/C 4m	27.1	4
MLS4 10500 EH/C 1m	32	4.4
MLS4 10500 EH/C 2m	32	4.4
MLS4 10500 EH/C 3m	32	4.4
MLS4 10500 EH/C 4m	32	4.4
MLS4 12600 EH/C 1m	43	5.6
MLS4 12600 EH/C 2m	43	5.6
MLS4 12600 EH/C 3m	43	5.6
MLS4 12600 EH/C 4m	43	5.6
MLS4 16800 EH/C 1m	46.3	7.2
MLS4 16800 EH/C 2m	46.3	7.2
MLS4 16800 EH/C 3m	46.3	7.2
MLS4 16800 EH/C 4m	46.3	7.2
MLS4 21000 EH/C 1m	102	10
MLS4 21000 EH/C 2m	102	10
MLS4 21000 EH/C 3m	102	10
MLS4 21000 EH/C 4m	102	10
MLS4 31500 EH/C 1m	168	14
MLS4 31500 EH/C 2m	168	14
MLS4 31500 EH/C 3m	168	14
MLS4 31500 EH/C 4m	168	14
MLS4 42000 EH/C 1m	260	20
MLS4 42000 EH/C 2m	260	20
MLS4 42000 EH/C 3m	260	20
MLS4 42000 EH/C 4m	260	20
MLS4 52500 EH/C 1m	343	24
MLS4 52500 EH/C 2m	343	24
MLS4 52500 EH/C 3m	343	24
MLS4 52500 EH/C 4m	343	24
MLS4 63000 EH/C 1m	363	32
MLS4 63000 EH/C 2m	363	32
MLS4 63000 EH/C 3m	363	32
MLS4 63000 EH/C 4m	363	32



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

WLL kg	1 m	2 m	3 m	4 m
2100 kg	2024715	2002884	2003354	2003355
4200 kg	2024716	2002886	2003356	2003357
6300 kg	2024717	2002888	2003358	2003359
8400 kg	2024718	2002890	2003360	2003361
10500 kg	2024719	2002892	2003362	2003363
12600 kg	2024720	2002894	2003364	2003365
16800 kg	2024721	2002896	2003366	2003367
21000 kg	2024722	2002898	2003368	2003369
31500 kg	2024723	2002900	2003370	2003371
42000 kg	2024724	2002902	2003372	2003373
52500 kg	2024725	2002904	2003374	2003375
63000 kg	2024726	2002906	2003376	2003796

■ Norms	EN 1492-2
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C
■ Packaging Unit (PU) Content	1

**SpanSet Nederland
B.V.**
Plaza 10A 4782 SK
Moerdijk Nederland
Tel.: +31 (0) 168 38
68 00
info@spanset.nl
www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
Certified
Safety**