




Nemag Quick Release Link

Quick and straightforward coupling and uncoupling of grabs on cranes

Item Name short	WLL t [t]	Weight Net [kg]
NEMAG NR.10-QRL	12	4.9
NEMAG NR.11-QRL	15	6.2
NEMAG NR.12-QRL	17	7.7
NEMAG NR.13-QRL	21	9.2
NEMAG NR.14-QRL	26	11.5
NEMAG NR.15-QRL	30	14



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

WLL t	NEMAG NR.10-QRL	NEMAG NR.11-QRL	NEMAG NR.12-QRL	NEMAG NR.13-QRL	NEMAG NR.14-QRL	NEMAG NR.15-QRL
12 t	2028595 NEMAG NR.10-QRL	-	-	-	-	-
15 t	-	2028596 NEMAG NR.11-QRL	-	-	-	-
17 t	-	-	2028597 NEMAG NR.12-QRL	-	-	-
21 t	-	-	-	2028599 NEMAG NR.13-QRL	-	-
26 t	-	-	-	-	2028600 NEMAG NR.14-QRL	-
30 t	-	-	-	-	-	2028601 NEMAG NR.15-QRL

- Main Material Steel
- Temperature Range -40° C to + 100° C

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**

