

Pince EXOSET® - Levage vertical

Pince de levage vertical, sûr, maniable et durable. De 0,5 t à 6 t.

Nom court de l'article	WLL [t]	Jaw Opening Width [mm]	Pour les matières	A [mm]	B [mm]	C [mm]	D [mm]
0.5t EVU	0.5	0 - 16	Ordinaire max.37HRC	39	209	134	40
0.5t EVU/H	0.5	0 - 16	Dur max.47HRC	39	209	134	40
0.5t EVU/S	0.5	0 - 16	Inox max.37HRC	39	209	134	40
1t EVU/H	1	0 - 20	Dur max.47HRC	39	22	145	52
1t EVU	1	0 - 20	Ordinaire max.37HRC	39	237	145	52
1t EVU/S	1	0 - 20	Inox max.37HRC	39	237	145	52
2t EVU	2	0 - 35	Ordinaire max.37HRC	68	375	209	76
2t EVU/H	2	0 - 35	Dur max.47HRC	68	375	209	76
2t EVU/S	2	0 - 35	Inox max.37HRC	68	375	209	76
3t EVU/H	3	0 - 40	Dur max.47HRC	73	446	262	101
3t EVU/S	3	0 - 40	Inox max.37HRC	73	446	262	101
3t EVU	3	0 - 40	Ordinaire max.37HRC	73	446	262	101
5t EVU	5	0 - 40	Ordinaire max.37HRC	73	446	262	101
5t EVU/H	5	0 - 40	Dur max.47HRC	73	446	262	101
5t EVU/S	5	0 - 40	Inox max.37HRC	73	446	262	101
6t EVU	6	0 - 50	Ordinaire max.37HRC	80	549	327	131
6t EVU/H	6	0 - 50	Dur max.47HRC	80	549	327	131
6t EVU/S	6	0 - 50	Inox max.37HRC	80	549	327	131

Nom court de l'article	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Poids net [kg]
0.5t EVU	44	22	123	13	20	28	1.9
0.5t EVU/H	44	22	123	13	20	28	1.9
0.5t EVU/S	44	22	123	13	20	28	1.9
1t EVU/H	46	28	123	13	20	28	2.1
1t EVU	44	28	127	13	20	28	2.1
1t EVU/S	44	28	127	13	20	28	2.1
2t EVU	61	48	192	18	32	44	7.6



Nom court de l'article	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Poids net [kg]
2t EVU/H	61	48	192	18	32	44	7.6
2t EVU/S	61	48	192	18	32	44	7.6
3t EVU/H	71	55	225	22	42	58	14.8
3t EVU/S	71	55	225	22	42	58	14.8
3t EVU	71	55	225	22	42	62	14.8
5t EVU	71	55	225	22	42	62	16
5t EVU/H	71	55	225	22	42	62	16
5t EVU/S	71	55	225	22	42	62	16
6t EVU	97	59	280	37	42	62	24
6t EVU/H	97	59	280	37	42	62	24
6t EVU/S	97	59	280	37	42	62	24

NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSFR]

WLL Vertical	Pour les matières	Jaw Opening Width	0.5 t	1 t	2 t	3 t	5 t	6 t
0 - 0.63 in	Ordinaire max.37HRC	0 - 16 mm	2002421	-	-	-	-	-
0 - 0.63 in	Inox max.37HRC	0 - 16 mm	2012567	-	-	-	-	-
0 - 0.63 in	Dur max.47HRC	0 - 16 mm	2012561	-	-	-	-	-
0 - 0.79 in	Ordinaire max.37HRC	0 - 20 mm	-	2002422	-	-	-	-
0 - 0.79 in	Inox max.37HRC	0 - 20 mm	-	2012568	-	-	-	-
0 - 0.79 in	Dur max.47HRC	0 - 20 mm	-	2012562	-	-	-	-
0 - 1.38 in	Ordinaire max.37HRC	0 - 35 mm	-	-	2002423	-	-	-
0 - 1.38 in	Inox max.37HRC	0 - 35 mm	-	-	2012569	-	-	-
0 - 1.38 in	Dur max.47HRC	0 - 35 mm	-	-	2012563	-	-	-
0 - 0.79 in	Ordinaire max.37HRC	0 - 40 mm	-	-	-	2002424	-	-
0 - 1.57 in	Inox max.37HRC	0 - 40 mm	-	-	-	2012570	-	-
0 - 1.57 in	Dur max.47HRC	0 - 40 mm	-	-	-	2012564	-	-
0 - 1.57 in	Ordinaire max.37HRC	0 - 40 mm	-	-	-	-	2002425	-
0 - 1.57 in	Inox max.37HRC	0 - 40 mm	-	-	-	-	2012571	-
0 - 1.57 in	Dur max.47HRC	0 - 40 mm	-	-	-	-	2012565	-
0 - 1.97 in	Ordinaire max.37HRC	0 - 50 mm	-	-	-	-	-	2002426
0 - 1.97 in	Inox max.37HRC	0 - 50 mm	-	-	-	-	-	2012572
0 - 1.97 in	Dur max.47HRC	0 - 50 mm	-	-	-	-	-	2012566



■ Normes	EN 13155 ASME B30.20 DNV GL
■ Contenu des unités d'emballage (UE)	1

