

PowerFlex

Eslinga plana con protección Anti-abrasión por ambas caras para cargas asperas y rugosas.

Nombre corto del Item	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Peso Neto [kg]	Color
PB 1000-P2 1.5m	1000	1	1.5	1	30	-	Morado
PB 1000-P2 2m	1000	1	2	1	30	0.7	Morado
PB 1000-P2 3m	1000	1	3	1	30	1	Morado
PB 1000-P2 4m	1000	1	4	1	30	1.3	Morado
PB 1000-P2 5m	1000	1	5	1	30	1.6	Morado
PB 2000-P2 2m	2000	2	2	1	60	1.6	Verde
PB 2000-P2 3m	2000	2	3	1	60	2.2	Verde
PB 2000-P2 4m	2000	2	4	1	60	2.8	Verde
PB 2000-P2 5m	2000	2	5	1	60	3.4	Verde
PB 3000-P2 2m	3000	3	2	1.3	90	2.1	Amarillo
PB 3000-P2 3m	3000	3	3	1.3	90	2.9	Amarillo
PB 3000-P2 4m	3000	3	4	1.3	90	3.7	Amarillo
PB 3000-P2 5m	3000	3	5	1.3	90	4.5	Amarillo
PB 4000-P2 2m	4000	4	2	1.3	120	2.9	Grís



REFERENCIAS DE PEDIDO[Global Item Number/Local ERP Number SSES]

Dimensión L1	Terminales	1000 kg	2000 kg	3000 kg	4000 kg
1.5 m		2033123 XSP0PPP01001005	-	-	-
2 m		2015456 XSB0PPP01002005	2015462 XSB0PPP02002005	2015469 XSB0PPP03002005	2015474 XSB0PPP04002005
3 m		2015457 XSB0PPP01003005	2015464 XSB0PPP02003005	2015470 XSB0PPP03003005	-
4 m		2015458 XSB0PPP01004005	2015465 XSB0PPP02004005	2015471 XSB0PPP03004005	-
5 m		2015459 XSB0PPP01005005	2015466 XSB0PPP02005005	2015472 XSB0PPP03005005	-

- Normas EN 1492-1: 2000
- Material principal Poliéster
- Rango de temperatura -40°C / +100°C
- Protección de la etiqueta Si
- Unidad de embalaje (PU) Contiene 1

