



PowerStar 2ply

High-strength polyester flat sling with reinforced loops

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 2ply 1t 1m	1000	1	1	1	30	5.6	0.3
PowerStar 2ply 1t 1.5m	1000	1	1.5	1	30	5.6	0.3
PowerStar 2ply 1t 2m	1000	1	2	1	30	5.6	0.3
PowerStar 2ply 1t 3m	1000	1	3	1	30	5.6	0.3
PowerStar 2ply 1t 4m	1000	1	4	1	30	5.6	0.3
PowerStar 2ply 1t 5m	1000	1	5	1	30	5.6	0.3
PowerStar 2ply 1t 6m	1000	1	6	1	30	5.6	0.3
PowerStar 2ply 1t 8m	1000	1	8	1	30	5.6	0.3
PowerStar 2ply 2t 2m	2000	2	2	1	60	5.6	0.6
PowerStar 2ply 2t 3m	2000	2	3	1	60	5.6	0.6
PowerStar 2ply 2t 4m	2000	2	4	1	60	5.6	0.6
PowerStar 2ply 2t 5m	2000	2	5	1	60	5.6	0.6
PowerStar 2ply 2t 6m	2000	2	6	1	60	5.6	0.6
PowerStar 2ply 2t 8m	2000	2	8	1	60	5.6	0.6
PowerStar 2ply 3t 2m	3000	3	2	1.3	90	6	1
PowerStar 2ply 3t 3m	3000	3	3	1.3	90	6	1
PowerStar 2ply 3t 4m	3000	3	4	1.3	90	6	1
PowerStar 2ply 3t 5m	3000	3	5	1.3	90	6	1
PowerStar 2ply 3t 6m	3000	3	6	1.3	90	6	1



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 2ply 3t 8m	3000	3	8	1.3	90	6	1
PowerStar 2ply 4t 2m	4000	4	2	1.3	120	6.2	1.4
PowerStar 2ply 4t 3m	4000	4	3	1.3	120	6.2	1.4
PowerStar 2ply 4t 4m	4000	4	4	1.3	120	6.2	1.4
PowerStar 2ply 4t 5m	4000	4	5	1.3	120	6.2	1.4
PowerStar 2ply 4t 6m	4000	4	6	1.3	120	6.2	1.4
PowerStar 2ply 4t 8m	4000	4	8	1.3	120	6.2	1.4
PowerStar 2ply 5t 2m	5000	5	2	1.5	150	6.4	1.7
PowerStar 2ply 5t 3m	5000	5	3	1.5	150	6.4	1.7
PowerStar 2ply 5t 4m	5000	5	4	1.5	150	6.4	1.7
PowerStar 2ply 5t 5m	5000	5	5	1.5	150	6.4	1.7
PowerStar 2ply 5t 6m	5000	5	6	1.5	150	6.4	1.7
PowerStar 2ply 5t 8m	5000	5	8	1.5	150	6.4	1.7
PowerStar 2ply 6t 2m	6000	6	2	1.9	180	7.6	2.2
PowerStar 2ply 6t 3m	6000	6	3	1.9	180	7.6	2.2
PowerStar 2ply 6t 4m	6000	6	4	1.9	180	7.6	2.2
PowerStar 2ply 6t 5m	6000	6	5	1.9	180	7.6	2.2
PowerStar 2ply 6t 6m	6000	6	6	1.9	180	7.6	2.2
PowerStar 2ply 6t 8m	6000	6	8	1.9	180	7.6	2.2
PowerStar 2ply 8t 3m	8000	8	3	2.2	240	7.6	2.9



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 2ply 8t 4m	8000	8	4	2.2	240	7.6	2.9
PowerStar 2ply 8t 5m	8000	8	5	2.2	240	7.6	2.9
PowerStar 2ply 8t 6m	8000	8	6	2.2	240	7.6	2.9
PowerStar 2ply 8t 8m	8000	8	8	2.2	240	7.6	2.9
PowerStar 2ply 10t 3m	10000	10	3	2.6	300	7.6	4.1
PowerStar 2ply 10t 4m	10000	10	4	2.6	300	7.6	4.1
PowerStar 2ply 10t 5m	10000	10	5	2.6	300	7.6	4.1
PowerStar 2ply 10t 6m	10000	10	6	2.6	300	7.6	4.1
PowerStar 2ply 10t 8m	10000	10	8	2.6	300	7.6	4.1

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
PowerStar 2ply 1t 1m	0.3	0.2	Purple
PowerStar 2ply 1t 1.5m	0.4	0.2	Purple
PowerStar 2ply 1t 2m	0.5	0.2	Purple
PowerStar 2ply 1t 3m	0.7	0.2	Purple
PowerStar 2ply 1t 4m	0.9	0.2	Purple
PowerStar 2ply 1t 5m	1.2	0.2	Purple
PowerStar 2ply 1t 6m	1.4	0.2	Purple
PowerStar 2ply 1t 8m	1.8	0.2	Purple
PowerStar 2ply 2t 2m	1.2	0.4	Green
PowerStar 2ply 2t 3m	1.6	0.4	Green
PowerStar 2ply 2t 4m	2	0.4	Green
PowerStar 2ply 2t 5m	2.4	0.4	Green



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
PowerStar 2ply 2t 6m	2.8	0.4	Green
PowerStar 2ply 2t 8m	3.6	0.4	Green
PowerStar 2ply 3t 2m	2	0.6	Yellow
PowerStar 2ply 3t 3m	2.6	0.6	Yellow
PowerStar 2ply 3t 4m	3.2	0.6	Yellow
PowerStar 2ply 3t 5m	3.8	0.6	Yellow
PowerStar 2ply 3t 6m	4.4	0.6	Yellow
PowerStar 2ply 3t 8m	5.6	0.6	Yellow
PowerStar 2ply 4t 2m	2.8	0.8	Grey
PowerStar 2ply 4t 3m	3.6	0.8	Grey
PowerStar 2ply 4t 4m	4.4	0.8	Grey
PowerStar 2ply 4t 5m	5.2	0.8	Grey
PowerStar 2ply 4t 6m	6	0.8	Grey
PowerStar 2ply 4t 8m	7.6	0.8	Grey
PowerStar 2ply 5t 2m	3.4	1	Red
PowerStar 2ply 5t 3m	4.4	1	Red
PowerStar 2ply 5t 4m	5.4	1	Red
PowerStar 2ply 5t 5m	6.4	1	Red
PowerStar 2ply 5t 6m	7.4	1	Red
PowerStar 2ply 5t 8m	9.4	1	Red
PowerStar 2ply 6t 2m	4.4	1.2	Brown
PowerStar 2ply 6t 3m	5.6	1.2	Brown
PowerStar 2ply 6t 4m	6.8	1.2	Brown
PowerStar 2ply 6t 5m	8	1.2	Brown
PowerStar 2ply 6t 6m	9.2	1.2	Brown
PowerStar 2ply 6t 8m	11.6	1.2	Brown



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
PowerStar 2ply 8t 3m	7.4	1.6	Blue
PowerStar 2ply 8t 4m	9	1.6	Blue
PowerStar 2ply 8t 5m	10.6	1.6	Blue
PowerStar 2ply 8t 6m	12.2	1.6	Blue
PowerStar 2ply 8t 8m	15.4	1.6	Blue
PowerStar 2ply 10t 3m	10.4	2.2	Orange
PowerStar 2ply 10t 4m	12.6	2.2	Orange
PowerStar 2ply 10t 5m	14.8	2.2	Orange
PowerStar 2ply 10t 6m	17	2.2	Orange
PowerStar 2ply 10t 8m	21.4	2.2	Orange

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

WLL kg	1 m	1.5 m	2 m	3 m	4 m	5 m	6 m	8 m
1000 kg	2015118	2030940	2002956 D005051	2003410 D005064	2003411 D005065	2003893 D012009	2003894 D005067	2003895 D015830
2000 kg	-	-	2002958 D005073	2003414 D005077	2003415 D005078	2003899 D005080	2003900 D005081	2003901 D015831
3000 kg	-	-	2002959 D011451	2003416 D005082	2003417 D005084	2003902 D013414	2003903 D010410	2003904 D015834
4000 kg	-	-	2002960 D017383	2003418 D008804	2003419 D008805	2003905 D015847	2003906 D015848	2003907 D015849
5000 kg	-	-	2002961 D015850	2003420 D015851	2003421 D015852	2003908 D015854	2003909 D015853	2003910 D015855
6000 kg	-	-	2002962 D015856	2003422 D015857	2003423 D015858	2003911 D015859	2003912 D015860	2003913 D015861
8000 kg	-	-	-	2002963 D015862	2003424 D015863	2003425 D015864	2003914 D015865	2003915 D015867
10000 kg	-	-	-	2002964 D015868	2003426 D015869	2003427 D015870	2003916 D012097	2003917 D012096

■ Norms	EN 1492-1: 2000
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**

