

PowerStar 2ply with D-links

Robust sling with D-Links resistant to wear and makes this version ideal for lifting procedures involving a noose

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 2ply 1000 DD 2m	1000.00	1	2	1	30	5.6	1.4
PowerStar 2ply 1000 DD 3m	1000.00	1	3	1	30	5.6	1.4
PowerStar 2ply 1000 DD 4m	1000.00	1	4	1	30	5.6	1.4
PowerStar 2ply 1000 DD 5m	1000.00	1	5	1	30	5.6	1.4
PowerStar 2ply 1000 DD 6m	1000.00	1	6	1	30	5.6	1.4
PowerStar 2ply 1000 DD 8m	1000.00	1	8	1	30	5.6	1.4
PowerStar 2ply 2000 DD 2m	2000.00	2	2	1	60	5.6	2.2
PowerStar 2ply 2000 DD 3m	2000.00	2	3	1	60	5.6	2.2
PowerStar 2ply 2000 DD 4m	2000.00	2	4	1	60	5.6	2.2
PowerStar 2ply 2000 DD 5m	2000.00	2	5	1	60	5.6	2.2
PowerStar 2ply 2000 DD 6m	2000.00	2	6	1	60	5.6	2.2
PowerStar 2ply 2000 DD 8m	2000.00	2	8	1	60	5.6	2.2
PowerStar 2ply 3000 DD 2m	3000.00	3	2	1	90	6	4.2
PowerStar 2ply 3000 DD 3m	3000.00	3	3	1	90	6	4.2
PowerStar 2ply 3000 DD 4m	3000.00	3	4	1	90	6	4.2
PowerStar 2ply 3000 DD 5m	3000.00	3	5	1	90	6	4.2
PowerStar 2ply 3000 DD 6m	3000.00	3	6	1	90	6	4.2
PowerStar 2ply 3000 DD 8m	3000.00	3	8	1	90	6	4.2
PowerStar 2ply 4000 DD 2m	4000.00	4	2	1.2	120	6.2	5.4



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 2ply 4000 DD 3m	4000.00	4	3	1.2	120	6.2	5.4
PowerStar 2ply 4000 DD 4m	4000.00	4	4	1.2	120	6.2	5.4
PowerStar 2ply 4000 DD 5m	4000.00	4	5	1.2	120	6.2	5.4
PowerStar 2ply 4000 DD 6m	4000.00	4	6	1.2	120	6.2	5.4
PowerStar 2ply 4000 DD 8m	4000.00	4	8	1.2	120	6.2	5.4
PowerStar 2ply 5000 DD 2m	5000.00	5	2	1.5	150	6.4	9
PowerStar 2ply 5000 DD 3m	5000.00	5	3	1.5	150	6.4	9
PowerStar 2ply 5000 DD 4m	5000.00	5	4	1.5	150	6.4	9
PowerStar 2ply 5000 DD 5m	5000.00	5	5	1.5	150	6.4	9
PowerStar 2ply 5000 DD 6m	5000.00	5	6	1.5	150	6.4	9
PowerStar 2ply 5000 DD 8m	5000.00	5	8	1.5	150	6.4	9
PowerStar 2ply 6000 DD 2m	6000.00	6	2	1.8	180	7.6	15.2
PowerStar 2ply 6000 DD 3m	6000.00	6	3	1.8	180	7.6	15.2
PowerStar 2ply 6000 DD 4m	6000.00	6	4	1.8	180	7.6	15.2
PowerStar 2ply 6000 DD 5m	6000.00	6	5	1.8	180	7.6	15.2
PowerStar 2ply 6000 DD 6m	6000.00	6	6	1.8	180	7.6	15.2
PowerStar 2ply 6000 DD 8m	6000.00	6	8	1.8	180	7.6	15.2
PowerStar 2ply 8000 DD 3m	8000.00	8	3	2.2	240	7.6	22.6
PowerStar 2ply 8000 DD 4m	8000.00	8	4	2.2	240	7.6	22.6
PowerStar 2ply 8000 DD 5m	8000.00	8	5	2.2	240	7.6	22.6



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 2ply 8000 DD 6m	8000.00	8	6	2.2	240	7.6	22.6
PowerStar 2ply 8000 DD 8m	8000.00	8	8	2.2	240	7.6	22.6
PowerStar 2ply 10000 DD 3m	10000	10	3	2.6	300	7.6	35.2
PowerStar 2ply 10000 DD 4m	10000	10	4	2.6	300	7.6	35.2
PowerStar 2ply 10000 DD 5m	10000	10	5	2.6	300	7.6	35.2
PowerStar 2ply 10000 DD 6m	10000	10	6	2.6	300	7.6	35.2
PowerStar 2ply 10000 DD 8m	10000	10	8	2.6	300	7.6	35.2

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
PowerStar 2ply 1000 DD 2m	2.8	0.2
PowerStar 2ply 1000 DD 3m	3	0.2
PowerStar 2ply 1000 DD 4m	3.2	0.2
PowerStar 2ply 1000 DD 5m	3.4	0.2
PowerStar 2ply 1000 DD 6m	3.6	0.2
PowerStar 2ply 1000 DD 8m	4	0.2
PowerStar 2ply 2000 DD 2m	4.4	0.4
PowerStar 2ply 2000 DD 3m	4.8	0.4
PowerStar 2ply 2000 DD 4m	5.2	0.4
PowerStar 2ply 2000 DD 5m	5.6	0.4
PowerStar 2ply 2000 DD 6m	6	0.4
PowerStar 2ply 2000 DD 8m	6.8	0.4
PowerStar 2ply 3000 DD 2m	8.4	0.6
PowerStar 2ply 3000 DD 3m	9	0.6
PowerStar 2ply 3000 DD 4m	9.6	0.6
PowerStar 2ply 3000 DD 5m	10.2	0.6
PowerStar 2ply 3000 DD 6m	10.8	0.6
PowerStar 2ply 3000 DD 8m	12	0.6



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
PowerStar 2ply 4000 DD 2m	10.8	0.8
PowerStar 2ply 4000 DD 3m	11.6	0.8
PowerStar 2ply 4000 DD 4m	12.4	0.8
PowerStar 2ply 4000 DD 5m	13.2	0.8
PowerStar 2ply 4000 DD 6m	14	0.8
PowerStar 2ply 4000 DD 8m	15.6	0.8
PowerStar 2ply 5000 DD 2m	18	1
PowerStar 2ply 5000 DD 3m	19	1
PowerStar 2ply 5000 DD 4m	20	1
PowerStar 2ply 5000 DD 5m	21	1
PowerStar 2ply 5000 DD 6m	22	1
PowerStar 2ply 5000 DD 8m	24	1
PowerStar 2ply 6000 DD 2m	30.4	1.2
PowerStar 2ply 6000 DD 3m	31.6	1.2
PowerStar 2ply 6000 DD 4m	32.8	1.2
PowerStar 2ply 6000 DD 5m	34	1.2
PowerStar 2ply 6000 DD 6m	35.2	1.2
PowerStar 2ply 6000 DD 8m	37.6	1.2
PowerStar 2ply 8000 DD 3m	46.8	1.6
PowerStar 2ply 8000 DD 4m	48.4	1.6
PowerStar 2ply 8000 DD 5m	50	1.6
PowerStar 2ply 8000 DD 6m	51.6	1.6
PowerStar 2ply 8000 DD 8m	54.8	1.6
PowerStar 2ply 10000 DD 3m	72.6	2.2
PowerStar 2ply 10000 DD 4m	74.8	2.2
PowerStar 2ply 10000 DD 5m	77	2.2
PowerStar 2ply 10000 DD 6m	79.2	2.2
PowerStar 2ply 10000 DD 8m	83.6	2.2



ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

WLL kg	2 m	3 m	4 m	5 m	6 m	8 m
1000.00 kg	2002957 D015887	2003412 D015888	2003413 D015891	2003896 D015893	2003897 D015894	2003898 D015895
2000.00 kg	2002965 D015896	2003428 D015897	2003429 D015898	2003918 D015899	2003919 D015900	2003920 D015901
3000.00 kg	2002966 D015902	2003430 D015903	2003431 D015904	2003921 D015905	2003922 D015906	2003923 D015907
4000.00 kg	2002967 D015908	2003432 D015909	2003433 D015910	2003924 D015911	2003925 D015913	2003926 D015914
5000.00 kg	2002968 D015915	2003434 D015916	2003435 D015917	2003927 D015918	2003928 D015919	2003929 D015920
6000.00 kg	2002969 D015921	2003436 D015922	2003437 D015923	2003930 D015924	2003931 D015925	2003932 D015926
8000.00 kg	-	2002970 D015927	2003438 D015928	2003439 D015929	2003933 D015930	2003934 D015931
10000 kg	-	2002971 D015932	2003440 D015933	2003441 D015934	2003935 D015935	2003936 D015937

■ Norms	EN 1492-1: 2000
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**