

PowerStar 4-Couches

Élingue plate très résistante, cousue en quatre couches, est un véritable concentré de puissance!

Nom court de l'article	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Poids pour 1m [kg]	Poids net [kg]
PowerStar PCS 4ply 12000 3m	12000	12	3	2.8	180	3.6	9.6
PowerStar PCS 4ply 12000 4m	12000	12	4	2.8	180	3.6	12
PowerStar PCS 4ply 12000 5m	12000	12	5	2.8	180	3.6	14.4
PowerStar PCS 4ply 12000 6m	12000	12	6	2.8	180	3.6	16.8
PowerStar 4ply 12000 7m	12000	12	7	2.8	180	3.6	18
PowerStar PCS 4ply 12000 8m	12000	12	8	2.8	180	3.6	21.6
PowerStar 4ply 16000 2m	16000	16	2	3	240	4	8.8
PowerStar 4ply 16000 3m	16000	16	3	3	240	4	11.2
PowerStar 4ply 16000 4m	16000	16	4	3	240	4	14.4
PowerStar 4ply 16000 5m	16000	16	5	3	240	4	17.6
PowerStar 4ply 16000 6m	16000	16	6	3	240	4	20.8
PowerStar 4ply 16000 7m	16000	16	7	3	240	4	23.2
PowerStar 4ply 16000 8m	16000	16	8	3	240	4	27.2
PowerStar 4ply 20000 3m	20000	20	3	3.4	300	7	18
PowerStar 4ply 20000 4m	20000	20	4	3.4	300	7	22.8
PowerStar 4ply 20000 5m	20000	20	5	3.4	300	7	27.2
PowerStar 4ply 20000 6m	20000	20	6	3.4	300	7	31.6
PowerStar 4ply 16000 7m	20000	20	7	3.4	300	7	33.4
PowerStar 4ply 20000 8m	20000	20	8	3.4	300	7	40.4



Nom court de l'article	Poids par mètre [kg/m]
PowerStar PCS 4ply 12000 3m	2.4
PowerStar PCS 4ply 12000 4m	2.4
PowerStar PCS 4ply 12000 5m	2.4
PowerStar PCS 4ply 12000 6m	2.4
PowerStar 4ply 12000 7m	2.4
PowerStar PCS 4ply 12000 8m	2.4
PowerStar 4ply 16000 2m	3.2
PowerStar 4ply 16000 3m	3.2
PowerStar 4ply 16000 4m	3.2
PowerStar 4ply 16000 5m	3.2
PowerStar 4ply 16000 6m	3.2
PowerStar 4ply 16000 7m	3.2
PowerStar 4ply 16000 8m	3.2
PowerStar 4ply 20000 3m	4.4
PowerStar 4ply 20000 4m	4.4
PowerStar 4ply 20000 5m	4.4
PowerStar 4ply 20000 6m	4.4
PowerStar 4ply 16000 7m	4.4
PowerStar 4ply 20000 8m	4.4



NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSFR]

Dimension L1	PowerStar PCS 4ply 12000 3m	PowerStar PCS 4ply 12000 4m	PowerStar PCS 4ply 12000 5m	PowerStar PCS 4ply 12000 6m	PowerStar 4ply 12000 7m	PowerStar PCS 4ply 12000 8m	PowerStar 4ply 16000 2m	PowerStar 4ply 16000 3m	PowerStar 4ply 16000 4m	PowerStar 4ply 16000 5m	PowerStar 4ply 16000 6m
2 m	-	-	-	-	-	-	2033073	-	-	-	-
3 m	2002953	-	-	-	-	-	-	2002954	-	-	-
4 m	-	2003404	-	-	-	-	-	-	2003406	-	-
5 m	-	-	2003405	-	-	-	-	-	-	2003407	-
6 m	-	-	-	2003888	-	-	-	-	-	-	2003890
7 m	-	-	-	-	2033017	-	-	-	-	-	-
8 m	-	-	-	-	-	2003889	-	-	-	-	-

Dimension L1	PowerStar 4ply 16000 7m	PowerStar 4ply 16000 8m	PowerStar 4ply 20000 3m	PowerStar 4ply 20000 4m	PowerStar 4ply 20000 5m	PowerStar 4ply 20000 6m	PowerStar 4ply 20000 8m
2 m	-	-	-	-	-	-	-
3 m	-	-	2033074	-	-	-	-
4 m	-	-	-	2002955	-	-	-
5 m	-	-	-	-	2003408	-	-
6 m	-	-	-	-	-	2003409	-
7 m	2033018,2033019	-	-	-	-	-	-
8 m	-	2003891	-	-	-	-	2003892

- Normes EN 1492-1: 2000
- Matériel principal Polyester
- Épaisseur de sangle 15.2 mm
- Plage de température -40°C / +100°C
- Protection d'étiquette Oui
- Contenu des unités d'emballage (UE) 1

SpanSet S.A
Pol.Ind. N° 7 Alm. 6
Barrio de Agaraitz,
Villabona 20150
Gipuzkoa
+33 (0)4 72 47 69 90
commercial@spanset.org
www.spanset.fr



Sous réserve de modifications techniques. Tous droits réservés. Aucune partie de cette fiche technique ne peut être reproduite sous quelque forme que ce soit (impression, photocopie, microfilm ou tout autre procédé) ou traitée, dupliquée ou distribuée à l'aide de systèmes électroniques sans l'autorisation écrite de SpanSet. Cette fiche technique a été préparée avec le plus grand soin ; SpanSet décline toute responsabilité en cas d'erreur ou d'omission. © SpanSet S.A.

**SpanSet
Certified
Safety**