

PowerStar 4-lagig

4-lagig mit Schlaufenverstärkung

Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Gurtbandbreite [mm]	Dicke des Gurtbandes in mm [mm]	Gewicht für 1m [kg]
PowerStar 4ply 2000 2m	2000	2	2	1.1	30	11.2	0.5
PowerStar 4ply 2000 3m	2000	2	3	1.1	30	11.2	0.5
PowerStar 4ply 2000 4m	2000	2	4	1.1	30	11.2	0.5
PowerStar 4ply 2000 5m	2000	2	5	1.1	30	11.2	0.5
PowerStar 4ply 2000 6m	2000	2	6	1.1	30	11.2	0.5
PowerStar 4ply 2000 8m	2000	2	8	1.1	30	11.2	0.5
PowerStar 4ply 4000 2m	4000	4	2	1.3	60	11.2	1
PowerStar 4ply 4000 3m	4000	4	3	1.3	60	11.2	1
PowerStar 4ply 4000 4m	4000	4	4	1.3	60	11.2	1
PowerStar 4ply 4000 5m	4000	4	5	1.3	60	11.2	1
PowerStar 4ply 4000 6m	4000	4	6	1.3	60	11.2	1
PowerStar 4ply 4000 8m	4000	4	8	1.3	60	11.2	1
PowerStar 4ply 6000 2m	6000	6	2	1.7	90	12	1.5
PowerStar 4ply 6000 3m	6000	6	3	1.7	90	12	1.5
PowerStar 4ply 6000 4m	6000	6	4	1.7	90	12	1.5
PowerStar 4ply 6000 5m	6000	6	5	1.7	90	12	1.5
PowerStar 4ply 6000 6m	6000	6	6	1.7	90	12	1.5
PowerStar 4ply 6000 8m	6000	6	8	1.7	90	12	1.5
PowerStar 4ply 8000 3m	8000	8	3	2.2	120	12.4	2.2



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Gurtbandbreite [mm]	Dicke des Gurtbandes in mm [mm]	Gewicht für 1m [kg]
PowerStar 4ply 8000 4m	8000	8	4	2.2	120	12.4	2.2
PowerStar 4ply 8000 5m	8000	8	5	2.2	120	12.4	2.2
PowerStar 4ply 8000 6m	8000	8	6	2.2	120	12.4	2.2
PowerStar 4ply 8000 8m	8000	8	8	2.2	120	12.4	2.2
PowerStar 4ply 10000 3m	10000	10	3	2.4	150	12.8	2.9
PowerStar 4ply 10000 4m	10000	10	4	2.4	150	12.8	2.9
PowerStar 4ply 10000 5m	10000	10	5	2.4	150	12.8	2.9
PowerStar 4ply 10000 6m	10000	10	6	2.4	150	12.8	2.9
PowerStar 4ply 10000 8m	10000	10	8	2.4	150	12.8	2.9
PowerStar PCS 4ply 12000 3m	12000	12	3	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 4m	12000	12	4	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 5m	12000	12	5	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 6m	12000	12	6	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 8m	12000	12	8	2.8	180	15.2	3.6
PowerStar 4ply 16000 3m	16000	16	3	3	240	15.2	4
PowerStar 4ply 16000 4m	16000	16	4	3	240	15.2	4
PowerStar 4ply 16000 5m	16000	16	5	3	240	15.2	4
PowerStar 4ply 16000 6m	16000	16	6	3	240	15.2	4
PowerStar 4ply 16000 8m	16000	16	8	3	240	15.2	4
PowerStar 4ply 20000 4m	20000	20	4	3.4	300	15.2	7



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	Gurtbandbreite [mm]	Dicke des Gurtbandes in mm [mm]	Gewicht für 1m [kg]
PowerStar 4ply 20000 5m	20000	20	5	3.4	300	15.2	7
PowerStar 4ply 20000 6m	20000	20	6	3.4	300	15.2	7
PowerStar 4ply 20000 8m	20000	20	8	3.4	300	15.2	7

Artikel Name kurz	Nettogewicht kg [kg]	Gewicht pro Meter [kg/m]
PowerStar 4ply 2000 2m	1	0.4
PowerStar 4ply 2000 3m	1.4	0.4
PowerStar 4ply 2000 4m	1.8	0.4
PowerStar 4ply 2000 5m	2.2	0.4
PowerStar 4ply 2000 6m	2.6	0.4
PowerStar 4ply 2000 8m	3.4	0.4
PowerStar 4ply 4000 2m	2	0.8
PowerStar 4ply 4000 3m	2.8	0.8
PowerStar 4ply 4000 4m	3.6	0.8
PowerStar 4ply 4000 5m	4.4	0.8
PowerStar 4ply 4000 6m	5.2	0.8
PowerStar 4ply 4000 8m	6.8	0.8
PowerStar 4ply 6000 2m	3	1.2
PowerStar 4ply 6000 3m	4.2	1.2
PowerStar 4ply 6000 4m	5.4	1.2
PowerStar 4ply 6000 5m	6.6	1.2
PowerStar 4ply 6000 6m	7.8	1.2
PowerStar 4ply 6000 8m	10.2	1.2
PowerStar 4ply 8000 3m	6	1.6
PowerStar 4ply 8000 4m	7.6	1.6
PowerStar 4ply 8000 5m	9.2	1.6
PowerStar 4ply 8000 6m	10.8	1.6
PowerStar 4ply 8000 8m	14	1.6
PowerStar 4ply 10000 3m	7.8	2
PowerStar 4ply 10000 4m	9.8	2



Artikel Name kurz	Nettogewicht kg [kg]	Gewicht pro Meter [kg/m]
PowerStar 4ply 10000 5m	11.8	2
PowerStar 4ply 10000 6m	13.8	2
PowerStar 4ply 10000 8m	17.8	2
PowerStar PCS 4ply 12000 3m	9.6	2.4
PowerStar PCS 4ply 12000 4m	12	2.4
PowerStar PCS 4ply 12000 5m	14.4	2.4
PowerStar PCS 4ply 12000 6m	16.8	2.4
PowerStar PCS 4ply 12000 8m	21.6	2.4
PowerStar 4ply 16000 3m	11.2	3.2
PowerStar 4ply 16000 4m	14.4	3.2
PowerStar 4ply 16000 5m	17.6	3.2
PowerStar 4ply 16000 6m	20.8	3.2
PowerStar 4ply 16000 8m	27.2	3.2
PowerStar 4ply 20000 4m	22.8	4.4
PowerStar 4ply 20000 5m	27.2	4.4
PowerStar 4ply 20000 6m	31.6	4.4
PowerStar 4ply 20000 8m	40.4	4.4



BESTELLNUMMERN[Global Item Number/Local ERP Number SSDE]

Länge L1	PowerStar 4ply 2000 2m	PowerStar 4ply 2000 3m	PowerStar 4ply 2000 4m	PowerStar 4ply 2000 5m	PowerStar 4ply 2000 6m	PowerStar 4ply 2000 8m	PowerStar 4ply 4000 2m	PowerStar 4ply 4000 3m	PowerStar 4ply 4000 4m	PowerStar 4ply 4000 5m	PowerStar 4ply 4000 6m
2 m	2002944 D012345	-	-	-	-	-	2002948 D015950	-	-	-	-
3 m	-	2002945 D015945	-	-	-	-	-	2002949 D015951	-	-	-
4 m	-	-	2003395 D015946	-	-	-	-	-	2003397 D011654	-	-
5 m	-	-	-	2003870 D015947	-	-	-	-	-	2003876 D015952	-
6 m	-	-	-	-	2003871 D015948	-	-	-	-	-	2003877 D015954
8 m	-	-	-	-	-	2003872 D015949	-	-	-	-	-

Länge L1	PowerStar 4ply 4000 8m	PowerStar 4ply 6000 2m	PowerStar 4ply 6000 3m	PowerStar 4ply 6000 4m	PowerStar 4ply 6000 5m	PowerStar 4ply 6000 6m	PowerStar 4ply 6000 8m	PowerStar 4ply 8000 3m	PowerStar 4ply 8000 4m	PowerStar 4ply 8000 5m	PowerStar 4ply 8000 6m
2 m	-	2002950 D015956	-	-	-	-	-	-	-	-	-
3 m	-	-	2003398 D015957	-	-	-	-	2002951 D015962	-	-	-
4 m	-	-	-	2003399 D010722	-	-	-	-	2003400 D015963	-	-
5 m	-	-	-	-	2003881 D015958	-	-	-	-	2003401 D015964	-
6 m	-	-	-	-	-	2003882 D015960	-	-	-	-	2003884 D015965
8 m	2003878 D015955	-	-	-	-	-	2003883 D015961	-	-	-	-

Länge L1	PowerStar 4ply 8000 8m	PowerStar 4ply 10000 3m	PowerStar 4ply 10000 4m	PowerStar 4ply 10000 5m	PowerStar 4ply 10000 6m	PowerStar 4ply 10000 8m	PowerStar PCS 4ply 12000 3m	PowerStar PCS 4ply 12000 4m	PowerStar PCS 4ply 12000 5m	PowerStar PCS 4ply 12000 6m	PowerStar PCS 4ply 12000 8m	PowerStar 4ply 16000 3m
2 m	-	-	-	-	-	-	-	-	-	-	-	-
3 m	-	2002952 D015967	-	-	-	-	2002953 D015971	-	-	-	-	2002954 D015976
4 m	-	-	2003402 D010723	-	-	-	-	2003404 D010781	-	-	-	-



Länge L1	PowerStar 4ply 8000 8m	PowerStar 4ply 10000 3m	PowerStar 4ply 10000 4m	PowerStar 4ply 10000 5m	PowerStar 4ply 10000 6m	PowerStar 4ply 10000 8m	PowerStar PCS 4ply 12000 3m	PowerStar PCS 4ply 12000 4m	PowerStar PCS 4ply 12000 5m	PowerStar PCS 4ply 12000 6m	PowerStar PCS 4ply 12000 8m	PowerStar 4ply 16000 3m
5 m	-	-	-	2003403 D015968	-	-	-	-	2003405 D015972	-	-	-
6 m	-	-	-	-	2003886 D012100	-	-	-	-	2003888 D015973	-	-
8 m	2003885 D015966	-	-	-	-	2003887	-	-	-	-	2003889 D015974	-

- Normen EN 1492-1: 2000
- Hauptmaterial Polyester
- Temperaturbereich -40°C / +100°C
- Etikettenschutz Ja
- Verpackungseinheit (VPE) Inhalt 1

