



PowerStar 4ply

Heavy-duty flat sling, which is sewn in four layers, is a true powerhouse!

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 4ply 2000 2m	2000	2	2	1.1	30	11.2	0.5
PowerStar 4ply 2000 3m	2000	2	3	1.1	30	11.2	0.5
PowerStar 4ply 2000 4m	2000	2	4	1.1	30	11.2	0.5
PowerStar 4ply 2000 5m	2000	2	5	1.1	30	11.2	0.5
PowerStar 4ply 2000 6m	2000	2	6	1.1	30	11.2	0.5
PowerStar 4ply 2000 8m	2000	2	8	1.1	30	11.2	0.5
PowerStar 4ply 4000 2m	4000	4	2	1.3	60	11.2	1
PowerStar 4ply 4000 3m	4000	4	3	1.3	60	11.2	1
PowerStar 4ply 4000 4m	4000	4	4	1.3	60	11.2	1
PowerStar 4ply 4000 5m	4000	4	5	1.3	60	11.2	1
PowerStar 4ply 4000 6m	4000	4	6	1.3	60	11.2	1
PowerStar 4ply 4000 8m	4000	4	8	1.3	60	11.2	1
PowerStar 4ply 6000 2m	6000	6	2	1.7	90	12	1.5
PowerStar 4ply 6000 3m	6000	6	3	1.7	90	12	1.5
PowerStar 4ply 6000 4m	6000	6	4	1.7	90	12	1.5
PowerStar 4ply 6000 5m	6000	6	5	1.7	90	12	1.5
PowerStar 4ply 6000 6m	6000	6	6	1.7	90	12	1.5
PowerStar 4ply 6000 8m	6000	6	8	1.7	90	12	1.5
PowerStar 4ply 8000 3m	8000	8	3	2.2	120	12.4	2.2



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 4ply 8000 4m	8000	8	4	2.2	120	12.4	2.2
PowerStar 4ply 8000 5m	8000	8	5	2.2	120	12.4	2.2
PowerStar 4ply 8000 6m	8000	8	6	2.2	120	12.4	2.2
PowerStar 4ply 8000 8m	8000	8	8	2.2	120	12.4	2.2
PowerStar 4ply 10000 3m	10000	10	3	2.4	150	12.8	2.9
PowerStar 4ply 10000 4m	10000	10	4	2.4	150	12.8	2.9
PowerStar 4ply 10000 5m	10000	10	5	2.4	150	12.8	2.9
PowerStar 4ply 10000 6m	10000	10	6	2.4	150	12.8	2.9
PowerStar 4ply 10000 8m	10000	10	8	2.4	150	12.8	2.9
PowerStar PCS 4ply 12000 3m	12000	12	3	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 4m	12000	12	4	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 5m	12000	12	5	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 6m	12000	12	6	2.8	180	15.2	3.6
PowerStar PCS 4ply 12000 8m	12000	12	8	2.8	180	15.2	3.6
PowerStar 4ply 16000 3m	16000	16	3	3	240	15.2	4
PowerStar 4ply 16000 4m	16000	16	4	3	240	15.2	4
PowerStar 4ply 16000 5m	16000	16	5	3	240	15.2	4
PowerStar 4ply 16000 6m	16000	16	6	3	240	15.2	4
PowerStar 4ply 16000 8m	16000	16	8	3	240	15.2	4
PowerStar 4ply 20000 4m	20000	20	4	3.4	300	15.2	7



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
PowerStar 4ply 20000 5m	20000	20	5	3.4	300	15.2	7
PowerStar 4ply 20000 6m	20000	20	6	3.4	300	15.2	7
PowerStar 4ply 20000 8m	20000	20	8	3.4	300	15.2	7

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
PowerStar 4ply 2000 2m	1	0.4
PowerStar 4ply 2000 3m	1.4	0.4
PowerStar 4ply 2000 4m	1.8	0.4
PowerStar 4ply 2000 5m	2.2	0.4
PowerStar 4ply 2000 6m	2.6	0.4
PowerStar 4ply 2000 8m	3.4	0.4
PowerStar 4ply 4000 2m	2	0.8
PowerStar 4ply 4000 3m	2.8	0.8
PowerStar 4ply 4000 4m	3.6	0.8
PowerStar 4ply 4000 5m	4.4	0.8
PowerStar 4ply 4000 6m	5.2	0.8
PowerStar 4ply 4000 8m	6.8	0.8
PowerStar 4ply 6000 2m	3	1.2
PowerStar 4ply 6000 3m	4.2	1.2
PowerStar 4ply 6000 4m	5.4	1.2
PowerStar 4ply 6000 5m	6.6	1.2
PowerStar 4ply 6000 6m	7.8	1.2
PowerStar 4ply 6000 8m	10.2	1.2
PowerStar 4ply 8000 3m	6	1.6
PowerStar 4ply 8000 4m	7.6	1.6
PowerStar 4ply 8000 5m	9.2	1.6
PowerStar 4ply 8000 6m	10.8	1.6
PowerStar 4ply 8000 8m	14	1.6
PowerStar 4ply 10000 3m	7.8	2
PowerStar 4ply 10000 4m	9.8	2



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]
PowerStar 4ply 10000 5m	11.8	2
PowerStar 4ply 10000 6m	13.8	2
PowerStar 4ply 10000 8m	17.8	2
PowerStar PCS 4ply 12000 3m	9.6	2.4
PowerStar PCS 4ply 12000 4m	12	2.4
PowerStar PCS 4ply 12000 5m	14.4	2.4
PowerStar PCS 4ply 12000 6m	16.8	2.4
PowerStar PCS 4ply 12000 8m	21.6	2.4
PowerStar 4ply 16000 3m	11.2	3.2
PowerStar 4ply 16000 4m	14.4	3.2
PowerStar 4ply 16000 5m	17.6	3.2
PowerStar 4ply 16000 6m	20.8	3.2
PowerStar 4ply 16000 8m	27.2	3.2
PowerStar 4ply 20000 4m	22.8	4.4
PowerStar 4ply 20000 5m	27.2	4.4
PowerStar 4ply 20000 6m	31.6	4.4
PowerStar 4ply 20000 8m	40.4	4.4

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

WLL t	2 m	3 m	4 m	5 m	6 m	8 m
2 t	2002944	2002945	2003395	2003870	2003871	2003872
4 t	2002948	2002949	2003397	2003876	2003877	2003878
6 t	2002950	2003398	2003399	2003881	2003882	2003883
8 t	-	2002951	2003400	2003401	2003884	2003885
10 t	-	2002952	2003402	2003403	2003886	2003887
12 t	-	2002953	2003404	2003405	2003888	2003889
16 t	-	2002954	2003406	2003407	2003890	2003891
20 t	-	-	2002955	2003408	2003409	2003892

■ Norms	EN 1492-1: 2000
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
 Certified
 Safety**

