

## PowerStar Webbing sling 2Ply

PowerStar Webbing sling 2-ply from SpanSet, engineered for high-capacity lifting, providing exceptional strength and reliability for industrial applications.

| Item Name short | WLL kg [kg] | WLL t [t] | L1 [m] | Weight for 1m [kg] | Weight Net [kg] | Weight per Meter [kg/m] | Colour |
|-----------------|-------------|-----------|--------|--------------------|-----------------|-------------------------|--------|
| PB1000          | 1000        | 1         | -      | 0.3                | -               | 0.2                     | Purple |
| PB1000-1M-01    | 1000        | 1         | 1      | 0.3                | 0.8             | 0.2                     | Purple |
| PB1000-2M-01    | 1000        | 1         | 2      | 0.3                | 1               | 0.2                     | Purple |
| PB1000-3M-01    | 1000        | 1         | 3      | 0.3                | 1.2             | 0.2                     | Purple |
| PB1000-4M-01    | 1000        | 1         | 4      | 0.3                | 1.4             | 0.2                     | Purple |
| PB1000-5M-01    | 1000        | 1         | 5      | 0.3                | 1.6             | 0.2                     | Purple |
| PB1000-6M-01    | 1000        | 1         | 6      | 0.3                | 1.8             | 0.2                     | Purple |
| PB1000-8M-01    | 1000        | 1         | 8      | 0.3                | 2.2             | 0.2                     | Purple |
| PB1000-10M-01   | 1000        | 1         | 10     | 0.3                | 2.6             | 0.2                     | Purple |
| PB2000          | 2000        | 2         | -      | 0.6                | -               | 0.4                     | Green  |
| PB2000-1M-01    | 2000        | 2         | 1      | 0.6                | 1.1             | 0.4                     | Green  |
| PB2000-2M-01    | 2000        | 2         | 2      | 0.6                | 1.5             | 0.4                     | Green  |
| PB2000-3M-01    | 2000        | 2         | 3      | 0.6                | 1.9             | 0.4                     | Green  |
| PB2000-4M-01    | 2000        | 2         | 4      | 0.6                | 2.3             | 0.4                     | Green  |
| PB2000-5M-01    | 2000        | 2         | 5      | 0.6                | 2.7             | 0.4                     | Green  |
| PB2000-6M-01    | 2000        | 2         | 6      | 0.6                | 3.1             | 0.4                     | Green  |
| PB2000-8M-01    | 2000        | 2         | 8      | 0.6                | 3.9             | 0.4                     | Green  |
| PB2000-10M-01   | 2000        | 2         | 10     | 0.6                | 4.7             | 0.4                     | Green  |
| PB3000          | 3000        | 3         | -      | 1                  | -               | 0.6                     | Yellow |
| PB3000-1M-01    | 3000        | 3         | 1      | 1                  | 1.5             | 0.6                     | Yellow |
| PB3000-2M-01    | 3000        | 3         | 2      | 1                  | 2.1             | 0.6                     | Yellow |
| PB3000-3M-01    | 3000        | 3         | 3      | 1                  | 2.7             | 0.6                     | Yellow |
| PB3000-4M-01    | 3000        | 3         | 4      | 1                  | 3.3             | 0.6                     | Yellow |
| PB3000-5M-01    | 3000        | 3         | 5      | 1                  | 3.9             | 0.6                     | Yellow |
| PB3000-6M-01    | 3000        | 3         | 6      | 1                  | 4.5             | 0.6                     | Yellow |



| Item Name short | WLL kg [kg] | WLL t [t] | L1 [m] | Weight for 1m [kg] | Weight Net [kg] | Weight per Meter [kg/m] | Colour |
|-----------------|-------------|-----------|--------|--------------------|-----------------|-------------------------|--------|
| PB3000-8M-01    | 3000        | 3         | 8      | 1                  | 5.7             | 0.6                     | Yellow |
| PB3000-10M-01   | 3000        | 3         | 10     | 1                  | 6.9             | 0.6                     | Yellow |
| PB4000          | 4000        | 4         | -      | 1.4                | -               | 0.8                     | Grey   |
| PB4000-2M-01    | 4000        | 4         | 2      | 1.4                | 2.7             | 0.8                     | Grey   |
| PB4000-3M-01    | 4000        | 4         | 3      | 1.4                | 3.5             | 0.8                     | Grey   |
| PB4000-4M-01    | 4000        | 4         | 4      | 1.4                | 4.3             | 0.8                     | Grey   |
| PB4000-5M-01    | 4000        | 4         | 5      | 1.4                | 5.1             | 0.8                     | Grey   |
| PB4000-6M-01    | 4000        | 4         | 6      | 1.4                | 5.9             | 0.8                     | Grey   |
| PB4000-8M-01    | 4000        | 4         | 8      | 1.4                | 7.5             | 0.8                     | Grey   |
| PB4000-10M-01   | 4000        | 4         | 10     | 1.4                | 9.1             | 0.8                     | Grey   |
| PB5000          | 5000        | 5         | -      | 1.7                | -               | 1                       | Red    |
| PB5000-2M-01    | 5000        | 5         | 2      | 1.7                | 3.2             | 1                       | Red    |
| PB5000-3M-01    | 5000        | 5         | 3      | 1.7                | 4.2             | 1                       | Red    |
| PB5000-4M-01    | 5000        | 5         | 4      | 1.7                | 5.2             | 1                       | Red    |
| PB5000-5M-01    | 5000        | 5         | 5      | 1.7                | 6.2             | 1                       | Red    |
| PB5000-6M-01    | 5000        | 5         | 6      | 1.7                | 7.2             | 1                       | Red    |
| PB5000-8M-01    | 5000        | 5         | 8      | 1.7                | 9.2             | 1                       | Red    |
| PB5000-10M-01   | 5000        | 5         | 10     | 1.7                | 11.2            | 1                       | Red    |
| PB6000          | 6000        | 6         | -      | 2.2                | -               | 1.2                     | Brown  |
| PB6000-2M-01    | 6000        | 6         | 2      | 2.2                | 3.9             | 1.2                     | Brown  |
| PB6000-3M-01    | 6000        | 6         | 3      | 2.2                | 5.1             | 1.2                     | Brown  |
| PB6000-4M-01    | 6000        | 6         | 4      | 2.2                | 6.3             | 1.2                     | Brown  |
| PB6000-5M-01    | 6000        | 6         | 5      | 2.2                | 7.5             | 1.2                     | Brown  |
| PB6000-6M-01    | 6000        | 6         | 6      | 2.2                | 8.7             | 1.2                     | Brown  |
| PB6000-8M-01    | 6000        | 6         | 8      | 2.2                | 11.1            | 1.2                     | Brown  |
| PB6000-10M-01   | 6000        | 6         | 10     | 2.2                | 13.5            | 1.2                     | Brown  |
| PB8000          | 8000        | 8         | -      | 2.9                | -               | 1.6                     | Blue   |



| Item Name short | WLL kg [kg] | WLL t [t] | L1 [m] | Weight for 1m [kg] | Weight Net [kg] | Weight per Meter [kg/m] | Colour |
|-----------------|-------------|-----------|--------|--------------------|-----------------|-------------------------|--------|
| PB8000-2M-01    | 8000        | 8         | 2      | 2.9                | 5               | 1.6                     | Blue   |
| PB8000-3M-01    | 8000        | 8         | 3      | 2.9                | 6.6             | 1.6                     | Blue   |
| PB8000-4M-01    | 8000        | 8         | 4      | 2.9                | 8.2             | 1.6                     | Blue   |
| PB8000-5M-01    | 8000        | 8         | 5      | 2.9                | 9.8             | 1.6                     | Blue   |
| PB8000-6M-01    | 8000        | 8         | 6      | 2.9                | 11.4            | 1.6                     | Blue   |
| PB8000-8M-01    | 8000        | 8         | 8      | 2.9                | 14.6            | 1.6                     | Blue   |
| PB8000-10M-01   | 8000        | 8         | 10     | 2.9                | 17.8            | 1.6                     | Blue   |
| PB10000         | 10000       | 10        | -      | 4.1                | -               | 2.2                     | Orange |
| PB10000-3M-01   | 10000       | 10        | 3      | 4.1                | 9               | 2.2                     | Orange |
| PB10000-4M-01   | 10000       | 10        | 4      | 4.1                | 11.2            | 2.2                     | Orange |
| PB10000-5M-01   | 10000       | 10        | 5      | 4.1                | 13.4            | 2.2                     | Orange |
| PB10000-6M-01   | 10000       | 10        | 6      | 4.1                | 15.6            | 2.2                     | Orange |
| PB10000-8M-01   | 10000       | 10        | 8      | 4.1                | 20              | 2.2                     | Orange |
| PB10000-10M-01  | 10000       | 10        | 10     | 4.1                | 24.4            | 2.2                     | Orange |



#### ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

| WLL kg   | 1 m                     | 2 m                     | 3 m                      | 4 m                      | 5 m                      | 6 m                      | 8 m                      | 10 m                      |
|----------|-------------------------|-------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|---------------------------|
| 1000 kg  | -                       | 2017742<br>PB1000-2M-01 | 2017743<br>PB1000-3M-01  | 2017744<br>PB1000-4M-01  | 2017745<br>PB1000-5M-01  | 2017746<br>PB1000-6M-01  | 2017747<br>PB1000-8M-01  | 2017748<br>PB1000-10M-01  |
| 1000 kg  | 2017741<br>PB1000-1M-01 | -                       | -                        | -                        | -                        | -                        | -                        | -                         |
| 1000 kg  | -                       | -                       | -                        | -                        | -                        | -                        | -                        | -                         |
| 2000 kg  | -                       | -                       | 2017751<br>PB2000-3M-01  | 2017752<br>PB2000-4M-01  | -                        | 2017754<br>PB2000-6M-01  | 2017755<br>PB2000-8M-01  | 2017756<br>PB2000-10M-01  |
| 2000 kg  | 2017749<br>PB2000-1M-01 | -                       | -                        | -                        | -                        | -                        | -                        | -                         |
| 2000 kg  | -                       | 2017750<br>PB2000-2M-01 | -                        | -                        | 2017753<br>PB2000-5M-01  | -                        | -                        | -                         |
| 3000 kg  | -                       | 2017758<br>PB3000-2M-01 | 2017759<br>PB3000-3M-01  | 2017760<br>PB3000-4M-01  | 2017761<br>PB3000-5M-01  | 2017762<br>PB3000-6M-01  | 2017763<br>PB3000-8M-01  | 2017764<br>PB3000-10M-01  |
| 3000 kg  | 2017757<br>PB3000-1M-01 | -                       | -                        | -                        | -                        | -                        | -                        | -                         |
| 3000 kg  | -                       | -                       | -                        | -                        | -                        | -                        | -                        | -                         |
| 4000 kg  | -                       | 2017765<br>PB4000-2M-01 | 2017766<br>PB4000-3M-01  | 2017767<br>PB4000-4M-01  | 2017768<br>PB4000-5M-01  | 2017769<br>PB4000-6M-01  | 2017770<br>PB4000-8M-01  | 2017771<br>PB4000-10M-01  |
| 5000 kg  | -                       | 2017772<br>PB5000-2M-01 | 2017773<br>PB5000-3M-01  | 2017774<br>PB5000-4M-01  | 2017775<br>PB5000-5M-01  | 2017776<br>PB5000-6M-01  | 2017777<br>PB5000-8M-01  | 2017778<br>PB5000-10M-01  |
| 6000 kg  | -                       | 2017779<br>PB6000-2M-01 | 2017780<br>PB6000-3M-01  | 2017781<br>PB6000-4M-01  | 2017782<br>PB6000-5M-01  | 2017783<br>PB6000-6M-01  | 2017784<br>PB6000-8M-01  | 2017785<br>PB6000-10M-01  |
| 8000 kg  | -                       | 2017786<br>PB8000-2M-01 | 2017787<br>PB8000-3M-01  | 2017788<br>PB8000-4M-01  | 2017789<br>PB8000-5M-01  | 2017790<br>PB8000-6M-01  | 2017791<br>PB8000-8M-01  | 2017792<br>PB8000-10M-01  |
| 10000 kg | -                       | -                       | 2017793<br>PB10000-3M-01 | 2017794<br>PB10000-4M-01 | 2017795<br>PB10000-5M-01 | 2017796<br>PB10000-6M-01 | 2017797<br>PB10000-8M-01 | 2017798<br>PB10000-10M-01 |

|                               |                   |
|-------------------------------|-------------------|
| ■ Norms                       | EN 1492-1: 2000   |
| ■ Main Material               | Polyester         |
| ■ Temperature Range           | -40° C to + 50° C |
| ■ Label Protection            | Yes               |
| ■ Packaging Unit (PU) Content | 1                 |

**SpanSet Indonesia**  
Marunda Center Blok  
F No.20 Segara  
Makmur, Tarumajaya.  
Bekasi, Indonesia.  
17211  
+62 21 285 100 77  
sales@spanset.co.id  
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet  
Certified  
Safety**