



Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ProXafe 1000daN 35mm

Robust with extra wide handle

Item Name short	Lashing Type	Lashing Capacity [daN]	L1 [m]	L2 [m]	L3 [m]	Lashing End Fitting Component
ProXafe LC2000/35 1pc 4m	One-piece	1000	4	-	-	No
ProXafe LC1000/35/STF440 2pc 4m RH	Two-piece	1000	4	0.3	3.7	RH-35
ProXafe LC1000/35/STF440 2pc 4m SHS	Two-piece	1000	4	0.3	3.7	SHS-25
ProXafe LC1000/35/STF440 2pc 4m DJH	Two-piece	1000	4	0.3	3.7	DJH-35
ProXafe LC1000/35/STF440 2pc 6m RH	Two-piece	1000	6	0.3	5.7	RH-35
ProXafe LC1000/35/STF440 2pc 6m SHS	Two-piece	1000	6	0.3	5.7	SHS-25
ProXafe LC1000/35/STF440 2pc 6m DJH	Two-piece	1000	6	0.3	5.7	DJH-35
ProXafe LC2000/35 1pc 6m	-	2000	6	-	-	No



ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Dimension L1	Lashing End Fitting Component		One-piece	Two-piece
4 m		No	2003020 D001564	-
6 m		No	-	-
4 m		SHS-25	-	2003522 D003567
4 m		RH-35	-	2004041 D003559
4 m		DJH-35	-	2003523 D003554
6 m		SHS-25	-	2015260 D003726
6 m		RH-35	-	2015262 D005991
6 m		DJH-35	-	2015261 D003725

■ Norms	EN 12195-2: 2001
■ Webbing Width B	35 mm
■ Standard Tension Force	440 daN
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**