



Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ProXafe 500daN 25mm

Robust, with wide handle

Item Name short	Lashing Type	L1 [m]	L3 [m]	Lashing End Fitting Component
ProXafe LC1000/25 1pc 4m	One-piece	4	-	No
ProXafe LC500/25/TF160 2pc 4m RH	Two-piece	4	3.7	RH-25
ProXafe LC500/25/TF160 2pc 4m AP	Two-piece	4	3.7	AP-25
ProXafe LC500/25/TF160 2pc 4m DJH	Two-piece	4	3.7	DJH-25
ProXafe LC500/25/TF160 2pc 4m SHS	Two-piece	4	3.7	SHS-25
ProXafe LC1000/25 1pc 6m	One-piece	6	-	No
ProXafe LC500/25/TF160 2pc 6m AP	Two-piece	6	3.7	AP-25
ProXafe LC500/25/TF160 2pc 6m DJH	Two-piece	6	3.7	DJH-25
ProXafe LC500/25/TF160 2pc 6m RH	Two-piece	6	3.7	RH-25
ProXafe LC500/25/TF160 2pc 6m SHS	Two-piece	6	3.7	SHS-25

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Dimension L1



No



RH-25



AP-25



DJH-25



SHS-25

4 m	2003021 D001576	2003524 D003525	2003525 D003526	2004043 D003528	2004044 D003529
6 m	2024164 D003216	2024166 D011491	2024168 D006977	2024167 D008365	2024165 D011492

■ Norms	EN 12195-2: 2001
■ Webbing Width B	25 mm
■ Standard Tension Force	160 daN
■ Lashing Capacity	500 daN
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**