



ProXafe 500daN 25mm

Robust, with wide handle

Item Name short	Lashing Type	L3 [m]	Lashing End Fitting Component
ProXafe LC1000/25 1pc 4m	One-piece	-	No
ProXafe LC500/25/TF160 2pc 4m RH	Two-piece	3.7	RH-25
ProXafe LC500/25/TF160 2pc 4m AP	Two-piece	3.7	AP-25
ProXafe LC500/25/TF160 2pc 4m DJH	Two-piece	3.7	DJH-25
ProXafe LC500/25/TF160 2pc 4m SHS	Two-piece	3.7	SHS-25

Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Dimension L1



No



RH-25



AP-25



DJH-25



SHS-25

4 m

2003021

2003524

2003525

2004043

2004044

■ Norms	EN 12195-2: 2001
■ Webbing Width B	25 mm
■ Lashing Capacity	500 daN
■ Standard Tension Force	160 daN
■ Packaging Unit (PU) Content	1

SpanSet Nederland B.V.
Plaza 10A 4782 SK
Moerdijk Nederland
Tel.: +31 (0) 168 38 68 00
info@spanset.nl
www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
Certified
Safety**