

Ratchet Lashing 35mm, LC 500daN



Item Name short	L1 [m]	Weight Net [kg]
1804/1	-	-
1804/1-2M-16	2	0.8
1804/1-4M-16	4	1.2
1804/1-6M-16	6	1.6
1804/1-8M-16	8	2
1804/1-10M-16	10	2.3
1804/1-12M-16	12	2.8

Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Dimension L1	1804/1	1804/1-2M-16	1804/1-4M-16	1804/1-6M-16	1804/1-8M-16	1804/1-10M-16	1804/1-12M-16
-	2028107	-	-	-	-	-	-
2 m	-	2021112 1804/1-2M-16	-	-	-	-	-
4 m	-	-	2021113 1804/1-4M-16	-	-	-	-
6 m	-	-	-	2021114 1804/1-6M-16	-	-	-
8 m	-	-	-	-	2021115 1804/1-8M-16	-	-
10 m	-	-	-	-	-	2021116 1804/1-10M-16	-
12 m	-	-	-	-	-	-	2021117 1804/1-12M-16

■ Norms

EN 12195-2: 2001

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**

■ Surface Coating	Epoxy
■ Webbing Material	Polyester
■ Colour	Orange
■ Webbing Width B	35 mm
■ Lashing Capacity	500 daN
■ Anti Belt Slip (ABS)	No
■ Tension Force Indicator (TFI)	No
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

