

Ratchet Lashing 50mm, LC 25kN



Item Name short	L1 [m]	Weight Net [kg]
1857/1	-	-
1857/1-4M-11	4	2.5
1857/1-6M-11	6	2.7
1857/1-8M-11	8	2.9
1857/1-10M-11	10	3.1
1857/1-12M-11	12	3.3

Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Dimension L1	1857/1	1857/1-4M-11	1857/1-6M-11	1857/1-8M-11	1857/1-10M-11	1857/1-12M-11
-	2028098	-	-	-	-	-
4 m	-	2021095 1857/1-4M-11	-	-	-	-
6 m	-	-	2021096 1857/1-6M-11	-	-	-
8 m	-	-	-	2021097 1857/1-8M-11	-	-
10 m	-	-	-	-	2021098 1857/1-10M-11	-
12 m	-	-	-	-	-	2021099 1857/1-12M-11

■ Norms	EN 12195-2: 2001
■ Surface Coating	Galvanized
■ Webbing Material	Polyester

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**

■ Colour	Orange
■ Webbing Width B	50 mm
■ Lashing Capacity	2'500 daN
■ Anti Belt Slip (ABS)	No
■ Tension Force Indicator (TFI)	No
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

