

Ratchet Lashing ABS 50mm, LC 25kN

Robust and durable ratchet with progressive release, for safe release of tension and no load tipping



Item Name short	L1 [m]	Weight Net [kg]
20020/1	-	-
20020/1-4M-07	4	2.9
20020/1-6M-07	6	3.1
20020/1-8M-07	8	3.3
20020/1-10M-07	10	3.5
20020/1-12M-07	12	3.7

Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Dimension L1	20020/1	20020/1-4M-07	20020/1-6M-07	20020/1-8M-07	20020/1-10M-07	20020/1-12M-07
-	2028111	-	-	-	-	-
4 m	-	2022061 20020/1-4M-07	-	-	-	-
6 m	-	-	2022062 20020/1-6M-07	-	-	-
8 m	-	-	-	2022063 20020/1-8M-07	-	-
10 m	-	-	-	-	2022064 20020/1-10M-07	-
12 m	-	-	-	-	-	2022065 20020/1-12M-07

- Norms EN 12195-2: 2001
- Surface Coating Epoxy
- Webbing Material Polyester, thermofixed and low-stretch <4%

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**

■ Colour	Yellow
■ Webbing Width B	50 mm
■ Lashing Capacity	2'500 daN
■ Standard Tension Force	450 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Standard
■ Packaging Unit (PU) Content	1

