

Ratchet Lashing ABS 75mm, LC 50kN

Transport heavy loads safely with progressive release, for safe release of tension and no load tipping



Item Name short	L1 [m]	Weight Net [kg]
20040/1	-	-
20040/1-4M-11	4	4.8
20040/1-6M-11	6	5.3
20040/1-8M-11	8	5.8
20040/1-10M-11	10	6.3
20040/1-12M-11	12	6.8

Lashing Configuration

1-Piece



Lashing Configuration

2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Dimension L1	20040/1	20040/1-4M-11	20040/1-6M-11	20040/1-8M-11	20040/1-10M-11	20040/1-12M-11
-	2028988	-	-	-	-	-
4 m	-	2020386 20040/1-4M-11	-	-	-	-
6 m	-	-	2020388 20040/1-6M-11	-	-	-
8 m	-	-	-	2020390 20040/1-8M-11	-	-
10 m	-	-	-	-	2020391 20040/1-10M-11	-
12 m	-	-	-	-	-	2020393 20040/1-12M-11

- Norms EN 12195-2: 2001
- Surface Coating Epoxy
- Webbing Material Polyester, thermofixed and low-stretch <4%

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**

■ Colour	Yellow
■ Webbing Width B	75 mm
■ Lashing Capacity	5'000 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Standard
■ Packaging Unit (PU) Content	1

