

### Ratchet Lashing Power Assisted, 75mm



Item Name short	L1 [m]	Weight Net [kg]
20031/2	-	-
20031/2-4M	4	17
20031/2-6M	6	18
20031/2-8M	8	19
20031/2-10M	10	20
20031/2-12M	12	21

Lashing Configuration

### 1-Piece



Lashing Configuration

### 2-Piece



### ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Dimension L1	20031/2	20031/2-4M	20031/2-6M	20031/2-8M	20031/2-10M	20031/2-12M
-	2028987	-	-	-	-	-
4 m	-	2022105 20031/2-4M	-	-	-	-
6 m	-	-	2022106 20031/2-6M	-	-	-
8 m	-	-	-	2022107 20031/2-8M	-	-
10 m	-	-	-	-	2022108 20031/2-10M	-
12 m	-	-	-	-	-	2022109 20031/2-12M

- Norms EN 12195-2: 2001
- Surface Coating Epoxy
- Webbing Material Polyester, thermofixed and low-stretch <4%

**SpanSet Indonesia**  
Marunda Center Blok  
F No.20 Segara  
Makmur, Tarumajaya.  
Bekasi, Indonesia.  
17211  
+62 21 285 100 77  
sales@spanset.co.id  
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet  
Certified  
Safety**

■ Colour	Yellow
■ Webbing Width B	75 mm
■ Lashing Capacity	10'000 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Standard
■ Packaging Unit (PU) Content	1

