

Rondstropsamenstelling 2-sprong

Economisch hijsen met SpanSet-oophangsystemen met rondstropen



Item Naam kort	WLL [kg]	WLL [t]	WLL Enkelvoudige gevouwen toepassing [kg]	WLL Enkelvoudige directe toepassing [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS2 1400 EH/C 1m	1400	1.4	1400.0	1000.0	1	1	10
MLS2 1400 EH/C 2m	1400	1.4	1400.0	1000.0	2	1	10
MLS2 1400 EH/C 3m	1400	1.4	1400.0	1000.0	3	1	10
MLS2 1400 EH/C 4m	1400	1.4	1400.0	1000.0	4	1	10
MLS2 2800 EH/C 1m	2800	2.8	2800.0	2000.0	1	1	10
MLS2 2800 EH/C 2m	2800	2.8	2800.0	2000.0	2	1	10
MLS2 2800 EH/C 3m	2800	2.8	2800.0	2000.0	3	1	10
MLS2 2800 EH/C 4m	2800	2.8	2800.0	2000.0	4	1	10
MLS2 4200 EH/C 1m	4200	4.2	4200.0	3000.0	1	1	20
MLS2 4200 EH/C 2m	4200	4.2	4200.0	3000.0	2	1	20
MLS2 4200 EH/C 3m	4200	4.2	4200.0	3000.0	3	1	20
MLS2 4200 EH/C 4m	4200	4.2	4200.0	3000.0	4	1	20
MLS2 5600 EH/C 1m	5600	5.6	5600.0	4000.0	1	0.38	20
MLS2 5600 EH/C 2m	5600	5.6	5600.0	4000.0	2	0.38	20
MLS2 5600 EH/C 3m	5600	5.6	5600.0	4000.0	3	0.38	20
MLS2 5600 EH/C 4m	5600	5.6	5600.0	4000.0	4	0.38	20
MLS2 7000 EH/C 1m	7000	7	7000.0	5000.0	1	0.38	20
MLS2 7000 EH/C 2m	7000	7	7000.0	5000.0	2	0.38	20
MLS2 7000 EH/C 3m	7000	7	7000.0	5000.0	3	0.38	20



Item Naam kort	WLL [kg]	WLL [t]	WLL Enkelvoudige gevouwen toepassing [kg]	WLL Enkelvoudige directe toepassing [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS2 7000 EH/C 4m	7000	7	7000.0	5000.0	4	0.38	20
MLS2 8400 EH/C 1m	8400	8.4	8400.0	6000.0	1	1	20
MLS2 8400 EH/C 2m	8400	8.4	8400.0	6000.0	2	1	20
MLS2 8400 EH/C 3m	8400	8.4	8400.0	6000.0	3	1	20
MLS2 8400 EH/C 4m	8400	8.4	8400.0	6000.0	4	1	20
MLS2 11200 EH/C 1m	11200	11.2	11200.0	8000.0	1	1	20
MLS2 11200 EH/C 2m	11200	11.2	11200.0	8000.0	2	1	20
MLS2 11200 EH/C 3m	11200	11.2	11200.0	8000.0	3	1	20
MLS2 11200 EH/C 4m	11200	11.2	11200.0	8000.0	4	1	20
MLS2 14000 EH/C 1m	14000	14	14000.0	10000.0	1	2	30
MLS2 14000 EH/C 2m	14000	14	14000.0	10000.0	2	2	30
MLS2 14000 EH/C 3m	14000	14	14000.0	10000.0	3	2	30
MLS2 14000 EH/C 4m	14000	14	14000.0	10000.0	4	2	30
MLS2 21000 EH/C 1m	21000	21	21000.0	15000.0	1	2	30
MLS2 21000 EH/C 2m	21000	21	21000.0	15000.0	2	2	30
MLS2 21000 EH/C 3m	21000	21	21000.0	15000.0	3	2	30
MLS2 21000 EH/C 4m	21000	21	21000.0	15000.0	4	2	30
MLS2 28000 EH/C 1m	28000	28	28000.0	20000.0	1	1	30
MLS2 28000 EH/C 2m	28000	28	28000.0	20000.0	2	1	30
MLS2 28000 EH/C 3m	28000	28	28000.0	20000.0	3	1	30



Item Naam kort	WLL [kg]	WLL [t]	WLL Enkelvoudige gevouwen toepassing [kg]	WLL Enkelvoudige directe toepassing [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS2 28000 EH/C 4m	28000	28	28000.0	20000.0	4	1	30
MLS2 35000 EH/C 1m	35000	35	35000.0	25000.0	1	1	30
MLS2 35000 EH/C 2m	35000	35	35000.0	25000.0	2	1	30
MLS2 35000 EH/C 3m	35000	35	35000.0	25000.0	3	1	30
MLS2 35000 EH/C 4m	35000	35	35000.0	25000.0	4	1	30
MLS2 42000 EH/C 1m	42000	42	42000.0	30000.0	1	1	30
MLS2 42000 EH/C 2m	42000	42	42000.0	30000.0	2	1	30
MLS2 42000 EH/C 3m	42000	42	42000.0	30000.0	3	1	30
MLS2 42000 EH/C 4m	42000	42	42000.0	30000.0	4	1	30

Item Naam kort	Gewicht voor 1m [kg]	Ca. gewicht lo. m [kg/m]
MLS2 1400 EH/C 1m	3.8	0.6
MLS2 1400 EH/C 2m	3.8	0.6
MLS2 1400 EH/C 3m	3.8	0.6
MLS2 1400 EH/C 4m	3.8	0.6
MLS2 2800 EH/C 1m	5.6	1
MLS2 2800 EH/C 2m	5.6	1
MLS2 2800 EH/C 3m	5.6	1
MLS2 2800 EH/C 4m	5.6	1
MLS2 4200 EH/C 1m	9	1.6
MLS2 4200 EH/C 2m	9	1.6
MLS2 4200 EH/C 3m	9	1.6
MLS2 4200 EH/C 4m	9	1.6
MLS2 5600 EH/C 1m	12.9	2
MLS2 5600 EH/C 2m	12.9	2
MLS2 5600 EH/C 3m	12.9	2



Item Naam kort	Gewicht voor 1m [kg]	Ca. gewicht lo. m [kg/m]
MLS2 5600 EH/C 4m	12.9	2
MLS2 7000 EH/C 1m	13.3	2.2
MLS2 7000 EH/C 2m	13.3	2.2
MLS2 7000 EH/C 3m	13.3	2.2
MLS2 7000 EH/C 4m	13.3	2.2
MLS2 8400 EH/C 1m	22.9	2.8
MLS2 8400 EH/C 2m	22.9	2.8
MLS2 8400 EH/C 3m	22.9	2.8
MLS2 8400 EH/C 4m	22.9	2.8
MLS2 11200 EH/C 1m	24.9	3.6
MLS2 11200 EH/C 2m	24.9	3.6
MLS2 11200 EH/C 3m	24.9	3.6
MLS2 11200 EH/C 4m	24.9	3.6
MLS2 14000 EH/C 1m	40	5
MLS2 14000 EH/C 2m	40	5
MLS2 14000 EH/C 3m	40	5
MLS2 14000 EH/C 4m	40	5
MLS2 21000 EH/C 1m	69	7
MLS2 21000 EH/C 2m	69	7
MLS2 21000 EH/C 3m	69	7
MLS2 21000 EH/C 4m	69	7
MLS2 28000 EH/C 1m	108	10
MLS2 28000 EH/C 2m	108	10
MLS2 28000 EH/C 3m	108	10
MLS2 28000 EH/C 4m	108	10
MLS2 35000 EH/C 1m	143	12
MLS2 35000 EH/C 2m	143	12
MLS2 35000 EH/C 3m	143	12
MLS2 35000 EH/C 4m	143	12
MLS2 42000 EH/C 1m	156	16
MLS2 42000 EH/C 2m	156	16
MLS2 42000 EH/C 3m	156	16
MLS2 42000 EH/C 4m	156	16



BESTELNUMMERS[Global Item Number/Local ERP Number SSNL]

WLL	1 m	2 m	3 m	4 m
1400 kg	2024703	2002860	2003330	2003331
2800 kg	2024704	2002862	2003332	2003333
4200 kg	2024705	2005924	2005925	2005926
5600 kg	2024706	2002865	2002866	2003336
7000 kg	2024707	2002868	2003338	2003339
8400 kg	2024708	2002870	2003340	2003341
11200 kg	2024709	2002872	2003342	2003343
14000 kg	2024710	2002874	2003344	2003345
21000 kg	2024711	2002876	2003346	2003347
28000 kg	2024712	2002878	2003348	2003349
35000 kg	2024713	2002880	2003350	2003351
42000 kg	2024714	2002882	2003352	2003353

- Normen EN 1492-2
- Hoofdmateriaal Polyester
- Temperatuurbereik -40°C / +100°C
- Verpakkingseenheid (PU) Inhoud 1

