

Rotating Eyebolt G100

Screwable Lifting Point 0.1t-12t, Steel Grade 100, anchorage point for load lifting



Item Name short	WLL kg [kg]	WLL t [t]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]
C807XHT-M6 0.1t	100	0.1	27	9.5	7	20	23
C807XHT-M8 0.3t	300	0.3	35	11	9	25	25.5
C807XHT-M10 0.4t	400	0.4	33.7	10	9.8	25	25.5
C807XHT-M12 0.75	750	0.75	41.5	12.5	11.5	30	30.6
C807XHT-M14 0.75	750	0.75	41.5	12.5	11.5	30	30.6
C807XHT-M16 1.5t	1500	1.5	49.5	14.5	15.7	35	36.5
C807XHT-M18 1.5t	1500	1.5	49.5	14.5	15.7	35	36.5
C807XHT-M20 2.3t	2300	2.3	58	16	18	40	42
C807XHT-M22 2.3t	2300	2.3	58	16	18	40	42
C807XHT-M24 3.2t	3200	3.2	69	20.5	22	49	50
C807XHT-M27 3.2t	3200	3.2	69	20.5	22	49	50
C807XHT-M30 4.5t	4500	4.5	86	25.5	28	60	66
C807XHT-M33 4.5t	4500	4.5	86	25.5	28	60	66
C807XHT-M36 7t	7000	7	105	32	30	74	77
C807XHT-M42 9t	9000	9	118	38	37	82	87
C807XHT-M48 12t	12000	12	137	43	38	95	102

Item Name short	L [mm]	M [mm]	Max tightening torque [Nm]	Weight Net [kg]
C807XHT-M6 0.1t	9	6	6	0.08
C807XHT-M8 0.3t	12	8	8	0.12
C807XHT-M10 0.4t	15	10	16	0.12
C807XHT-M12 0.75	18	12	25	0.2
C807XHT-M14 0.75	18	14	30	0.2
C807XHT-M16 1.5t	24	14	60	0.35
C807XHT-M18 1.5t	24	18	70	0.35
C807XHT-M20 2.3t	30	20	110	0.6
C807XHT-M22 2.3t	30	22	120	0.6
C807XHT-M24 3.2t	36	24	195	1
C807XHT-M27 3.2t	36	27	240	1
C807XHT-M30 4.5t	45	30	320	2



Item Name short	L [mm]	M [mm]	Max tightening torque [Nm]	Weight Net [kg]
C807XHT-M33 4.5t	45	33	350	2
C807XHT-M36 7t	55	36	585	3.4
C807XHT-M42 9t	65	42	920	5.7
C807XHT-M48 12t	72	48	1590	8.5



ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Dimension M	C807XHT-M6 0.1t	C807XHT-M8 0.3t	C807XHT-M10 0.4t	C807XHT-M12 0.75	C807XHT-M14 0.75	C807XHT-M16 1.5t	C807XHT-M18 1.5t	C807XHT-M20 2.3t	C807XHT-M22 2.3t	C807XHT-M24 3.2t	C807XHT-M27 3.2t
6 mm	2029854	-	-	-	-	-	-	-	-	-	-
8 mm	-	2029855	-	-	-	-	-	-	-	-	-
10 mm	-	-	2029856	-	-	-	-	-	-	-	-
12 mm	-	-	-	2029857	-	-	-	-	-	-	-
14 mm	-	-	-	-	2029858	2029859	-	-	-	-	-
18 mm	-	-	-	-	-	-	2029860	-	-	-	-
20 mm	-	-	-	-	-	-	-	2029861	-	-	-
22 mm	-	-	-	-	-	-	-	-	2029862	-	-
24 mm	-	-	-	-	-	-	-	-	-	2029863	-
27 mm	-	-	-	-	-	-	-	-	-	-	2029864
30 mm	-	-	-	-	-	-	-	-	-	-	-
33 mm	-	-	-	-	-	-	-	-	-	-	-
36 mm	-	-	-	-	-	-	-	-	-	-	-
42 mm	-	-	-	-	-	-	-	-	-	-	-
48 mm	-	-	-	-	-	-	-	-	-	-	-

Dimension M	C807XHT-M30 4.5t	C807XHT-M33 4.5t	C807XHT-M36 7t	C807XHT-M42 9t	C807XHT-M48 12t
6 mm	-	-	-	-	-
8 mm	-	-	-	-	-
10 mm	-	-	-	-	-
12 mm	-	-	-	-	-
14 mm	-	-	-	-	-
18 mm	-	-	-	-	-
20 mm	-	-	-	-	-
22 mm	-	-	-	-	-
24 mm	-	-	-	-	-
27 mm	-	-	-	-	-
30 mm	2029865	-	-	-	-
33 mm	-	2029866	-	-	-
36 mm	-	-	2029867	-	-
42 mm	-	-	-	2029868	-
48 mm	-	-	-	-	2029869



■ Grade	100
■ Main Material	Steel
■ Colour	Red
■ Packaging Unit (PU) Content	1

