

SecuFlex

Cut-resistant side and Abrasion resistant side flat sling

Item Name short	WLL kg [kg]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]
SecuFlex 1000 1m	1000	1	1	30	13
SecuFlex 1000 2m	1000	2	1	30	13
SecuFlex 1000 3m	1000	3	1	30	13
SecuFlex 1000 4m	1000	4	1	30	13
SecuFlex 1000 5m	1000	5	1	30	13
SecuFlex 1000 6m	1000	6	1	30	13
SecuFlex 1000 8m	1000	8	1	30	13
SecuFlex 2000 2m	2000	2	1	60	13
SecuFlex 2000 3m	2000	3	1	60	13
SecuFlex 2000 4m	2000	4	1	60	13
SecuFlex 2000 5m	2000	5	1	60	13
SecuFlex 2000 6m	2000	6	1	60	13
SecuFlex 2000 8m	2000	8	1	60	13
SecuFlex 3000 2m	3000	2	1.3	90	13
SecuFlex 3000 3m	3000	3	1.3	90	13
SecuFlex 3000 4m	3000	4	1.3	90	13
SecuFlex 3000 5m	3000	5	1.3	90	13
SecuFlex 3000 6m	3000	6	1.3	90	13
SecuFlex 3000 8m	3000	8	1.3	90	13
SecuFlex 4000 2m	4000	2	1.3	120	-
SecuFlex 4000 3m	4000	3	1.3	120	-
SecuFlex 4000 4m	4000	4	1.3	120	-
SecuFlex 4000 5m	4000	5	1.3	120	-
SecuFlex 4000 6m	4000	6	1.3	120	-
SecuFlex 4000 8m	4000	8	1.3	120	-
SecuFlex 5000 2m	5000	2	1.5	150	-
SecuFlex 5000 3m	5000	3	1.5	150	-
SecuFlex 5000 4m	5000	4	1.5	150	-
SecuFlex 5000 5m	5000	5	1.5	150	-
SecuFlex 5000 6m	5000	6	1.5	150	-
SecuFlex 5000 8m	5000	8	1.5	150	-
SecuFlex 6000 2m	6000	2	1.9	180	13



Item Name short	WLL kg [kg]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]
SecuFlex 6000 3m	6000	3	1.9	180	13
SecuFlex 6000 4m	6000	4	1.9	180	13
SecuFlex 6000 5m	6000	5	1.9	180	13
SecuFlex 6000 6m	6000	6	1.9	180	13
SecuFlex 6000 8m	6000	8	1.9	180	13
SecuFlex 8000 3m	8000	3	2.2	240	13
SecuFlex 8000 4m	8000	4	2.2	240	13
SecuFlex 8000 5m	8000	5	2.2	240	13
SecuFlex 8000 6m	8000	6	2.2	240	13
SecuFlex 8000 8m	8000	8	2.2	240	13
SecuFlex 10000 3m	10000	3	2.6	300	13
SecuFlex 10000 4m	10000	4	2.6	300	13
SecuFlex 10000 5m	10000	5	2.6	300	13
SecuFlex 10000 6m	10000	6	2.6	300	13
SecuFlex 10000 8m	10000	8	2.6	300	13

ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

WLL kg	1 m	2 m	3 m	4 m	5 m	6 m	8 m
1000 kg	2027168	2025156	2025157	2025158	2025159	2025160	2025161
2000 kg	-	2025162	2025163	2025164 B2000F4	2025165	2025166	2025167
3000 kg	-	2025168	2025169	2025170	2025171	2025172	2025173
4000 kg	-	2025174	2025175	2025176	2025177	2025178	2025179
5000 kg	-	2025180	2025181	2025182	2025183	2025184	2025185
6000 kg	-	2025186	2025187	2025188	2025189	2025190	2025191
8000 kg	-	-	2025192	2025193	2025194	2025196	2025197
10000 kg	-	-	2025198	2025199	2025201	2025202	2025203

■ Norms	EN 1492-1: 2000
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United
Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet
Certified
Safety**