

SecuFlex

Haute résistance à la coupure sur une face et protection contre l'abrasion sur l'autre face

Nom court de l'article	WLL [kg]	L1 [m]	L1 min. [m]	Largeur de la sangle B [mm]	Épaisseur de sangle [mm]
SecuFlex 1000 2m	1000	2	1	30	13
SecuFlex 1000 3m	1000	3	1	30	13
SecuFlex 1000 4m	1000	4	1	30	13
SecuFlex 1000 5m	1000	5	1	30	13
SecuFlex 1000 6m	1000	6	1	30	13
SecuFlex 2000 2m	2000	2	1	60	13
SecuFlex 2000 3m	2000	3	1	60	13
SecuFlex 2000 4m	2000	4	1	60	13
SecuFlex 2000 5m	2000	5	1	60	13
SecuFlex 2000 6m	2000	6	1	60	13
SecuFlex 2000 8m	2000	8	1	60	13
SecuFlex 3000 2m	3000	2	1.3	90	13
SecuFlex 3000 3m	3000	3	1.3	90	13
SecuFlex 3000 4m	3000	4	1.3	90	13
SecuFlex 3000 5m	3000	5	1.3	90	13
SecuFlex 3000 6m	3000	6	1.3	90	13
SecuFlex 4000 2m	4000	2	1.3	120	-
SecuFlex 4000 3m	4000	3	1.3	120	-
SecuFlex 4000 4m	4000	4	1.3	120	-
SecuFlex 4000 5m	4000	5	1.3	120	-
SecuFlex 4000 6m	4000	6	1.3	120	-
SecuFlex 5000 2m	5000	2	1.5	150	-
SecuFlex 5000 3m	5000	3	1.5	150	-
SecuFlex 5000 4m	5000	4	1.5	150	-
SecuFlex 5000 5m	5000	5	1.5	150	-
SecuFlex 5000 6m	5000	6	1.5	150	-
SecuFlex 6000 2m	6000	2	1.9	180	13
SecuFlex 6000 3m	6000	3	1.9	180	13
SecuFlex 6000 4m	6000	4	1.9	180	13
SecuFlex 6000 5m	6000	5	1.9	180	13
SecuFlex 6000 6m	6000	6	1.9	180	13



NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSCH]

WLL	2 m	3 m	4 m	5 m	6 m	8 m
1000 kg	2025156 B1000F2	2025157 B1000F3	2025158 B1000F4	2025159 B1000F5	2025160 B1000F6	-
2000 kg	2025162 B2000F2	2025163 B2000F3	2025164	2025165 B2000F5	2025166 B2000F6	2025167 B2000F8
3000 kg	2025168 B3000F2	2025169 B3000F3	2025170 B3000F4	2025171 B3000F5	2025172 B3000F6	-
4000 kg	2025174 B4000F2	2025175 B4000F3	2025176 B4000F4	2025177 B4000F5	2025178 B4000F6	-
5000 kg	2025180 B5000F2	2025181 B5000F3	2025182 B5000F4	2025183 B5000F5	2025184 B5000F6	-
6000 kg	2025186 B6000F2	2025187 B6000F3	2025188 B6000F4	2025189 B6000F5	2025190 B6000F6	-

- Normes EN 1492-1: 2000
- Matériel principal Polyester
- Plage de température -40°C / +100°C
- Protection d'étiquette Oui
- Contenu des unités d'emballage (UE) 1

