

Secutex S2

Cut-resistant full coated flat sling, Nearly indestructible!

Item Name short	WLL kg [kg]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]	Weight Net [kg]	Weight per Meter [kg/m]
PB 5000-S2 8m	5000	1.5	150	18.9	3.7	27.5	3.4
PB 6000-S2 8m	6000	1.9	180	19.1	4.4	31	3.8

Item Name short	Colour
PB 5000-S2 8m	Red
PB 6000-S2 8m	Brown



Loop + D-Ring



2x Rings



ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

WLL kg	8 m
5000 kg	2018503 2018503
6000 kg	2018504 2018504

■ Norms	EN 1492-1: 2000
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

SpanSet
Certified
Safety

■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

