



Secutex S2

Élingue plate avec revêtement protection contre les coupures des deux côtés

Nom court de l'article	WLL [kg]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Épaisseur de sangle [mm]	Poids pour 1m [kg]	Poids net [kg]
PB 1000-S2 2m	1000	2	1	30	17.1	0.9	0.9
PB 1000-S2 3m	1000	3	1	30	17.1	0.9	1.3
PB 1000-S2 4m	1000	4	1	30	17.1	0.9	1.7
PB 1000-S2 5m	1000	5	1	30	17.1	0.9	2.1
PB 2000-S2 2m	2000	2	1	60	17.5	1.4	2
PB 2000-S2 3m	2000	3	1	60	17.5	1.4	2.8
PB 2000-S2 4m	2000	4	1	60	17.5	1.4	3.6
PB 2000-S2 5m	2000	5	1	60	17.5	1.4	4.4
PB 3000-S2 2m	3000	2	1.3	90	17.9	2.1	2.9
PB 3000-S2 3m	3000	3	1.3	90	17.9	2.1	4.2
PB 3000-S2 4m	3000	4	1.3	90	17.9	2.1	5.5
PB 3000-S2 5m	3000	5	1.3	90	17.9	2.1	6.8
PB 4000-S2 2m	4000	2	1.3	120	18.9	2.9	4
PB 4000-S2 3m	4000	3	1.3	120	18.9	2.9	5.8
PB 4000-S2 4m	4000	4	1.3	120	18.9	2.9	7.6
PB 4000-S2 5m	4000	5	1.3	120	18.9	2.9	9.4

Nom court de l'article	Poids par mètre [kg/m]	Couleur
PB 1000-S2 2m	0.8	Violet
PB 1000-S2 3m	0.8	Violet
PB 1000-S2 4m	0.8	Violet
PB 1000-S2 5m	0.8	Violet
PB 2000-S2 2m	1.4	Vert
PB 2000-S2 3m	1.4	Vert
PB 2000-S2 4m	1.4	Vert
PB 2000-S2 5m	1.4	Vert
PB 3000-S2 2m	2	Jaune



Nom court de l'article	Poids par mètre [kg/m]	Couleur
PB 3000-S2 3m	2	Jaune
PB 3000-S2 4m	2	Jaune
PB 3000-S2 5m	2	Jaune
PB 4000-S2 2m	2.7	Gris
PB 4000-S2 3m	2.7	Gris
PB 4000-S2 4m	2.7	Gris
PB 4000-S2 5m	2.7	Gris

NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSFR]

WLL	2 m	3 m	4 m	5 m
1000 kg	2015425	2015426	2015427	2015428
2000 kg	2015430	2015431	2015432	2015433
3000 kg	2015436	2015437	2015438	2015439
4000 kg	2015442	2015443	2015444	2015445

■ Normes	EN 1492-1: 2000
■ Matériel principal	Polyester
■ Plage de température	-40°C / +100°C
■ Protection d'étiquette	Oui
■ Contenu des unités d'emballage (UE)	1

