

## Self-Retracting lanyard for work platforms

1.8m webbing lifeline with aluminium housing

| Item Name short           | Lifeline Length [m] | Anchor Connector | B [mm] | L [mm] | T [mm] | Weight Net [kg] | Temperature Range |
|---------------------------|---------------------|------------------|--------|--------|--------|-----------------|-------------------|
| Saverline MEWP SRL W 1.8m | 1.8                 | IKV35            | 84     | 240    | 61     | 0.96            | -40°C / +50° C    |

  

| Item Name short           | Temperature Range | Multilingual User Instruction Manual | Packaging Unit (PU) Content | Individually Serial Numbered | Individual Certificate | Lifespan [yr.] | Colour |
|---------------------------|-------------------|--------------------------------------|-----------------------------|------------------------------|------------------------|----------------|--------|
| Saverline MEWP SRL W 1.8m | -40°F / +120° F   | Yes                                  | 1                           | Yes                          | Yes                    | 10             | Red    |



## ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

| Lifeline Length | Saverline MEWP SRL W 1.8m |
|-----------------|---------------------------|
| 1.8 m           | 2002361                   |

|                    |              |
|--------------------|--------------|
| ■ Norms            | EN 360: 2002 |
| ■ Anchor Connector | IKV35        |
| ■ Colour           | Red          |
| ■ Lifeline Length  | 1.8 m        |
| ■ Weight Net       | 0.96 kg      |

**SpanSet Nederland B.V.**  
 Plaza 10A 4782 SK  
 Moerdijk Nederland  
 Tel.: +31 (0) 168 38 68 00  
 info@spanset.nl  
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet  
 Certified  
 Safety**

|                               |                 |
|-------------------------------|-----------------|
| ■ Temperature Range           | -40°C / +50° C  |
| ■ Temperature Range           | -40°F / +120° F |
| ■ Packaging Unit (PU) Content | 1               |

