




Self-Retracting Lifeline with Recovery Winch Function

Recovery device for work at height and confined space rescue applications

Item Name short	Lifeline Length [m]	B [mm]	D [mm]	L [mm]	T [mm]	W [mm]	Weight Net [kg]
SRLR S 12m	12	195	180	450	90	195	7
SRLR S 18m	18	240	200	570	210	240	11.5
SRLR S 24m	24	275	220	630	110	275	16
SRLR S 30m	30	315	230	640	112	315	21
SRLR S 40m	40	370	235	740	260	170	40
SRLR S 65m	65	390	240	780	240	390	43



ORDER NUMBERS[Global Item Number/Local ERP Number SSAU]

Lifeline Length	SRLR S 12m	SRLR S 18m	SRLR S 24m	SRLR S 30m	SRLR S 40m	SRLR S 65m
12 m	2002363 2002363	-	-	-	-	-
18 m	-	2002380 2002380	-	-	-	-
24 m	-	-	2002381 2002381	-	-	-
30 m	-	-	-	2002382 2002382	-	-
40 m	-	-	-	-	2002383 2002383	-
65 m	-	-	-	-	-	2002384 2002384

Standards

EN 1496: 2006 EN 360: 2002

SpanSet Australia Ltd
 150 Old Bathurst Road
 Emu Plains NSW 2750
 Australia
 +61 (02) 4735 3955
 sales@spanset.com.au
 www.spanset.com.au



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Australia Ltd

**SpanSet
 Certified
 Safety**

■ Harness Connector	IKV52
■ Main Material	Steel
■ Colour	Blue
■ Temperature Range	-40°C / +50° C
■ Temperature Range	-40°F / +120° F
■ Packaging Unit (PU) Content	1

