

Self-Retracting Steel Rope Lifeline with Plastic Housing

Robust plastic housing and galvanised steel rope are approved for vertical and horizontal use.



Item Name short	Lifeline Length [m]	Anchor Connector	Harness Connector	B [mm]	D [mm]	L [mm]	T [mm]
41-HWPS 6SP 51	6	65	65	165	80	420	80
41-HWPS 12SP 51	12	-	IKV 51	195	95	500	95
41-HWPS 18 51	18	-	IKV 51	220	-	540	970

Item Name short	W [mm]	Weight Net [kg]
41-HWPS 6SP 51	145	2.7
41-HWPS 12SP 51	195	4.7
41-HWPS 18 51	-	6.3

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Lifeline Length	41-HWPS 6SP 51	41-HWPS 12SP 51	41-HWPS 18 51
6 m	2002109	-	-
12 m	-	2002111	-
18 m	-	-	2002373

■ Norms

EN 360: 2002 ANSI Z359.14-2014

■ Harness Connector

IKV51

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
 Certified
 Safety**

■ Colour	Blue
■ Temperature Range	-40°C / +50° C
■ Temperature Range	-40°F / +120° F
■ Packaging Unit (PU) Content	1

