



Sewn-Eye Tow Strap

Designed to stretch, allowing a "shock absorbing" action which reduces shock loads that could damage vehicles or equipment.

Item Name short	Lashing Capacity [lbs]	Weight Net [lbs]	Length [ft.]	Width [in]
TS615	6000	2	15	2
TS620	6000	2	20	2
TS1215	12000	3	15	2
TS1220	12000	3.05	20	2
TS1225	12000	3.15	25	2
TS4524	15000	3.15	45	3
TS1820	18000	3.15	20	3
TS2430	24000	3.15	30	3

ORDER NUMBERS[Global Item Number/Local ERP Number SSUS]

Length	End Fitting Component	6000 lbs	12000 lbs	15000 lbs	18000 lbs	24000 lbs
15 ft.	 No hooks	2014627 TS615	2014630 TS1215	-	-	-
20 ft.	 No hooks	2014628 TS620	2014631 TS1220	-	2014639 TS1820	-
25 ft.	 No hooks	-	2014632 TS1225	-	-	-
30 ft.	 No hooks	-	-	-	-	2014642 TS2430
45 ft.	 No hooks	-	-	2026691 TS4524	-	-

- End Fitting Component Loop
- Temperature Range -40° C to + 50° C
- Temperature Range -40 °F to 120 °F
- Packaging Unit (PU) Content 1

SpanSet, Inc.
3125 Industrial Drive
Sanford, NC 27331
United States of
America
800-334-7505
info@spanset.com
www.spanset.com



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet, Inc. - USA

**SpanSet
Certified
Safety**