


SP150 Single Loop Back

Lanyard with working length adjustment loops - can be used for both fall prevention and fall arrest applications.



Item Name short	Lanyard Leg Type	Energy Absorbing	Maximum User Weight [kg]	Length [m]	Anchor Connector	Harness Connector	Main Material
SP150 S TL 2m 1DK2	Single Loop Back	Yes	150	2	1DK2	1DK2	High-performance polyester

Item Name short	Inspection Guide	Multilingual User Instruction Manual	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]	Colour
SP150 S TL 2m 1DK2	Yes	Yes	1	Yes	Yes	10	Blue



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Length



1DK2

2 m

2031322

■ Norms	EN 355: 2002
■ Anchor Connector	1DK2
■ Harness Connector	1DK2
■ Main Material	High-performance polyester
■ Colour	Blue
■ Energy Absorbing	Yes
■ Packaging Unit (PU) Content	1

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
 Certified
 Safety**