

SupraPlus

SupraPlus Rundschlinge aus Polyester



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
SupraPlus-X 0.5t 0.5m	500	0.5	0.5	0.5	38	4	0.1
SupraPlus-X 0.5t 0.75m	500	0.5	0.75	0.5	38	4	0.15
SupraPlus-X 0.5t 1m	500	0.5	1	0.5	38	4	0.2
SupraPlus-X 0.5t 1.5m	500	0.5	1.5	0.5	38	4	0.3
SupraPlus-X 0.5t 2.0m	500	0.5	2	0.5	38	4	0.4
SupraPlus-X 0.5t 2.5m	500	0.5	2.5	0.5	38	4	0.4
SupraPlus-X 0.5t 3.0m	500	0.5	3	0.5	38	4	0.4
SupraPlus-X 0.5t 5.0m	500	0.5	5	0.5	38	4	0.4
SupraPlus-X 1t 0.5m	1000	1	0.5	0.5	39	4	0.15
SupraPlus-X 1t 0.75m	1000	1	0.75	0.5	39	4	0.22
SupraPlus-X 1t 1m	1000	1	1	0.5	39	4	0.3
SupraPlus-X 1t 1.5m	1000	1	1.5	0.5	39	4	0.45
SupraPlus-X 1t 2m	1000	1	2	0.5	39	4	0.6
SupraPlus-X 1t 2.5m	1000	1	2.5	0.5	39	4	0.75
SupraPlus-X 1t 3m	1000	1	3	0.5	39	4	0.9
SupraPlus-X 1t 4m	1000	1	4	0.5	39	4	1.2
SupraPlus-X 1t 5m	1000	1	5	0.5	39	4	1.5
SupraPlus-X 1t 6m	1000	1	6	0.5	39	4	2.4
SupraPlus-X 1t 10m	1000	1	10	0.5	39	4	4



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
SupraPlus-X 2t 0.5m	2000	2	0.5	0.5	40	8	0.25
SupraPlus-X 2t 0.75m	2000	2	0.75	0.5	40	8	0.37
SupraPlus-X 2t 1m	2000	2	1	0.5	40	8	0.5
SupraPlus-X 2t 1.5m	2000	2	1.5	0.5	40	8	0.75
SupraPlus-X 2t 2m	2000	2	2	0.5	40	8	1
SupraPlus-X 2t 2.5m	2000	2	2.5	0.5	40	8	1.25
SupraPlus-X 2t 3m	2000	2	3	0.5	40	8	1.5
SupraPlus-X 2t 4m	2000	2	4	0.5	40	8	2
SupraPlus-X 2t 5m	2000	2	5	0.5	40	8	2.5
SupraPlus-X 2t 6m	2000	2	6	0.5	40	8	3
SupraPlus-X 3t 0.5m	3000	3	0.5	0.5	48	8	-
SupraPlus-X 3t 1m	3000	3	1	0.5	48	8	0.6
SupraPlus-X 3t 1.5m	3000	3	1.5	0.5	48	8	0.9
SupraPlus-X 3t 2m	3000	3	2	0.5	48	8	1.2
SupraPlus-X 3t 2.5m	3000	3	2.5	0.5	48	8	1.5
SupraPlus-X 3t 3m	3000	3	3	0.5	48	8	1.8
SupraPlus-X 3t 3.5m	3000	3	3.5	0.5	48	8	2
SupraPlus-X 3t 4m	3000	3	4	0.5	48	8	2.4
SupraPlus-X 3t 5m	3000	3	5	0.5	48	8	3.0
SupraPlus-X 3t 6m	3000	3	6	0.5	48	8	3.6



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
SupraPlus-X 4t 0.5m	4000	4	0.5	0.75	55	9	0.4
SupraPlus-X 4t 1m	4000	4	1	0.75	55	9	0.8
SupraPlus-X 4t 1.5m	4000	4	1.5	0.75	55	9	1.2
SupraPlus-X 4t 2m	4000	4	2	0.75	55	9	1.6
SupraPlus-X 4t 2.5m	4000	4	2.5	0.75	55	9	2
SupraPlus-X 4t 3m	4000	4	3	0.75	55	9	2.4
SupraPlus-X 4t 4m	4000	4	4	0.75	55	9	3.2
SupraPlus-X 4t 5m	4000	4	5	0.75	55	9	4
SupraPlus-X 4t 6m	4000	4	6	0.75	55	9	4.8
SupraPlus-X 4t 8m	4000	4	8	0.75	55	9	-
SupraPlus-X 5t 0.5m	5000	5	0.5	0.75	59	11	2
SupraPlus-X 5t 1m	5000	5	1	0.75	59	11	1
SupraPlus-X 5t 1.5m	5000	5	1.5	0.75	59	11	1.5
SupraPlus-X 5t 2m	5000	5	2	0.75	59	11	2
SupraPlus-X 5t 2.5m	5000	5	2.5	0.75	59	11	2.5
SupraPlus-X 5t 3m	5000	5	3	0.75	59	11	3
SupraPlus-X 5t 3.5m	5000	5	3.5	0.75	59	11	3.5
SupraPlus-X 5t 4m	5000	5	4	0.75	59	11	4
SupraPlus-X 5t 5m	5000	5	5	0.75	59	11	5
SupraPlus-X 5t 6m	5000	5	6	0.75	59	11	6



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
SupraPlus-X 6t 1m	6000	6	1	0.75	73	11	1.2
SupraPlus-X 6t 1.5m	6000	6	1.5	0.75	73	11	1.8
SupraPlus-X 6t 2m	6000	6	2	0.75	73	11	2.4
SupraPlus-X 6t 2.5m	6000	6	2.5	0.75	73	11	3
SupraPlus-X 6t 3m	6000	6	3	0.75	73	11	3.6
SupraPlus-X 6t 4m	6000	6	4	0.75	73	11	4.8
SupraPlus-X 6t 5m	6000	6	5	0.75	73	11	6
SupraPlus-X 6t 6m	6000	6	6	0.75	73	11	7.2
SupraPlus-X 8t 1m	8000	8	1	0.75	77	13	1.6
SupraPlus-X 8t 1.5m	8000	8	1.5	0.75	77	13	2.4
SupraPlus-X 8t 2m	8000	8	2	0.75	77	13	3.2
SupraPlus-X 8t 2.5m	8000	8	2.5	0.75	77	13	4
SupraPlus-X 8t 3m	8000	8	3	0.75	77	13	4.8
SupraPlus-X 8t 4m	8000	8	4	0.75	77	13	6.4
SupraPlus-X 8t 5m	8000	8	5	0.75	77	13	8
SupraPlus-X 8t 6m	8000	8	6	0.75	77	13	9.6

Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
SupraPlus-X 0.5t 0.5m	0.2	Olivgrün
SupraPlus-X 0.5t 0.75m	0.2	Olivgrün
SupraPlus-X 0.5t 1m	0.2	Olivgrün



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
SupraPlus-X 0.5t 1.5m	0.2	Olivgrün
SupraPlus-X 0.5t 2.0m	0.2	Olivgrün
SupraPlus-X 0.5t 2.5m	0.2	Olivgrün
SupraPlus-X 0.5t 3.0m	0.2	Olivgrün
SupraPlus-X 0.5t 5.0m	0.2	Olivgrün
SupraPlus-X 1t 0.5m	0.3	violett
SupraPlus-X 1t 0.75m	0.3	violett
SupraPlus-X 1t 1m	0.3	violett
SupraPlus-X 1t 1.5m	0.3	violett
SupraPlus-X 1t 2m	0.3	violett
SupraPlus-X 1t 2.5m	0.3	violett
SupraPlus-X 1t 3m	0.3	violett
SupraPlus-X 1t 4m	0.3	violett
SupraPlus-X 1t 5m	0.3	violett
SupraPlus-X 1t 6m	0.3	violett
SupraPlus-X 1t 10m	0.3	violett
SupraPlus-X 2t 0.5m	0.5	Grün
SupraPlus-X 2t 0.75m	0.5	Grün
SupraPlus-X 2t 1m	0.5	Grün
SupraPlus-X 2t 1.5m	0.5	Grün
SupraPlus-X 2t 2m	0.5	Grün
SupraPlus-X 2t 2.5m	0.5	Grün
SupraPlus-X 2t 3m	0.5	Grün
SupraPlus-X 2t 4m	0.5	Grün
SupraPlus-X 2t 5m	0.5	Grün
SupraPlus-X 2t 6m	0.5	Grün



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
SupraPlus-X 3t 0.5m	0.6	Gelb
SupraPlus-X 3t 1m	0.6	Gelb
SupraPlus-X 3t 1.5m	0.6	Gelb
SupraPlus-X 3t 2m	0.6	Gelb
SupraPlus-X 3t 2.5m	0.6	Gelb
SupraPlus-X 3t 3m	0.6	Gelb
SupraPlus-X 3t 3.5m	0.6	Gelb
SupraPlus-X 3t 4m	0.6	Gelb
SupraPlus-X 3t 5m	0.6	Gelb
SupraPlus-X 3t 6m	0.6	Gelb
SupraPlus-X 4t 0.5m	0.8	Grau
SupraPlus-X 4t 1m	0.8	Grau
SupraPlus-X 4t 1.5m	0.8	Grau
SupraPlus-X 4t 2m	0.8	Grau
SupraPlus-X 4t 2.5m	0.8	Grau
SupraPlus-X 4t 3m	0.8	Grau
SupraPlus-X 4t 4m	0.8	Grau
SupraPlus-X 4t 5m	0.8	Grau
SupraPlus-X 4t 6m	0.8	Grau
SupraPlus-X 4t 8m	0.8	Grau
SupraPlus-X 5t 0.5m	1.0	Rot
SupraPlus-X 5t 1m	1.0	Rot
SupraPlus-X 5t 1.5m	1.0	Rot
SupraPlus-X 5t 2m	1.0	Rot
SupraPlus-X 5t 2.5m	1.0	Rot
SupraPlus-X 5t 3m	1.0	Rot



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
SupraPlus-X 5t 3.5m	1.0	Rot
SupraPlus-X 5t 4m	1.0	Rot
SupraPlus-X 5t 5m	1.0	Rot
SupraPlus-X 5t 6m	1.0	Rot
SupraPlus-X 6t 1m	1.2	Braun
SupraPlus-X 6t 1.5m	1.2	Braun
SupraPlus-X 6t 2m	1.2	Braun
SupraPlus-X 6t 2.5m	1.2	Braun
SupraPlus-X 6t 3m	1.2	Braun
SupraPlus-X 6t 4m	1.2	Braun
SupraPlus-X 6t 5m	1.2	Braun
SupraPlus-X 6t 6m	1.2	Braun
SupraPlus-X 8t 1m	1.6	Blau
SupraPlus-X 8t 1.5m	1.6	Blau
SupraPlus-X 8t 2m	1.6	Blau
SupraPlus-X 8t 2.5m	1.6	Blau
SupraPlus-X 8t 3m	1.6	Blau
SupraPlus-X 8t 4m	1.6	Blau
SupraPlus-X 8t 5m	1.6	Blau
SupraPlus-X 8t 6m	1.6	Blau



BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

Länge L1	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5 m	2019184 EP005/0050	2019189 EP010/0050	2019198 EP020/0050	2027101 EP030/0050	2027104 EP040/0050	2027105 EP050/0050	-	-
0.75 m	2019185 EP005/0075	2019190 EP010/0075	2019199 EP020/0075	-	-	-	-	-
1 m	2019186 EP005/0100	2019191 EP010/0100	2019200 EP020/0100	2019208 EP030/0100	2024570 EP040/0100	2024811 EP050/0100	2024571 EP060/0100	2024816 EP080/0100
1.5 m	2019187 EP005/0150	2019192 EP010/0150	2019201 EP020/0150	2019209 EP030/0150	2024669 EP040/0150	2024812 EP050/0150	2024814 EP060/0150	2024817 EP080/0150
2 m	2019188 EP005/0200	2019193 EP010/0200	2019202 EP020/0200	2019210 EP030/0200	2019216 EP040/0200	2019222 EP050/0200	2022135 EP060/0200	2022140 EP080/0200
2.5 m	2027097 EP005/0250	2019194 EP010/0250	2019203 EP020/0250	2019211 EP030/0250	2019217 EP040/0250	2024813 EP050/0250	2024815 EP060/0250	2024818 EP080/0250
3 m	2027098 EP005/0300	2019195 EP010/0300	2019204 EP020/0300	2019212 EP030/0300	2019218 EP040/0300	2019223 EP050/0300	2022136 EP060/0300	2022141 EP080/0300
3.5 m	-	-	-	2027103 EP030/0350	-	2027106 EP050/0350	-	-
4 m	-	2019196 EP010/0400	2019205 EP020/0400	2019213 EP030/0400	2019219 EP040/0400	2019224 EP050/0400	2022137 EP060/0400	2022142 EP080/0400
5 m	2027099 EP005/0500	2019197 EP010/0500	2019206 EP020/0500	2019214 EP030/0500	2019220 EP040/0500	2019225 EP050/0500	2022138 EP060/0500	2022143 EP080/0500
6 m	-	2024660 EP010/0600	2019207 EP020/0600	2019215 EP030/0600	2019221 EP040/0600	2019226 EP050/0600	2022139 EP060/0600	2022144 EP080/0600
8 m	-	-	-	-	2024668 EP040/0800	-	-	-
10 m	-	2027100 EP010/1000	-	-	-	-	-	-

■ Normen	EN 1492-2: 2000
■ Hauptmaterial	Polyester
■ Temperaturbereich	- 40° / +100°C
■ Etikettenschutz	Ja
■ Verpackungseinheit (VPE) Inhalt	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

