

### SupraPlus-X

Eslinga de elevación duradera y compacta de alto rendimiento, con protecciones de funda y etiqueta para una larga vida útil



Nombre corto del ítem	CMU [kg]	CMU [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
SupraPlus-X 0.5t 0.5m	500	0.5	0.5	0.5	38	4	0.1
SupraPlus-X 0.5t 0.75m	500	0.5	0.75	0.5	38	4	0.15
SupraPlus-X 0.5t 1m	500	0.5	1	0.5	38	4	0.2
SupraPlus-X 0.5t 1.5m	500	0.5	1.5	0.5	38	4	0.3
SupraPlus-X 0.5t 2.0m	500	0.5	2	0.5	38	4	0.4
SupraPlus-X 0.5t 2.5m	500	0.5	2.5	0.5	38	4	0.4
SupraPlus-X 0.5t 3.0m	500	0.5	3	0.5	38	4	0.4
SupraPlus-X 0.5t 5.0m	500	0.5	5	0.5	38	4	0.4
SupraPlus-X 1t 0.5m	1000	1	0.5	0.5	39	4	0.15
SupraPlus-X 1t 0.75m	1000	1	0.75	0.5	39	4	0.22
SupraPlus-X 1t 1m	1000	1	1	0.5	39	4	0.3
SupraPlus-X 1t 1.5m	1000	1	1.5	0.5	39	4	0.45
SupraPlus-X 1t 2m	1000	1	2	0.5	39	4	0.6
SupraPlus-X 1t 2.5m	1000	1	2.5	0.5	39	4	0.75
SupraPlus-X 1t 3m	1000	1	3	0.5	39	4	0.9
SupraPlus-X 1t 4m	1000	1	4	0.5	39	4	1.2
SupraPlus-X 1t 5m	1000	1	5	0.5	39	4	1.5
SupraPlus-X 1t 6m	1000	1	6	0.5	39	4	2.4
SupraPlus-X 1t 10m	1000	1	10	0.5	39	4	4



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
SupraPlus-X 2t 0.5m	2000	2	0.5	0.5	40	8	0.25
SupraPlus-X 2t 0.75m	2000	2	0.75	0.5	40	8	0.37
SupraPlus-X 2t 1m	2000	2	1	0.5	40	8	0.5
SupraPlus-X 2t 1.5m	2000	2	1.5	0.5	40	8	0.75
SupraPlus-X 2t 2m	2000	2	2	0.5	40	8	1
SupraPlus-X 2t 2.5m	2000	2	2.5	0.5	40	8	1.25
SupraPlus-X 2t 3m	2000	2	3	0.5	40	8	1.5
SupraPlus-X 2t 4m	2000	2	4	0.5	40	8	2
SupraPlus-X 2t 5m	2000	2	5	0.5	40	8	2.5
SupraPlus-X 2t 6m	2000	2	6	0.5	40	8	3
SupraPlus-X 2t 7m	2000	2	7	0.5	40	8	-
Supra-Plus-X 2t 8m	2000	2	8	0.5	40	8	-
SupraPlus-X 3t 0.5m	3000	3	0.5	0.5	48	8	-
SupraPlus-X 3t 1m	3000	3	1	0.5	48	8	0.6
SupraPlus-X 3t 1.5m	3000	3	1.5	0.5	48	8	0.9
SupraPlus-X 3t 2m	3000	3	2	0.5	48	8	1.2
SupraPlus-X 3t 2.5m	3000	3	2.5	0.5	48	8	1.5
SupraPlus-X 3t 3m	3000	3	3	0.5	48	8	1.8
SupraPlus-X 3t 3.5m	3000	3	3.5	0.5	48	8	2
SupraPlus-X 3t 4m	3000	3	4	0.5	48	8	2.4



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
SupraPlus-X 3t 5m	3000	3	5	0.5	48	8	3.0
SupraPlus-X 3t 6m	3000	3	6	0.5	48	8	3.6
SupraPlus-X 3t 7m	3000	3	7	0.5	48	8	-
SupraPlus-X 3t 8m	3000	3	8	0.5	48	8	-
SupraPlus-X 4t 0.5m	4000	4	0.5	0.75	55	9	0.4
SupraPlus-X 4t 1m	4000	4	1	0.75	55	9	0.8
SupraPlus-X 4t 1.5m	4000	4	1.5	0.75	55	9	1.2
SupraPlus-X 4t 2m	4000	4	2	0.75	55	9	1.6
SupraPlus-X 4t 2.5m	4000	4	2.5	0.75	55	9	2
SupraPlus-X 4t 3m	4000	4	3	0.75	55	9	2.4
SupraPlus-X 4t 4m	4000	4	4	0.75	55	9	3.2
SupraPlus-X 4t 5m	4000	4	5	0.75	55	9	4
SupraPlus-X 4t 6m	4000	4	6	0.75	55	9	4.8
SupraPlus-X 4t 7m	4000	4	7	0.75	55	9	-
SupraPlus-X 4t 8m	4000	4	8	0.75	55	9	-
SupraPlus-X 5t 0.5m	5000	5	0.5	0.75	59	11	2
SupraPlus-X 5t 1m	5000	5	1	0.75	59	11	1
SupraPlus-X 5t 1.5m	5000	5	1.5	0.75	59	11	1.5
SupraPlus-X 5t 2m	5000	5	2	0.75	59	11	2
SupraPlus-X 5t 2.5m	5000	5	2.5	0.75	59	11	2.5



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
SupraPlus-X 5t 3m	5000	5	3	0.75	59	11	3
SupraPlus-X 5t 3.5m	5000	5	3.5	0.75	59	11	3.5
SupraPlus-X 5t 4m	5000	5	4	0.75	59	11	4
SupraPlus-X 5t 5m	5000	5	5	0.75	59	11	5
SupraPlus-X 5t 6m	5000	5	6	0.75	59	11	6
SupraPlus-X 5t 7m	5000	5	7	0.75	59	11	-
SupraPlus-X 6t 1m	6000	6	1	0.75	73	11	1.2
SupraPlus-X 6t 1.5m	6000	6	1.5	0.75	73	11	1.8
SupraPlus-X 6t 2m	6000	6	2	0.75	73	11	2.4
SupraPlus-X 6t 2.5m	6000	6	2.5	0.75	73	11	3
SupraPlus-X 6t 3m	6000	6	3	0.75	73	11	3.6
SupraPlus-X 6t 4m	6000	6	4	0.75	73	11	4.8
SupraPlus-X 6t 5m	6000	6	5	0.75	73	11	6
SupraPlus-X 6t 6m	6000	6	6	0.75	73	11	7.2
SupraPlus-X 6t 7m	6000	6	7	0.75	73	11	8.4
SupraPlus-X 6t 8m	6000	6	8	0.75	73	11	9.6
SupraPlus-X 8t 1m	8000	8	1	0.75	77	13	1.6
SupraPlus-X 8t 1.5m	8000	8	1.5	0.75	77	13	2.4
SupraPlus-X 8t 2m	8000	8	2	0.75	77	13	-
SupraPlus-X 8t 2.5m	8000	8	2.5	0.75	77	13	4



Nombre corto del ítem	CMU [kg]	CMU [t] [t]	L1 [m]	L1 min. [m]	Ancho de tejido bajo carga [mm]	Grosor bajo carga [mm]	Peso Neto [kg]
SupraPlus-X 8t 3m	8000	8	3	0.75	77	13	4.8
SupraPlus-X 8t 4m	8000	8	4	0.75	77	13	6.4
SupraPlus-X 8t 5m	8000	8	5	0.75	77	13	8
SupraPlus-X 8t 6m	8000	8	6	0.75	77	13	9.6
SupraPlus-X 8t 7m	8000	8	7	0.75	77	13	10.6
SupraPlus-X 8t 8m	8000	8	8	0.75	77	13	12

Nombre corto del ítem	Peso por metro [kg/m]	Color
SupraPlus-X 0.5t 0.5m	0.2	Oliva
SupraPlus-X 0.5t 0.75m	0.2	Oliva
SupraPlus-X 0.5t 1m	0.2	Oliva
SupraPlus-X 0.5t 1.5m	0.2	Oliva
SupraPlus-X 0.5t 2.0m	0.2	Oliva
SupraPlus-X 0.5t 2.5m	0.2	Oliva
SupraPlus-X 0.5t 3.0m	0.2	Oliva
SupraPlus-X 0.5t 5.0m	0.2	Oliva
SupraPlus-X 1t 0.5m	0.3	Morado
SupraPlus-X 1t 0.75m	0.3	Morado
SupraPlus-X 1t 1m	0.3	Morado
SupraPlus-X 1t 1.5m	0.3	Morado
SupraPlus-X 1t 2m	0.3	Morado
SupraPlus-X 1t 2.5m	0.3	Morado
SupraPlus-X 1t 3m	0.3	Morado
SupraPlus-X 1t 4m	0.3	Morado



Nombre corto del ítem	Peso por metro [kg/m]	Color
SupraPlus-X 1t 5m	0.3	Morado
SupraPlus-X 1t 6m	0.3	Morado
SupraPlus-X 1t 10m	0.3	Morado
SupraPlus-X 2t 0.5m	0.5	Verde
SupraPlus-X 2t 0.75m	0.5	Verde
SupraPlus-X 2t 1m	0.5	Verde
SupraPlus-X 2t 1.5m	0.5	Verde
SupraPlus-X 2t 2m	0.5	Verde
SupraPlus-X 2t 2.5m	0.5	Verde
SupraPlus-X 2t 3m	0.5	Verde
SupraPlus-X 2t 4m	0.5	Verde
SupraPlus-X 2t 5m	0.5	Verde
SupraPlus-X 2t 6m	0.5	Verde
SupraPlus-X 2t 7m	0.5	Verde
Supra-Plus-X 2t 8m	0.5	Verde
SupraPlus-X 3t 0.5m	0.6	Amarillo
SupraPlus-X 3t 1m	0.6	Amarillo
SupraPlus-X 3t 1.5m	0.6	Amarillo
SupraPlus-X 3t 2m	0.6	Amarillo
SupraPlus-X 3t 2.5m	0.6	Amarillo
SupraPlus-X 3t 3m	0.6	Amarillo
SupraPlus-X 3t 3.5m	0.6	Amarillo
SupraPlus-X 3t 4m	0.6	Amarillo
SupraPlus-X 3t 5m	0.6	Amarillo
SupraPlus-X 3t 6m	0.6	Amarillo
SupraPlus-X 3t 7m	0.6	Amarillo



Nombre corto del ítem	Peso por metro [kg/m]	Color
SupraPlus-X 3t 8m	0.6	Amarillo
SupraPlus-X 4t 0.5m	0.8	Grís
SupraPlus-X 4t 1m	0.8	Grís
SupraPlus-X 4t 1.5m	0.8	Grís
SupraPlus-X 4t 2m	0.8	Grís
SupraPlus-X 4t 2.5m	0.8	Grís
SupraPlus-X 4t 3m	0.8	Grís
SupraPlus-X 4t 4m	0.8	Grís
SupraPlus-X 4t 5m	0.8	Grís
SupraPlus-X 4t 6m	0.8	Grís
SupraPlus-X 4t 7m	0.8	Grís
SupraPlus-X 4t 8m	0.8	Grís
SupraPlus-X 5t 0.5m	1.0	Rojo
SupraPlus-X 5t 1m	1.0	Rojo
SupraPlus-X 5t 1.5m	1.0	Rojo
SupraPlus-X 5t 2m	1.0	Rojo
SupraPlus-X 5t 2.5m	1.0	Rojo
SupraPlus-X 5t 3m	1.0	Rojo
SupraPlus-X 5t 3.5m	1.0	Rojo
SupraPlus-X 5t 4m	1.0	Rojo
SupraPlus-X 5t 5m	1.0	Rojo
SupraPlus-X 5t 6m	1.0	Rojo
SupraPlus-X 5t 7m	1.0	Rojo
SupraPlus-X 6t 1m	1.2	Marrón
SupraPlus-X 6t 1.5m	1.2	Marrón
SupraPlus-X 6t 2m	1.2	Marrón



Nombre corto del ítem	Peso por metro [kg/m]	Color
SupraPlus-X 6t 2.5m	1.2	Marrón
SupraPlus-X 6t 3m	1.2	Marrón
SupraPlus-X 6t 4m	1.2	Marrón
SupraPlus-X 6t 5m	1.2	Marrón
SupraPlus-X 6t 6m	1.2	Marrón
SupraPlus-X 6t 7m	1.2	Marrón
SupraPlus-X 6t 8m	1.2	Marrón
SupraPlus-X 8t 1m	1.6	Azul
SupraPlus-X 8t 1.5m	1.6	Azul
SupraPlus-X 8t 2m	1.6	Azul
SupraPlus-X 8t 2.5m	1.6	Azul
SupraPlus-X 8t 3m	1.6	Azul
SupraPlus-X 8t 4m	1.6	Azul
SupraPlus-X 8t 5m	1.6	Azul
SupraPlus-X 8t 6m	1.6	Azul
SupraPlus-X 8t 7m	1.6	Azul
SupraPlus-X 8t 8m	1.6	Azul



### REFERENCIAS DE PEDIDO [Global Item Number/Local ERP Number SSES]

Dimensión L1	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5 m	2019184 RHS000000500501	2019189 RHS000001000501	2019198 RHS000002000501	2027101	2027104	2027105	-	-
0.75 m	2019185 RHS000000500701	2019190 RHS000001000701	2019199 RHS000002000701	-	-	-	-	-
1 m	2019186 RHS000000501001	2019191 RHS000001001001	2019200 RHS000002001001	2019208 RHS000003001001	2024570 RHS000004001001	2024811 RHS000005001001	2024571 RHS000006001001	2024816 RHS000008001001
1.5 m	2019187 RHS000000501501	2019192 RHS000001001501	2019201 RHS000002001501	2019209 RHS000003001501	2024669 RHS000004001501	2024812 RHS000005001501	2024814 RHS000006001501	2024817 RHS000008001501
2 m	2019188 RHS000000502001	2019193 RHS000001002001	2019202 RHS000002002001	2019210 RHS000003002001	2019216 RHS000004002001	2019222 RHS000005002001	2022135 RHS000006002001	2022140 RHS000008002001
2.5 m	2027097	2019194 RHS000001002501	2019203 RHS000002002501	2019211 RHS000003002501	2019217 RHS000004002501	2024813	2024815	2024818
3 m	2027098	2019195 RHS000001003001	2019204 RHS000002003001	2019212 RHS000003003001	2019218 RHS000004003001	2019223 RHS000005003001	2022136 RHS000006003001	2022141 RHS000008003001
3.5 m	-	-	-	2027103	-	2027106	-	-
4 m	-	2019196 RHS000001004001	2019205 RHS000002004001	2019213 RHS000003004001	2019219 RHS000004004001	2019224 RHS000005004001	2022137 RHS000006004001	2022142 RHS000008004001
5 m	2027099	2019197 RHS000001005001	2019206 RHS000002005001	2019214 RHS000003005001	2019220 RHS000004005001	2019225 RHS000005005001	2022138 RHS000006005001	2022143 RHS000008005001
6 m	-	2024660	2019207 RHS000002006001	2019215 RHS000003006001	2019221 RHS000004006001	2019226 RHS000005006001	2022139	2022144
7 m	-	-	2024663	2024665	2024667	2024670	2024672	2024819
8 m	-	-	2024664	2024666	2024668	-	2024673	2024820
10 m	-	2027100	-	-	-	-	-	-

- Normas EN 1492-2: 2000
- Material principal Poliéster
- Rango de temperatura - 40° / +100°C
- Protección de la etiqueta Si
- Unidad de embalaje (PU) Contiene 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

