

SupraPlus-X

Funi di sollevamento dal design resistente e compatto con etichetta protettiva, garantisce prestazioni affidabili e una durata prolungata



Nome articolo breve	WLL kg [kg]	WLL ton [t]	L1 [m]	L1 min. [m]	Larghezza parte a contatto sotto carico [mm]	Spessore sotto carico [mm]	Peso netto [kg]
SupraPlus-X 0.5t 0.5m	500	0.5	0.5	0.5	38	4	0.1
SupraPlus-X 0.5t 1m	500	0.5	1	0.5	38	4	0.2
SupraPlus-X 0.5t 2.0m	500	0.5	2	0.5	38	4	0.4
SupraPlus-X 1t 0.5m	1000	1	0.5	0.5	39	4	0.15
SupraPlus-X 1t 1m	1000	1	1	0.5	39	4	0.3
SupraPlus-X 1t 2m	1000	1	2	0.5	39	4	0.6
SupraPlus-X 1t 3m	1000	1	3	0.5	39	4	0.9
SupraPlus-X 1t 4m	1000	1	4	0.5	39	4	1.2
SupraPlus-X 1t 5m	1000	1	5	0.5	39	4	1.5
SupraPlus-X 2t 0.5m	2000	2	0.5	0.5	40	8	0.25
SupraPlus-X 2t 1m	2000	2	1	0.5	40	8	0.5
SupraPlus-X 2t 2m	2000	2	2	0.5	40	8	1
SupraPlus-X 2t 3m	2000	2	3	0.5	40	8	1.5
SupraPlus-X 2t 4m	2000	2	4	0.5	40	8	2
SupraPlus-X 2t 5m	2000	2	5	0.5	40	8	2.5
SupraPlus-X 2t 6m	2000	2	6	0.5	40	8	3
SupraPlus-X 3t 1m	3000	3	1	0.5	48	8	0.6
SupraPlus-X 3t 2m	3000	3	2	0.5	48	8	1.2
SupraPlus-X 3t 3m	3000	3	3	0.5	48	8	1.8



Nome articolo breve	WLL kg [kg]	WLL ton [t]	L1 [m]	L1 min. [m]	Larghezza parte a contatto sotto carico [mm]	Spessore sotto carico [mm]	Peso netto [kg]
SupraPlus-X 3t 4m	3000	3	4	0.5	48	8	2.4
SupraPlus-X 3t 5m	3000	3	5	0.5	48	8	3.0
SupraPlus-X 3t 6m	3000	3	6	0.5	48	8	3.6
SupraPlus-X 4t 1m	4000	4	1	0.75	55	9	0.8
SupraPlus-X 4t 2m	4000	4	2	0.75	55	9	1.6
SupraPlus-X 4t 3m	4000	4	3	0.75	55	9	2.4
SupraPlus-X 4t 4m	4000	4	4	0.75	55	9	3.2
SupraPlus-X 4t 5m	4000	4	5	0.75	55	9	4
SupraPlus-X 4t 6m	4000	4	6	0.75	55	9	4.8
SupraPlus-X 5t 1m	5000	5	1	0.75	59	11	1
SupraPlus-X 5t 2m	5000	5	2	0.75	59	11	2
SupraPlus-X 5t 3m	5000	5	3	0.75	59	11	3
SupraPlus-X 5t 4m	5000	5	4	0.75	59	11	4
SupraPlus-X 5t 5m	5000	5	5	0.75	59	11	5
SupraPlus-X 5t 6m	5000	5	6	0.75	59	11	6
SupraPlus-X 6t 1m	6000	6	1	0.75	73	11	1.2
SupraPlus-X 6t 2m	6000	6	2	0.75	73	11	2.4
SupraPlus-X 6t 3m	6000	6	3	0.75	73	11	3.6
SupraPlus-X 6t 4m	6000	6	4	0.75	73	11	4.8
SupraPlus-X 6t 5m	6000	6	5	0.75	73	11	6



Nome articolo breve	WLL kg [kg]	WLL ton [t]	L1 [m]	L1 min. [m]	Larghezza parte a contatto sotto carico [mm]	Spessore sotto carico [mm]	Peso netto [kg]
SupraPlus-X 6t 6m	6000	6	6	0.75	73	11	7.2
SupraPlus-X 8t 2m	8000	8	2	0.75	77	13	3.2
SupraPlus-X 8t 3m	8000	8	3	0.75	77	13	4.8
SupraPlus-X 8t 4m	8000	8	4	0.75	77	13	6.4
SupraPlus-X 8t 5m	8000	8	5	0.75	77	13	8
SupraPlus-X 8t 6m	8000	8	6	0.75	77	13	9.6

Nome articolo breve	Peso al metro [kg/m]	Colore
SupraPlus-X 0.5t 0.5m	0.2	Olivastro
SupraPlus-X 0.5t 1m	0.2	Olivastro
SupraPlus-X 0.5t 2.0m	0.2	Olivastro
SupraPlus-X 1t 0.5m	0.3	Viola
SupraPlus-X 1t 1m	0.3	Viola
SupraPlus-X 1t 2m	0.3	Viola
SupraPlus-X 1t 3m	0.3	Viola
SupraPlus-X 1t 4m	0.3	Viola
SupraPlus-X 1t 5m	0.3	Viola
SupraPlus-X 2t 0.5m	0.5	Verde
SupraPlus-X 2t 1m	0.5	Verde
SupraPlus-X 2t 2m	0.5	Verde
SupraPlus-X 2t 3m	0.5	Verde
SupraPlus-X 2t 4m	0.5	Verde
SupraPlus-X 2t 5m	0.5	Verde
SupraPlus-X 2t 6m	0.5	Verde



Nome articolo breve	Peso al metro [kg/m]	Colore
SupraPlus-X 3t 1m	0.6	Giallo
SupraPlus-X 3t 2m	0.6	Giallo
SupraPlus-X 3t 3m	0.6	Giallo
SupraPlus-X 3t 4m	0.6	Giallo
SupraPlus-X 3t 5m	0.6	Giallo
SupraPlus-X 3t 6m	0.6	Giallo
SupraPlus-X 4t 1m	0.8	Grigio
SupraPlus-X 4t 2m	0.8	Grigio
SupraPlus-X 4t 3m	0.8	Grigio
SupraPlus-X 4t 4m	0.8	Grigio
SupraPlus-X 4t 5m	0.8	Grigio
SupraPlus-X 4t 6m	0.8	Grigio
SupraPlus-X 5t 1m	1.0	Rosso
SupraPlus-X 5t 2m	1.0	Rosso
SupraPlus-X 5t 3m	1.0	Rosso
SupraPlus-X 5t 4m	1.0	Rosso
SupraPlus-X 5t 5m	1.0	Rosso
SupraPlus-X 5t 6m	1.0	Rosso
SupraPlus-X 6t 1m	1.2	Marrone
SupraPlus-X 6t 2m	1.2	Marrone
SupraPlus-X 6t 3m	1.2	Marrone
SupraPlus-X 6t 4m	1.2	Marrone
SupraPlus-X 6t 5m	1.2	Marrone
SupraPlus-X 6t 6m	1.2	Marrone
SupraPlus-X 8t 2m	1.6	Blu
SupraPlus-X 8t 3m	1.6	Blu



Nome articolo breve	Peso al metro [kg/m]	Colore
SupraPlus-X 8t 4m	1.6	Blu
SupraPlus-X 8t 5m	1.6	Blu
SupraPlus-X 8t 6m	1.6	Blu

ARTICOLO[Global Item Number/Local ERP Number SSIT]

Dimensione L1	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5 m	2019184 SUPRA0500-010	2019189 SUPRAX1000-010	2019198 SUPRAX2000-010	-	-	-	-	-
1 m	2019186 SUPRA0500-020	2019191 SUPRAX1000-020	2019200 SUPRAX2000-020	2019208 SUPRAX3000-020	2024570 SUPRAX4000-020	2024811 SUPRAX5000-020	2024571 SUPRA6000-020	-
2 m	2019188 SUPRAX500-040	2019193 SUPRAX1000-040	2019202 SUPRAX2000-040	2019210 SUPRAX3000-040	2019216 SUPRA4000-040	2019222 SUPRAX5000-040	2022135 SUPRA6000-040	2022140 SUPRAX8000-040
3 m	-	2019195 SUPRAX1000-060	2019204 SUPRAX2000-060	2019212 SUPRAX3000-060	2019218 SUPRAX4000-060	2019223 SUPRAX5000-060	2022136 SUPRAX6000-060	2022141 SUPRAX8000-060
4 m	-	2019196 SUPRAX1000-080	2019205 SUPRAX2000-080	2019213 SUPRAX3000-080	2019219 SUPRAX4000-080	2019224 SUPRAX5000-080	2022137 SUPRAX6000-080	2022142 SUPRAX8000-080
5 m	-	2019197 SUPRA1000-100	2019206 SUPRA2000-100	2019214 SUPRAX3000-100	2019220 SUPRAX4000-100	2019225 SUPRAX5000-100	2022138 SUPRAX6000-100	2022143 SUPRAX8000-100
6 m	-	-	2019207 SUPRAX2000-120	2019215 SUPRAX3000-120	2019221 SUPRAX4000-120	2019226 SUPRAX5000-120	2022139 SUPRAX6000-120	2022144 SUPRAX8000-120

■ Norme	EN 1492-2: 2000
■ Materiale principale	Poliestere
■ Intervallo di temperatura	- 40° / +100°C
■ Protezione dell'etichetta [y/n]	Sì
■ Packaging Unit (PU) Contenuto	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

