

SupraPlus®-X packaging unit 1

Durable and compact design lifting sling with protected label ensures reliable performance and extended service life



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
SupraPlus-X 0.5t 0.5m	500	0.5	0.5	0.5	38	4	0.1
SupraPlus-X 0.5t 0.75m	500	0.5	0.75	0.5	38	4	0.15
SupraPlus-X 0.5t 1m	500	0.5	1	0.5	38	4	0.2
SupraPlus-X 0.5t 1.5m	500	0.5	1.5	0.5	38	4	0.3
SupraPlus-X 0.5t 2.0m	500	0.5	2	0.5	38	4	0.4
SupraPlus-X 0.5t 2.5m	500	0.5	2.5	0.5	38	4	0.4
SupraPlus-X 0.5t 3.0m	500	0.5	3	0.5	38	4	0.4
SupraPlus-X 0.5t 5.0m	500	0.5	5	0.5	38	4	0.4
SupraPlus-X 1t 0.5m	1000	1	0.5	0.5	39	4	0.15
SupraPlus-X 1t 0.75m	1000	1	0.75	0.5	39	4	0.22
SupraPlus-X 1t 1m	1000	1	1	0.5	39	4	0.3
SupraPlus-X 1t 1.5m	1000	1	1.5	0.5	39	4	0.45
SupraPlus-X 1t 2m	1000	1	2	0.5	39	4	0.6
SupraPlus-X 1t 2.5m	1000	1	2.5	0.5	39	4	0.75
SupraPlus-X 1t 3m	1000	1	3	0.5	39	4	0.9
SupraPlus-X 1t 4m	1000	1	4	0.5	39	4	1.2
SupraPlus-X 1t 5m	1000	1	5	0.5	39	4	1.5
SupraPlus-X 2t 0.5m	2000	2	0.5	0.5	40	8	0.25
SupraPlus-X 2t 1m	2000	2	1	0.5	40	8	0.5



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
SupraPlus-X 2t 1.5m	2000	2	1.5	0.5	40	8	0.75
SupraPlus-X 2t 2m	2000	2	2	0.5	40	8	1
SupraPlus-X 2t 2.5m	2000	2	2.5	0.5	40	8	1.25
SupraPlus-X 2t 3m	2000	2	3	0.5	40	8	1.5
SupraPlus-X 2t 4m	2000	2	4	0.5	40	8	2
SupraPlus-X 2t 5m	2000	2	5	0.5	40	8	2.5
SupraPlus-X 2t 6m	2000	2	6	0.5	40	8	3
SupraPlus-X 3t 1m	3000	3	1	0.5	48	8	0.6
SupraPlus-X 3t 1.5m	3000	3	1.5	0.5	48	8	0.9
SupraPlus-X 3t 2m	3000	3	2	0.5	48	8	1.2
SupraPlus-X 3t 2.5m	3000	3	2.5	0.5	48	8	1.5
SupraPlus-X 3t 3m	3000	3	3	0.5	48	8	1.8
SupraPlus-X 3t 3.5m	3000	3	3.5	0.5	48	8	2
SupraPlus-X 3t 4m	3000	3	4	0.5	48	8	2.4
SupraPlus-X 3t 5m	3000	3	5	0.5	48	8	3.0
SupraPlus-X 3t 6m	3000	3	6	0.5	48	8	3.6
SupraPlus-X 4t 0.5m	4000	4	0.5	0.75	55	9	0.4
SupraPlus-X 4t 1m	4000	4	1	0.75	55	9	0.8
SupraPlus-X 4t 2m	4000	4	2	0.75	55	9	1.6
SupraPlus-X 4t 2.5m	4000	4	2.5	0.75	55	9	2



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
SupraPlus-X 4t 3m	4000	4	3	0.75	55	9	2.4
SupraPlus-X 4t 4m	4000	4	4	0.75	55	9	3.2
SupraPlus-X 4t 5m	4000	4	5	0.75	55	9	4
SupraPlus-X 4t 6m	4000	4	6	0.75	55	9	4.8
SupraPlus-X 5t 0.5m	5000	5	0.5	0.75	59	11	2
SupraPlus-X 5t 2m	5000	5	2	0.75	59	11	2
SupraPlus-X 5t 3m	5000	5	3	0.75	59	11	3
SupraPlus-X 5t 3.5m	5000	5	3.5	0.75	59	11	3.5
SupraPlus-X 5t 4m	5000	5	4	0.75	59	11	4
SupraPlus-X 5t 5m	5000	5	5	0.75	59	11	5
SupraPlus-X 5t 6m	5000	5	6	0.75	59	11	6
SupraPlus-X 6t 1m	6000	6	1	0.75	73	11	1.2
SupraPlus-X 6t 1.5m	6000	6	1.5	0.75	73	11	1.8
SupraPlus-X 6t 2m	6000	6	2	0.75	73	11	2.4
SupraPlus-X 6t 3m	6000	6	3	0.75	73	11	3.6
SupraPlus-X 6t 4m	6000	6	4	0.75	73	11	4.8
SupraPlus-X 6t 5m	6000	6	5	0.75	73	11	6
SupraPlus-X 8t 1m	8000	8	1	0.75	77	13	1.6
SupraPlus-X 8t 1.5m	8000	8	1.5	0.75	77	13	2.4
SupraPlus-X 8t 2m	8000	8	2	0.75	77	13	3.2



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Weight Net [kg]
SupraPlus-X 8t 3m	8000	8	3	0.75	77	13	4.8
SupraPlus-X 8t 4m	8000	8	4	0.75	77	13	6.4
SupraPlus-X 8t 5m	8000	8	5	0.75	77	13	8

Item Name short	Weight per Meter [kg/m]	Colour
SupraPlus-X 0.5t 0.5m	0.2	Olive
SupraPlus-X 0.5t 0.75m	0.2	Olive
SupraPlus-X 0.5t 1m	0.2	Olive
SupraPlus-X 0.5t 1.5m	0.2	Olive
SupraPlus-X 0.5t 2.0m	0.2	Olive
SupraPlus-X 0.5t 2.5m	0.2	Olive
SupraPlus-X 0.5t 3.0m	0.2	Olive
SupraPlus-X 0.5t 5.0m	0.2	Olive
SupraPlus-X 1t 0.5m	0.3	Purple
SupraPlus-X 1t 0.75m	0.3	Purple
SupraPlus-X 1t 1m	0.3	Purple
SupraPlus-X 1t 1.5m	0.3	Purple
SupraPlus-X 1t 2m	0.3	Purple
SupraPlus-X 1t 2.5m	0.3	Purple
SupraPlus-X 1t 3m	0.3	Purple
SupraPlus-X 1t 4m	0.3	Purple
SupraPlus-X 1t 5m	0.3	Purple
SupraPlus-X 2t 0.5m	0.5	Green
SupraPlus-X 2t 1m	0.5	Green
SupraPlus-X 2t 1.5m	0.5	Green



Item Name short	Weight per Meter [kg/m]	Colour
SupraPlus-X 2t 2m	0.5	Green
SupraPlus-X 2t 2.5m	0.5	Green
SupraPlus-X 2t 3m	0.5	Green
SupraPlus-X 2t 4m	0.5	Green
SupraPlus-X 2t 5m	0.5	Green
SupraPlus-X 2t 6m	0.5	Green
SupraPlus-X 3t 1m	0.6	Yellow
SupraPlus-X 3t 1.5m	0.6	Yellow
SupraPlus-X 3t 2m	0.6	Yellow
SupraPlus-X 3t 2.5m	0.6	Yellow
SupraPlus-X 3t 3m	0.6	Yellow
SupraPlus-X 3t 3.5m	0.6	Yellow
SupraPlus-X 3t 4m	0.6	Yellow
SupraPlus-X 3t 5m	0.6	Yellow
SupraPlus-X 3t 6m	0.6	Yellow
SupraPlus-X 4t 0.5m	0.8	Grey
SupraPlus-X 4t 1m	0.8	Grey
SupraPlus-X 4t 2m	0.8	Grey
SupraPlus-X 4t 2.5m	0.8	Grey
SupraPlus-X 4t 3m	0.8	Grey
SupraPlus-X 4t 4m	0.8	Grey
SupraPlus-X 4t 5m	0.8	Grey
SupraPlus-X 4t 6m	0.8	Grey
SupraPlus-X 5t 0.5m	1.0	Red
SupraPlus-X 5t 2m	1.0	Red
SupraPlus-X 5t 3m	1.0	Red



Item Name short	Weight per Meter [kg/m]	Colour
SupraPlus-X 5t 3.5m	1.0	Red
SupraPlus-X 5t 4m	1.0	Red
SupraPlus-X 5t 5m	1.0	Red
SupraPlus-X 5t 6m	1.0	Red
SupraPlus-X 6t 1m	1.2	Brown
SupraPlus-X 6t 1.5m	1.2	Brown
SupraPlus-X 6t 2m	1.2	Brown
SupraPlus-X 6t 3m	1.2	Brown
SupraPlus-X 6t 4m	1.2	Brown
SupraPlus-X 6t 5m	1.2	Brown
SupraPlus-X 8t 1m	1.6	Blue
SupraPlus-X 8t 1.5m	1.6	Blue
SupraPlus-X 8t 2m	1.6	Blue
SupraPlus-X 8t 3m	1.6	Blue
SupraPlus-X 8t 4m	1.6	Blue
SupraPlus-X 8t 5m	1.6	Blue



ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Dimension L1	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5 m	2019184 D083898	2019189 D083905	2019198 D083915	-	2027104	2027105 D086905	-	-
0.75 m	2019185 D083901	2019190 D083906	-	-	-	-	-	-
1 m	2019186 D083903	2019191 D083908	2019200 D083918	2019208 D083926	2024570	-	2024571 D084666	2024816 D084669
1.5 m	2019187 D083902	2019192 D083907	2019201 D083917	2019209 D083925	-	-	2024814 D084483	2024817 D083978
2 m	2019188 D083904	2019193 D083910	2019202 D083920	2019210 D083928	2019216 D083934	2019222 D083939	2022135 D082857	2022140 D082858
2.5 m	2027097	2019194 D083909	2019203 D083919	2019211 D083927	2019217 D083933	-	-	-
3 m	2027098	2019195 D083911	2019204 D083921	2019212 D083929	2019218 D083935	2019223 D083940	2022136 D083328	2022141 D083329
3.5 m	-	-	-	2027103	-	2027106 D084955	-	-
4 m	-	2019196 D083912	2019205 D083922	2019213 D083930	2019219 D083936	2019224 D083941	2022137 D084538	2022142 D084490
5 m	2027099	2019197 D083913	2019206 D083923	2019214 D083931	2019220 D083937	2019225 D083942	2022138 D084668	2022143 D084234
6 m	-	-	2019207 D083924	2019215 D083932	2019221 D083938	2019226 D083943	-	-

■ Norms	EN 1492-2: 2000
■ Main Material	Polyester
■ Temperature Range	- 40° / +100°C
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

